Jacksonville
Where Florida Begins.

Permittee:
Exact, Inc.
5285 Ramona Blvd.
Jacksonville, FL 32205-4414

Permit No.: 0310291-005-AO
Facility ID No.: 0310291
SIC Number: 3479
Project: Metal Finishing System

This permit is for the operation of a metal finishing system. This facility is located at 5285 Ramona Boulevard, Jacksonville, Duval County, FL 32205; UTM Coordinates: Zone 17, 429.150 km East and 3353.680 km North; Latitude: 30° 18' 52" North and Longitude: 81° 44' 13" West.

This permit is issued under the provisions of Chapter 403, Florida Statutes (F.S.) and Chapters 62-4, 62-204, 62-210, 62-212, 62-213, 62-296, and 62-297 Florida Administrative Code (F.A.C.). The permittee is hereby authorized to perform the work or operate the facility shown on the application and approved drawings, plans, and other documents, attached hereto or on file with the Environmental and Compliance Department, Environmental Quality Division (Permitting Authority) in accordance with the terms and conditions of this permit.

Renewal Application Due Date: **November 30, 2015**
Expiration Date: **January 31, 2016**

Environmental and Compliance Department
Environmental Quality Division

Robert Steven Pace, P.E., Manager
Air Quality Branch

RSP/CBJ

Section I. Facility Information

Subsection A. Facility/Project Description

This facility manufactures metal parts for the electronic and computer industry. The parts are pretreated then painted in a conveyorized finishing system.

The facility is a natural minor source of air pollution because the potential emissions of regulated air pollutants are less than 100 tons per year pursuant to Chapter 62-210, F.A.C., and Rule 2.301, Jacksonville Environmental Protection Board (JEPB).

Subsection B. Summary of Emission Unit (EU) ID Numbers, Brief Descriptions, and Control Devices

EU No.	EU Description	Control Device
001	Primer/Wash coat spray booth	Protectaire 88 ARC dry filter spray booth
002	Finish/Flat coat spray booth	Protectaire 88 ARC dry filter spray booth
003	Texture coat spray booth	Protectaire 88 ARC dry filter spray booth
004	Touch-up spray booth	Protectaire 88 ARC dry filter spray booth
005	Drying/curing oven	None

Subsection C. Relevant documents

Permit Number: 0310291-004-AO
Air operating permit application received January 3, 2011

Section II. Facility Wide Conditions

Subsection A. General Conditions

1. The terms, conditions, requirements, limitations and restrictions set forth in this permit, are "permit conditions" and are binding and enforceable pursuant to Sections 403.141, 403.727, or 403.859 through 403.861, F.S. The permittee is placed on notice that the Permitting Authority will review this permit periodically and may initiate enforcement action for any violation of these conditions.

2. This permit is valid only for the specific processes and operations applied for and indicated in the approved drawings or exhibits. Any unauthorized deviation from the approved drawings, exhibits, specifications, or conditions of this permit may constitute grounds for revocation and enforcement action by the Permitting Authority.

3. As provided in subsections 403.987(6) and 403.722(5), F.S., the issuance of this permit does not convey any vested rights or any exclusive privileges. Neither does it authorize any injury to public or private property or any invasion of personal rights, nor any infringement of federal, state, or local laws or regulations. This permit is not a waiver of or approval of any other Permitting Authority permit that may be required for other aspects of the total project which are not addressed in this permit.

4. This permit conveys no title to land or water, does not constitute State recognition or acknowledgment of title, and not constitute authority for the use of submerged lands unless herein provided and the necessary title or leasehold interests have been obtained from the State. Only the Trustees of the Internal Improvement Trust Fund may express State opinion as to title.

5. This permit does not relieve the permittee from liability for harm or injury to human health or welfare, animal, or plant life, or property caused by the construction or operation of this permitted source, or from penalties therefore; nor does it allow the permittee to cause pollution in contravention of Florida Statutes and Permitting Authority rules, unless specifically authorized by an order from the Permitting Authority.

6. The permittee shall properly operate and maintain the facility and systems of treatment and control (and related appurtenances) that are installed and used by the permittee to achieve compliance with the conditions of this permit, as required by Permitting Authority rules. This provision includes the operation of backup or auxiliary facilities or similar systems when necessary to achieve compliance with the conditions of the permit and when required by Permitting Authority rules.

7. The permittee, by accepting this permit, specifically agrees to allow authorized Permitting Authority personnel, upon presentation of credentials or other documents as may be required by law and at reasonable times, access to the premises where the permitted activity is located or conducted to:
   a. Have access to and copy any records that must be kept under conditions of the permit;
   b. Inspect the facility, equipment, practices, or operations regulated or required under this permit; and
   c. Sample or monitor any substances or parameters at any location reasonably necessary to assure compliance with this permit or Permitting Authority rules.

   Reasonable time may depend on the nature of the concern being investigated.

8. If, for any reason, the permittee does not comply with or will be unable to comply with any condition or limitation specified in this permit, the permittee shall immediately provide the Permitting Authority with the following information:
   a. A description of and cause of noncompliance; and
   b. The period of noncompliance, including dates and times; or, if not corrected, the anticipated time the noncompliance is expected to continue, and steps being taken to reduce, eliminate, and prevent recurrence of the noncompliance. The permittee shall be responsible for any and all damages which may result and may be subject to enforcement action by the Permitting Authority for penalties or for revocation of this permit.

9. In accepting this permit, the permittee understands and agrees that all records, notes, monitoring data and other information relating to the construction or operation of this permitted source which are submitted to the Permitting Authority may be used by the Permitting Authority as evidence in any enforcement case involving the permitted source arising under the Florida Statutes or Permitting Authority rules, except where such use is prescribed by Sections 403.111 and 403.73, F.S. Such evidence shall only be used to the extent it is consistent with the Florida Rules of Civil Procedure and appropriate evidentiary rules.

10. The permittee agrees to comply with changes in Permitting Authority rules and Florida Statutes after a reasonable time for compliance; provided, however, the permittee does not waive any other rights granted by Florida Statutes or Permitting Authority rules.

11. This permit is transferable only upon Permitting Authority approval in accordance with Rules 62-4.120 and 62-730.300, F.A.C., as applicable. The permittee shall be liable for any non-compliance of the permitted activity until the transfer is approved by the Permitting Authority.

12. This permit or a copy thereof shall be kept at the work site of the permitted activity.

13. This permit also constitutes:
    ( ) Determination of Best Available Control Technology (BACT)
    ( ) Determination of Prevention of Significant Deterioration (PSD)
    ( ) Compliance with New Source Performance Standards (NSPS)

14. The permittee shall comply with the following:
    a. Upon request, the permittee shall furnish all records and plans required under Permitting Authority rules. During enforcement actions, the retention period for all records will be extended automatically unless otherwise stipulated by the Permitting Authority.
    b. The permittee shall hold at the facility or other location designated by this permit records of all monitoring information (including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation) required by the permit, copies of all reports required by this permit, and records of all data used to complete the application for this permit. These materials shall be retained at least three years from the date of the sample, measurement, report, or application unless otherwise specified by Permitting Authority rule.
    c. Records of monitoring information shall include:
        1. The date, exact place, and time of sampling or measurements;
        2. The person responsible for performing the sampling or measurements;
        3. The dates analyses were performed;
        4. The person responsible for performing the analyses;
        5. The analytical techniques or methods used;
        6. The results of such analyses.

15. When requested by the Permitting Authority, the permittee shall within a reasonable time furnish any information required by law which is needed to determine compliance with the permit. If the permittee becomes aware the relevant facts were not submitted or were incorrect in the permit application or in any report to the Permitting Authority, such facts or information shall be corrected promptly.

[Rule 62-4.160, F.A.C., and Rule 2.1401, JEPB]

Subsection B. Specific Conditions

1. Any revision to an air permit or application shall be submitted to and approved by the Permitting Authority prior to implementation.
   [Rule 62-4.080(2), F.A.C., and Rule 2.1401, JEPB]

2. Prior to sixty (60) days before the expiration of this permit, the permittee shall apply for renewal of the permit using DEP form 62-210.900(4).
   [Rule 62-4.090, F.A.C., and Rule 2.1401, JEPB]

3. Within 30 days after the sale or legal transfer of a permitted facility, an "Application for Transfer of Air Permit" (DEP Form 62-210.900(7)) shall be submitted to the Permitting Authority. The application must be completed with the notarized signatures of both the permittee and the proposed new permittee.
   [Rule 62-4.120, F.A.C., and Rule 2.1401, JEPB]

4. The permittee shall immediately notify the Permitting Authority if the permittee is unable to comply with any of the conditions of this air permit.
   [Rule 62-4.130, F.A.C., and Rule 2.1401, JEPB]

5. The permittee shall obtain an air construction permit prior to the beginning of construction, reconstruction or modification of the facility, emission unit or the addition of air pollution control equipment.
[Rule 62-210.300(1)(a), F.A.C., and Rule 2.301, JEPB]

6. The permittee shall notify the Permitting Authority in writing of minor corrections or amendments to information contained in an air permit. Such minor corrections or amendments shall include:
   (a) Typographical errors noted in the permit
   (b) Name, address or phone number change from that in the permit
   (c) A change requiring more frequent monitoring or reporting by the permittee
   (d) A change in ownership or operational control of a facility
[Rule 62-210.360, F.A.C., and Rule 2.301, JEPB]

7. The permittee shall complete an "Annual Operating Report for Air Pollutant Emitting Facility" (DEP Form No. 62-210.900(5)) each year. The annual operating report shall be submitted to the Permitting Authority no later than April 1st of the following year.
[Rule 62-210.370(3), F.A.C., and Rule 2.301, JEPB]

8. The permittee shall not circumvent any air pollution control device, or allow the emission of air pollutants without the applicable air pollution control device operating properly.
[Rule 62-210.650, F.A.C., and Rule 2.301, JEPB]

9. The permittee shall not cause, suffer, allow, or permit the discharge of air pollutants which cause or contribute to an objectionable odor.
[Rule 62-296.320(2), F.A.C., and Rule 2.1101, JEPB]

10. The permittee shall not cause, let, permit, suffer or allow to be discharged into the atmosphere the emissions of air pollutants from any activity, the density of which is equal to or greater than 20 percent opacity.
[Rule 62-296.320(4)(b)1, F.A.C., and Rule 2.1101, JEPB]

11. The permittee shall conduct emission testing with the EU operating at permitted capacity. Permitted capacity is defined as 90-100 percent of the maximum operating rate allowed by the air permit. If it is impractical to test at permitted capacity, then the EU may be tested at less than capacity; in this case subsequent EU operation is limited to 110 percent of the test load until a new test is conducted. Once the EU is so limited, operation at higher capacities is allowed for no more than 15 consecutive days solely for the purposes of additional compliance testing to regain the permitted capacity in the air permit.
[Rule 62-297.310(2), F.A.C., and Rule 2.1201, JEPB]

12. The permittee shall provide stack sampling facilities, upon Permitting Authority request, with a method of access that is safe and readily accessible in accordance with OSHA standards (29CFR1910, Subparts D and E). Permanent sampling facilities are not required.
[Rule 62-297.310(6), F.A.C., and Rule 2.1201, JEPB]

13. The permittee shall notify the Permitting Authority at least fifteen (15) days prior to EU compliance testing.
[Rule 62-297.310(7)(a)9, F.A.C, and Rule 2.1201, JEPB]

14. The permittee shall file a report with the Permitting Authority on the results of each compliance test as soon as practical but no later than forty-five (45) days after completion of testing.
[Rule 62-297.310(8), F.A.C., and Rule 2.1201, JEPB]

15. The permittee shall submit all compliance related notifications and reports required by this air permit to:

Environmental and Compliance Department
Environmental Quality Division
407 North Laura Street, Third Floor
Jacksonville, FL 32202
Telephone: (904) 255-7100
Fax: (904) 588-0518

Section III. Emission Units and Conditions

Emission Unit 001 - Primer/Wash coat spray booth

Emission Unit Description – Primer/Wash coat spray booth

Control Device – Protectaire 88 ARC dry filter spray booth

Essential Potential to Emit (PTE) Parameters

1. Coating and solvent usage is limited to a maximum of 6739.2 gallons per year (total of EU's 001, 002, 003, and 004).
[Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

2. This emission unit is permitted to perform coating applications for no more than 4992 hours per year.
[Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

Emission Limitations and Standards

3. The spray booth shall not be operated unless all exhaust air passes through the dry filter.
[Rule 62-210.650, F.A.C., and Rule 2.301, JEPB]

4. The volatile organic compound (VOC) content of coating (as applied) shall not exceed 3.5 pounds per gallon of coating, excluding water.
[Rule 62-296.513(2)(a)2, F.A.C., and Rule 2.1101, JEPB]

Test Methods and Procedures

5. Testing for demonstration of compliance for VOC shall be performed in accordance with EPA Reference Method (RM) 24 (as described in 40 CFR 60, Appendix A).
[Rule 62-296.513(4), F.A.C. and Rule 2.1101, JEPB]

6. Manufacturers' data sheets showing VOC content may be substituted for VOC testing with the approval of the Permitting Authority.
[Rule 62-296.500(2)(b)4, F.A.C., and Rule 2.1101, JEPB]

Recordkeeping and Reporting Requirements

7. Records shall be maintained daily for the following:
   a. Gallons of coating(s) applied
   b. VOC content (lbs/gal) of coating as applied
   c. Gallons of solvent / thinner usage
   d. VOC content (lbs/gal) of solvent / thinner
   e. Total VOC emissions

   Records shall be retained for a minimum of two (2) years and made available to the Permitting Authority upon request.
   [Rule 62-296.500(2)(b)1, F.A.C. and Rule 2.1101, JEPB]

Emission Unit 002 - Finish/Flat coat spray booth

Emission Unit Description – Finish/Flat coat spray booth

Control Device – Protectaire 88 ARC dry filter spray booth

Essential Potential to Emit (PTE) Parameters

1. Coating and solvent usage is limited to a maximum of 6739.2 gallons per year (total of EU's 001, 002, 003, and 004).
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

2. This emission unit is permitted to perform coating applications for no more than 4992 hours per year.
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

Emission Limitations and Standards

3. The spray booth shall not be operated unless all exhaust air passes through the dry filter.
   [Rule 62-210.650, F.A.C., and Rule 2.301, JEPB]

4. The volatile organic compound (VOC) content of coating (as applied) shall not exceed 3.5 pounds per gallon of coating, excluding water.
   [Rule 62-296.513(2)(a)2, F.A.C., and Rule 2.1101, JEPB]

Test Methods and Procedures

5. Testing for demonstration of compliance for VOC shall be performed in accordance with EPA Reference Method (RM) 24 (as described in 40 CFR 60, Appendix A).
   [Rule 62-296.513(4), F.A.C. and Rule 2.1101, JEPB]

6. Manufacturers' data sheets showing VOC content may be substituted for VOC testing with the approval of the Permitting Authority.
   [Rule 62-296.500(2)(b)4, F.A.C., and Rule 2.1101, JEPB]

Recordkeeping and Reporting Requirements

7. Records shall be maintained daily for the following:
   a. Gallons of coating(s) applied
   b. VOC content (lbs/gal) of coating as applied
   c. Gallons of solvent / thinner usage
   d. VOC content (lbs/gal) of solvent / thinner
   e. Total VOC emissions

   Records shall be retained for a minimum of two (2) years and made available to the Permitting Authority upon request.
   [Rule 62-296.500(2)(b)1, F.A.C. and Rule 2.1101, JEPB]

Emission Unit 003 - Texture coat spray booth

Emission Unit Description – Texture coat spray booth

Control Device – Protectaire 88 ARC dry filter spray booth

Essential Potential to Emit (PTE) Parameters

1. Coating and solvent usage is limited to a maximum of 6739.2 gallons per year (total of EU's 001, 002, 003, and 004).
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

2. This emission unit is permitted to perform coating applications for no more than 4992 hours per year.
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

Emission Limitations and Standards

3. The spray booth shall not be operated unless all exhaust air passes through the dry filter.
   [Rule 62-210.650, F.A.C., and Rule 2.301, JEPB]

4. The volatile organic compound (VOC) content of coating (as applied) shall not exceed 3.5 pounds per gallon of coating, excluding water.
   [Rule 62-296.513(2)(a)2, F.A.C., and Rule 2.1101, JEPB]

Test Methods and Procedures

5. Testing for demonstration of compliance for VOC shall be performed in accordance with EPA Reference Method (RM) 24 (as described in 40 CFR 60, Appendix A).
   [Rule 62-296.513(4), F.A.C. and Rule 2.1101, JEPB]

6. Manufacturers' data sheets showing VOC content may be substituted for VOC testing with the approval of the Permitting Authority.
   [Rule 62-296.500(2)(b)4, F.A.C., and Rule 2.1101, JEPB]

Recordkeeping and Reporting Requirements

7. Records shall be maintained daily for the following:
   a. Gallons of coating(s) applied
   b. VOC content (lbs/gal) of coating as applied
   c. Gallons of solvent / thinner usage
   d. VOC content (lbs/gal) of solvent / thinner
   e. Total VOC emissions

   Records shall be retained for a minimum of two (2) years and made available to the Permitting Authority upon request.
   [Rule 62-296.500(2)(b)1, F.A.C. and Rule 2.1101, JEPB]

Emission Unit 004 - Touch-up spray booth

Emission Unit Description – Touch-up coat spray booth

Control Device – Protectaire 88 ARC dry filter spray booth

Essential Potential to Emit (PTE) Parameters

1. Coating and solvent usage is limited to a maximum of 6739.2 gallons per year (total of EU's 001, 002, 003, and 004).
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

2. This emission unit is permitted to perform coating applications for no more than 4992 hours per year.
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

Emission Limitations and Standards

3. The spray booth shall not be operated unless all exhaust air passes through the dry filter.
   [Rule 62-210.650, F.A.C., and Rule 2.301, JEPB]

4. The volatile organic compound (VOC) content of coating (as applied) shall not exceed 3.5 pounds per gallon of coating, excluding water.
   [Rule 62-296.513(2)(a)2, F.A.C., and Rule 2.1101, JEPB]

Test Methods and Procedures

5. Testing for demonstration of compliance for VOC shall be performed in accordance with EPA Reference Method (RM) 24 (as described in 40 CFR 60, Appendix A).
   [Rule 62-296.513(4), F.A.C. and Rule 2.1101, JEPB]

6. Manufacturers' data sheets showing VOC content may be substituted for VOC testing with the approval of the Permitting Authority.
   [Rule 62-296.500(2)(b)4, F.A.C., and Rule 2.1101, JEPB]

Recordkeeping and Reporting Requirements

7. Records shall be maintained daily for the following:
   a. Gallons of coating(s) applied
   b. VOC content (lbs/gal) of coating as applied
   c. Gallons of solvent / thinner usage
   d. VOC content (lbs/gal) of solvent / thinner
   e. Total VOC emissions

   Records shall be retained for a minimum of two (2) years and made available to the Permitting Authority upon request.
   [Rule 62-296.500(2)(b)1, F.A.C. and Rule 2.1101, JEPB]

Emission Unit 005 - Drying/Curing oven

Emission Unit Description – Three pass combination dry-off and cure oven

Control Device – None

Essential Potential to Emit (PTE) Parameters

1. The maximum heat input rate is limited to 2.0 MMBtu per hour (0.002 million cubic feet per hour of natural gas).
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

2. This emission unit is permitted to operate 4992 hours/year.
   [Rule 62-210.200(PTE), F.A.C., and Rule 2.301, JEPB]

Emission Limitations and Standards

3. Visible Emissions (VE) shall not exceed 5% opacity except that VE not exceeding 15% opacity are allowed for up to six (6) minutes in any one (1) hour period.
   [Rule 62-296.401(1)(a), F.A.C., and Rule 2.1101, JEPB]

Test Methods and Procedures

4. Testing for the demonstration of compliance shall be performed in accordance with EPA Reference Method (RM) 9 for the visual determination of opacity.
   [Rule 62-296.401(1)(b), F.A.C., and Rule 2.1101, JEPB]

5. The required minimum period of observation for the compliance test shall be sixty (60) minutes.
   [Rule 62-297.310(4)(a)2, F.A.C., and Rule 2.1201, JEPB]

6. Testing for the demonstration of compliance shall be performed five (5) years from the date of May 1, 2010.
   [Rule 62-297.310(7)(a)4, F.A.C., and Rule 2.1201, JEPB]