To:

A.4. Fuel Types and Usage. The facility may operate using fuel oil or "on-spec" used oil with a maximum sulfur content of 1.0 percent by weight, or alternatively, may operate using natural gas. Total combined fuel oil consumption for the asphalt concrete plant, asphalt heater and portable RAP crusher shall not exceed the Title V exemption limit of 1.2 MM gallons in any consecutive 12-month period. The owner shall maintain records to demonstrate that each shipment of fuel oil has 1.0 percent or less sulfur and that the sulfur content was determined by ASTM methods ASTM D4057-88 and ASTM D129-91, ASTM D2622-94 or ASTM D4294- 90, adopted and incorporated by reference in Rule 62- 297.440(1), F.A.C., or updated versions of the referenced ASTM methods approved by the Department. [Rules 62-210.300(3)(c)2.b and c, F.A.C., and permit 7775118-007-AC]

All other specific conditions of the permit remain in effect. This letter shall be attached to and made a part of permit 7775118-008-AO.

If you have any questions, please contact Maria J. Irizarry at 850/595-0670 or e-mail maria.irizarry@dep.state.fl.us.

Sincerely,

Rick Bradburn
Air Program Administrator

Enclosure
c: Tammy Reed; Koogler & Associates: treed@kooglerassociates.com
Joseph Shuler, C. W. Roberts: jshuler@cwrcontracting.com