

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)				
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO:				
AIRS ID#: 0250686 DA 7	ΓΕ: <u>1/28/2010</u>	ARRIVE: <u>10:44 AM</u> DEPART: <u>11:30 AM</u>				
FACILITY NAME: SSS OF AMERICAS DRY CLEANER						
FACILITY LOCATION: 3980 W 12th AVE						
	HIALEAH 33012	2-4105				
OWNER/AUTHORIZE	D REPRESENTATIVE:	ROLANDO ALVAREZ PHONE: (305)824-4996				
CONTACT NAME:		PHONE:				
ENTITLEMENT PERIOD: 1/19/2008 / 1/19/2013 (effective date) (end date)						
PART I: INSPECTION	COMPLIANCE STATUS	§ (check ☑ only one box)				
☐ IN COMPLIANO	CE MINOR Non-Co	OMPLIANCE SIGNIFICANT Non-COMPLIANCE				
	LASSIFICATION - Rule	62-213.300 FAC				
(check ⊻ onl	y one box in A)					
A. 1. Existing smal	l <u>area source</u> ly, x < 140 gal/yr	2. New small area source dry-to-dry only, x < 140 gal/yr				
transfer only,	x < 200 gal/yr	transfer only, x < 200 gal/yr				
both types, x - (constructed b	< 140 gal/yr before 12/9/91)	both types, x < 140 gal/yr (constructed on or after 12/9/91)				
,	,					
3. Existing large dry-to-dry only	e area source ly, 140 < x < 2,100 gal/yr	4. New large area source dry-to-dry only, $140 \le x \le 2{,}100 \text{ gal/yr}$				
transfer only,	$200 \le x \le 1,800 \text{ gal/yr}$	transfer only, $200 \le x \le 1,800 \text{ gal/yr}$				
	$0 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91$)	both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)				
5. Ineligible for	General Permit					
drop store/out	General Permit of business/petroleum ds above limits					

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ on	lly one box			
Do	es the responsible official of the dry cleaning facility:	for each qu	uestion)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □N	No No/A			
2.	Examine the containers for leakage?	□Yes □	No N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □	No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □	No N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □	No 🛭 N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)					
	1. If the facility classification is a Existing small area source , no controls are requi	red. Proceed	l to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.					
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993					
	4. If the facility classification is a <u>New large area source</u> , the machine should be eccondenser. Complete both sections A and B below.	uippeu wiiii a	a tettigerateu			
A.	Has the responsible official of all <u>existing large area & new sources</u> :	(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □	No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes □	No No/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes □1	No No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes □	No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	□Yes □1	No No/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □1	No			

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No				
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A				
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A				
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A				
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A				
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A				
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A				
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A				
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC					
Does the responsible official:	(check ✓ only one box for each question)				
1. Maintain receipts for perc purchased?	Yes No				
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No				
3. Maintain leak detection inspection and repair reports for the following:					
a) da accesa atati a a afilia la accesi a di accioni 24 la aggiorni					
a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A				
b) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	-				
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days					
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	 ☐ Yes ☐ No ☑ N/A ☐ Yes ☐ No ☑ N/A 				
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 	 ☐ Yes ☐ No ☐ No ☐ No ☐ No ☐ No ☐ No 				
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations?	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A Yes □ No 				
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	Yes No N/A Yes No N/A Yes No N/A Yes No Yes No Yes No				
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?		
2. Does the facility maintain a leak log?	Yes No	
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves		
4. Which method(s) of detection (is/are) used by the responsible official?		
a) Visual examination (condensed solvent on exterior surfaces)		
**If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-500 pc. 2) Calibrated against a standard gas prior to and after each use (PID/FII and a standard gas prior to an a weekly basis?	ppm? 1) Yes No ID only)? 2) Yes No 3) Yes No 4) Yes No	
FRANK DELGADO	1/28/2010	
Inspector's Name (Please Print)	Date of Inspection	
1/2	2011	
Inspector's Signature	Approximate Date of Next Inspection	
COMMENTS: ALL RECORDS WERE UP-TO-DATE. NO LEAKS WERE FOUND.		