WORK WOTECTION
San Martin
FLORIDA

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D ARMS COMPLA	DISCOVERY (CI)
AIRS ID#: 0694808 DATE: <u>2/26/14</u>	ARRIVE: <u>12:22</u>	DEPART: <u>13:03</u>
FACILITY NAME: PUGH'S DRY CLEANERS		
FACILITY LOCATION: 215 S. BAY STREET		
EUSTIS 32726		
OWNER/AUTHORIZED REPRESENTATIVE: ROBI Email: REOcleanersinc@aol.com CONTACT NAME: BRETT OWENS Email: ENTITLEMENT PERIOD: 6/9/2012 / 6/9/2017 (effective date) (end date)	ERT OWENS	PHONE: (352)357-3104 Mobile: (352)551-8592 PHONE: (352)357-3104 Mobile: (352)551-0317
PART I: INSPECTION COMPLIANCE STATUS (che	eck 🗹 only one box)
IN COMPLIANCE MINOR Non-COMPI	LIANCE SIG	SNIFICANT Non-COMPLIANCE
PART II: <u>FACILITY CLASSIFICATION</u> - Rule 62-2 (check I only one box in A)	213.300 FAC	
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)3. Existing large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)5. Ineligible for General Permit \Box d rop store/out of business/petroleum / facility exceeds above limits	transfer only, both types, x (constructed of 4. New large are dry-to-dry onl transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)

B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry cleaning facility was 90.00 gallons.

			<u> </u>	
PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC		·	(check 🗹 🛛	2
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	- 🛛	Yes	🗌 No	N/A
2. Are all perc. containers leak free ?	🛛	Yes	🗌 No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	🛛	Yes	🗌 No	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	🖂	Yes	🗌 No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with		_		
manufacturer's instructions.	凵	Yes	🗌 No	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	🗆	Yes	🗌 No	N/A
				l
 PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u>, this form) 1. If the f acility classification is an <u>existing small area source</u>, no controls are required. 2. If the facility classification is a <u>new small area source</u>, the machine should be equippe condenser. Complete section A. below. 3. If the facility classification is an <u>existing large area source</u>, the machine should be equippe refrigerated condenser or a carbon adsorber. Complete both sections A and B below. 	ed with a	a refrig with e	gerated either a	
 <i>must have been installed prior to September 22, 1993</i> 4. If the facility classification is a <u>new large area source</u>, the machine should be equipped condenser. Complete both sections A and B below. 	∍d with			only one
A. Has the responsible official of all <u>existing large area & new sources</u> :		·	ox for each q	
1. Equipped all machines with the appropriate vent controls?	🛛	Yes	🗌 No	
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?	🛛	Yes	🗌 No	N/A
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	🛛	Yes	🗌 No	N/A
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	🛛	Yes	🗌 No	N/A
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	🗆	Yes	🗌 No	N/A

the condenser exceeded 45° F?		Yes	∐ No	\geq
6. Conducted all temperature monitoring after an appropriate cool-down period and				
after verifying that the coolant had been completely charged?	\boxtimes	Yes	No No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes Yes	□ No	□ N/A □ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	□ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	D No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	□ N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			check ☑ x for each c	only one Juestion)
1.	Are receipts maintained for all perc purchased?	\boxtimes	Yes	🗌 No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	\boxtimes	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:				
	a) Of any leaks repaired w/in 24 hrs? or;		Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?		Yes	🗌 No	N/A
4.	Is calibration data maintained for applicable direct reading instruments?	\boxtimes	Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?	\boxtimes	Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?	\square	Yes	🗌 No	
7.	Are deviation reports maintained?		Yes	🗌 No	N/A
	a) Problem corrected?		Yes	🗌 No	N/A
8.	Is a compliance plan maintained, if applicable?	\square	Yes	🗌 No	N/A

P	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	(check	only one
1.	What type of leak detection equipment is used to detect leaks?	box for e	ach question)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ? 🖂	Yes 🗌 N	lo
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes 🗌 N	lo 🛛 N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery? 🖾	Yes 🗌 N	ю
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes 🗌 N	lo 🛛 N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? \boxtimes	Yes 🗌 N	lo 🗌 N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sr	mell or touch)	while the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection.	spection of perce	ptible leaks)
	b) Door gaskets and seating Xes No N/A h) Stills Xes No		D I N/A D I N/A D I N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydroc	arbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph shall satis	fy the
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)		
	b) Door gaskets and seating Yes No N/A h) Stills c) Filter gaskets and seating Yes No N/A i) Exhaust dampers	Yes No Yes No Yes No Yes No Yes No	D Image: N/A D Image: N/A D Image: N/A D Image: N/A

FAC (continued)
observation 🗌 other
February 26, 2014
Date of Inspection
Approximate Date of Next Inspection

COMMENTS: Pugh's Cleaners was inspected as a conditionally exempt small quantity generator of hazardous waste and as a dry cleaner under the air and dry cleaner standards regulations. The facility was found to be in compliance with air, hazardous waste, and dry cleaners standards regulations. Please see the hazardous waste report for additional information regarding findings for that program.