

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOV	ERY (CI)				
	RE-INSPECTION (FUI)	ARMS COMPLAINT N	O:				
AIRS ID#: 0112206 DAT	E: <u>2/15/2007</u>	ARRIVE: <u>1030</u>	DEPART: <u>1130</u>				
FACILITY NAME: MAYFAIR CLEANERS							
FACILITY LOCATION: 2760 East Oakland Park Blvd							
	FT LAUDERDALE 333	306					
RESPONSIBLE OFFICE	AL: RUSSELL O'MALLEY	PHON	NE: (954)566-0873				
CONTACT NAME:		PHONE:					
REMITTANCE YEAR:	2006 ENTITLE	EMENT PERIOD: 3/6/2000 (effective of					
DIDEL NIGHT CHION		. [7]					
IN COMPLIANC	COMPLIANCE STATUS (che E MINOR Non-COMPI	_	ANT N COMBLIANCE				
IN COMPLIANC	E MINOR Non-COMPI	LIANCE SIGNIFICA	ANT Non-COMPLIANCE				
	LASSIFICATION - Rule 62-21 y one box in A)	3.300 FAC					
A. 1. Existing small dry-to-dry only transfer only, x both types, x < (constructed be	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr	2. New small area sour dry-to-dry only, x < 1 transfer only, x < 200 both types, x < 140 g (constructed on or after	140 gal/yr) gal/yr al/yr				
transfer only, 2	y, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $0 \le x \le 1,800 \text{ gal/yr}$	4. New large area sour dry-to-dry only, 140 transfer only, $200 \le x$ both types, $140 \le x \le$ (constructed on or after the source of the source).	≤ x ≤ 2,100 gal/yr x ≤ 1,800 gal/yr z 1,800 gal/yr				
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits							
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 60 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A	
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A	
3.	Close and secure machine doors except during loading/unloading?	X Yes	☐ No		
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes	□ No	□ N/A	
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	⊠Yes	□ No	□ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Pro	ceed to l	Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	with a ref	rigerated	
A.	Has the responsible official of all <u>existing large area & new sources</u> :		only each ques	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	□N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	□No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	□No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ⊠Yes	□No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No		

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- ∐Yes □ No □N/A			
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☐ N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A			
5	Equip transfer machines (dryers, reclaimers, and washers) with individual				
٦.	condenser coils?	- Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A			
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for			
Does the responsible official:		each question)			
1.	Maintain receipts for perc purchased?	Yes No			
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No			
3.	Maintain leak detection inspection and repair reports for the following:				
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A			
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days				
4.	and parts installed w/in 5 days of receipt?	∑ Yes □ No □ N/A			
	and parts installed w/in 5 days of receipt? Maintain calibration data? (for applicable direct reading instruments)	✓ Yes ☐ No ☐ N/A✓ Yes ☐ No ☐ N/A			
5.		Yes No N/A			
6.	Maintain calibration data? (for applicable direct reading instruments) Maintain exhaust duct monitoring data on perc concentrations? Maintain a startup/shutdown/malfunction plan?	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No 			
6.	Maintain calibration data? (for applicable direct reading instruments) Maintain exhaust duct monitoring data on perc concentrations?	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No 			
6.	Maintain calibration data? (for applicable direct reading instruments) Maintain exhaust duct monitoring data on perc concentrations? Maintain a startup/shutdown/malfunction plan?	Yes No N/A Yes No N/A Yes No Yes No Yes No No N/A			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?					
2. Does the facility maintain a leak log?	<u> </u>				
3. Does the responsible official check the following areas for leaks a) Hose connections, fittings, couplings, and valves	? Muck cookers				
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————					
Elizabeth F. Susky 2/15/2007					
Inspector's Name (Please Print)	Date of Inspection				
	2/15/2008				
Inspector's Signature	Approximate Date of Next Inspection				

COMMENTS: In a compliance inspection conducted on 2/15/2008, AQD staff observed operations at Mayfair Cleaners @ 2760 East Oakland Park Blvd., Fort Lauderdale, FL 33306. AQD staff was accompanied by the owner, Russell O'Mailey. The facility has one dry-cleaning machine and Mr. O'mailey is keeping accurate records of his chiller temperatures. Housekeeping was good.