

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	NS1, INS2) 🔀 COMPLAINT/DISCO	VERY (CI)				
RE-INSPECT	TION (FUI) ARMS COMPLAINT	NO:				
AIRS ID#: 0990362 DATE: <u>12/3/2008</u>	8 ARRIVE: <u>1:45 PM</u>	DEPART: 2:10 PM				
FACILITY NAME: M&D ONE PRIC	CE DRY CLEANERS					
FACILITY LOCATION: 9841 C	FACILITY LOCATION: 9841 GLADES RD					
BOCA	A RATON 33434					
OWNER/AUTHORIZED REPRESEN	NTATIVE: IGOR KLEYMAN PHO	<b>DNE:</b> (561)504-0743				
CONTACT NAME: Same	РНС	ONE: (				
ENTITLEMENT PERIOD: 3/17/200 (effective d						
	NCE STATUS (check ☑ only one box)					
☐ IN COMPLIANCE ☐ MI	INOR Non-COMPLIANCE SIGNIFIC	CANT Non-COMPLIANCE				
PART II: FACILITY CLASSIFICAT (check ☑ only one box in A						
A. 1. Existing small area source dry-to-dry only, x < 140 gal transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	dry-to-dry only, $x < 2t$ transfer only, $x < 2t$ both types, $x < 140$	c 140 gal/yr 00 gal/yr gal/yr				
	4. New large area sou					
3. Existing large area source dry-to-dry only, $140 \le x \le 2$ transfer only, $200 \le x \le 1,80$ both types, $140 \le x \le 1,800$ (constructed before $12/9/91$ )	2,100 gal/yr dry-to-dry only, 140 $00$ gal/yr transfer only, 200 $\leq$ gal/yr both types, 140 $\leq$ x	$0 \le x \le 2\overline{,100}$ gal/yr $x \le 1,800$ gal/yr $x \le 1,800$ gal/yr				
dry-to-dry only, $140 \le x \le 2$ transfer only, $200 \le x \le 1,80$ both types, $140 \le x \le 1,800$	2,100 gal/yr dry-to-dry only, 140 $\leq$ 00 gal/yr transfer only, 200 $\leq$ both types, 140 $\leq$ x (constructed on or a mit $\boxtimes$ betroleum	$0 \le x \le 2\overline{,100}$ gal/yr $x \le 1,800$ gal/yr $x \le 1,800$ gal/yr				

PA	RT III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC		only or	
Do	es the responsible official of the dry cleaning facility:	for ea	ich questi	ion)
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes	□No	⊠N/A
2.	Examine the containers for leakage?	Yes	☐ No	N/A
3.	Close and secure machine doors except during loading/unloading?	Yes	☐ No	
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes	□ No	⊠ N/A
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes	□ No	⊠ N/A
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)			
	1. If the facility classification is a <b>Existing small area source</b> , no controls are required.	red. Pro	ceed to l	Part V.
	2. If the facility classification is a <u>New small area source</u> , the machine should be eccondenser. <b>Complete section A. below.</b>	quipped v	with a ref	rigerated
	<ol> <li>If the facility classification is a <u>Existing large area source</u>, the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below must have been installed prior to September 22, 1993</li> <li>If the facility classification is a <u>New large area source</u>, the machine should be equenced condenser. Complete both sections A and B below.</li> </ol>	w. Carb	oon adsor	rber
A.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		only each ques	one box for stion)
1.	Equipped all machines with the appropriate vent controls?	□Yes	□No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	□Yes	□No	⊠N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	∐Yes	□No	⊠N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	□Yes	□No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	□Yes	□No	⊠N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	□Yes	□No	

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)						
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No				
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- ∐Yes □ No ⊠N/A				
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☒ N/A				
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A				
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A				
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ⊠ N/A				
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- □Yes □ No □ N/A				
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A				
	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC best he responsible official:	(check ☑ only one box for each question)				
1.	Maintain receipts for perc purchased?	Yes No				
2.	Maintain rolling monthly total of yearly perc consumption?	☐ Yes ☐ No				
3.	Maintain leak detection inspection and repair reports for the following:					
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A				
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A				
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A				
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A				
6.	Maintain a startup/shutdown/malfunction plan?	Yes No				
7.	Maintain deviation reports?	Yes No N/A				
	a) Problem corrected?	Yes No N/A				
8.	Maintain a compliance plan, if applicable?	Yes No N/A				

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection? Yes No					
2. Does the facility maintain a leak log? Yes No					
3. Does the responsible official check the following areas for leaks?  a) Hose connections, fittings,     couplings, and valves					
4. Which method(s) of detection (is/are) used by the responsible official?					
a) Visual examination (condensed solvent on exterior surfaces)					
c) Odor (noticeable perc odor) c)					
d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) **(see below) e) Halogen leak detector					
**If using direct-reading instrumentation, is the equipment: ** \begin{align*} N/A \\ 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm?					
Jeffrey Dizek 12/3/2008					
Inspector's Name (Please Print)  Date of Inspection					
NA					
Inspector's Signature Approximate Date of Next Inspection					
COMMENTS: Facility uses Dry Solv only.					