

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	⊠ co	MPLAINT/DISCOVI	ERY (CI)			
F	RE-INSPECTION (FUI)	AR	MS COMPLAINT NO	O:			
AIRS ID#: 0250701 DATE: <u>9/18/2007</u> ARRIVE: <u>11:28 AM</u> DEPART: <u>12:00 PM</u>							
FACILITY NAME: SAN SOUCI DRY CLEANERS							
FACILITY LOCATION: 2184 NE 123rd Street							
NORTH MIAMI 33181							
RESPONSIBLE OFFICIA	AL: SULEIMAN KOSH	O	PHON	E: (305)981-0304			
CONTACT NAME:	CONTACT NAME: PHONE:						
REMITTANCE YEAR: 2	2006 ENT	TITLEMENT	Γ PERIOD: 11/6/200 (effective da				
			(enconve da	ate) (end date)			
PART I: INSPECTION C	COMPLIANCE STATU	S (check 🗹	only one box)				
IN COMPLIANCE	E MINOR Non-C	COMPLIANC	E SIGNIFICA	NT Non-COMPLIANCE			
PART II: FACILITY CL (check ☑ only		62-213.300	FAC				
A. 1. Existing small a dry-to-dry only transfer only, x both types, x < (constructed be	, x < 140 gal/yr < 200 gal/yr 140 gal/yr		New small area sourd dry-to-dry only, $x < 1$ transfer only, $x < 200$ both types, $x < 140$ ga (constructed on or after	40 gal/yr gal/yr tl/yr			
transfer only, 20	0.05 = 0.05, $0.05 = 0.05$, 0.05		New large area source dry-to-dry only, $140 \le x$ transfer only, $200 \le x$ both types, $140 \le x \le x$ (constructed on or after	$\leq x \leq 2,100 \text{ gal/yr}$ $\leq 1,800 \text{ gal/yr}$ 1,800 gal/yr			
5. Ineligible for G drop store/out of facility exceeds	of business/petroleum						
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 80 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2. Examine the containers for leakage?		⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below <i>must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No No
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A
6. Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A
PART V: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC	(1-1-7-1
Does the responsible official:	(check ✓ only one box for each question)
1. Maintain receipts for perc purchased?	- Xes No
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	-
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	 ☐ Yes ☐ No ☑ N/A ☐ Yes ☐ No ☑ N/A
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations?	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A Yes □ No
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments) 5. Maintain exhaust duct monitoring data on perc concentrations? 6. Maintain a startup/shutdown/malfunction plan?	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?
. Does the facility maintain a leak log? Yes No
a) Hose connections, fittings, couplings, and valves
. Which method(s) of detection (is/are) used by the responsible official?
a) Visual examination (condensed solvent on exterior surfaces)
RANK DELGADO 9/18/07
Inspector's Name (Please Print) Date of Inspection
9/2008
Inspector's Signature Approximate Date of Next Inspection
COMMENTS: NO LEAKS FOUND. PERC DRY CLEANING MACHINE OPERATIONAL ECORDS ARE AVAILABLE.