

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI) ARMS COMPLAINT NO:			
AIRS ID#: 0150059 DATE: 07/16/2008	ARRIVE: 10:00 a.m. DEPART: 10:35 a.m.			
				
FACILITY NAME: LA FRANCE CHARLOTTE HARBOR				
FACILITY LOCATION: 4435 Tamiami Trail				
PORT CHARLOTTE	33980-2123			
OWNER/AUTHORIZED REPRESENTATIVE: GL	PHONE: (941)627-6969			
CONTACT NAME:	PHONE:			
ENTITLEMENT PERIOD: 11/27/2003 / 11/27/2008 (effective date) (end date)				
PART I: <u>INSPECTION</u> <u>COMPLIANCE</u> <u>STATUS</u> (check ✓ only one box)				
☐ IN COMPLIANCE ☐ MINOR Non-COM	IPLIANCE SIGNIFICANT Non-COMPLIANCE			
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check ☑ only one box in A)				
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91)			
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)			
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 115.8 gallons.				

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box					
Does the responsible official of the dry cleaning facility: for each question)					
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A			
2.	Examine the containers for leakage?	☐Yes ☐ No ☒ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below <i>must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No No		
	a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☐ No ☐ N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No No		
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☐ N/A		
	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC best he responsible official:	(check ☑ only one box for each question)		
1.	Maintain receipts for perc purchased?	- Xes No		
	Maintain rolling monthly total of yearly perc consumption?			
	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A		
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A		
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☒ N/A		
6.	Maintain a startup/shutdown/malfunction plan?	∑ Yes □ No		
7.	Maintain deviation reports?	Yes No N/A		
	a) Problem corrected?	Yes No N/A		
8.	Maintain a compliance plan, if applicable?	Yes No N/A		

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and name in increastion?	V ₂₀ □ N ₂
detection and repair inspection?	
2. Does the facility maintain a leak log?	
	Is
4. Which method(s) of detection (is/are) used by the responsible official	al?
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tube) Halogen leak detector	b)⊠ c)⊠ es)d)□**(see below)
**If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-5 2) Calibrated against a standard gas prior to and after each use (PII 3) Inspected for leaks and obvious signs of wear on a weekly basis 4) Kept in a clean and secure area when not in use? 5) Verified for accuracy by use of duplicate samples (calorimetric of	00 ppm? 1) Yes No D/FID only)? 2) Yes No ? 3) Yes No 4) Yes No
ROBERT J. STEWART	07/16/2008
Inspector's Name (Please Print)	Date of Inspection
	07/2009
Robert J. Stewart	
Inspector's Signature	Approximate Date of Next Inspection

COMMENTS: Rolling monthly total of yearly perc consumption has not been maintained in DEP 2008 Compliance calendar since January 2008. The DEP Compliance calendar for 2007 was not present at the facility for inspection. Facility has not purchased a halogen leak detector as mandated by E.P.A. regulations by July 27, 2008, but owner stated that he has ordered the equipment.