

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: | ANNUAL (INS1, INS2) RE-INSPECTION (FUI) | COMPLAINT/DISCO | · / <u>-</u> | | | |
|---|--|-----------------------------|--|--|--|--|
| AIRS ID#: 0571033 DA7 | ГЕ: 10-16-2012 | ARRIVE: 8:40am | DEPART: <u>8:50am</u> | | | |
| FACILITY NAME: VIO | CTORIAN CLEANERS | | | | | |
| FACILITY LOCATION | : 4920 Newkirk Drive Sui | te 10 | | | | |
| | TAMPA 33624-1080 | | | | | |
| OWNER/AUTHORIZED REPRESENTATIVE: AMINSULTAN CHARANIA PHONE: (813)264-5120 Email: Mobile: CONTACT NAME: PHONE: Email: Mobile: ENTITLEMENT PERIOD: 4/10/2011 / 4/10/2016 (effective date) (end date) | | | | | | |
| PART I: INSPECTION COMPLIANCE STATUS (check ✓ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE | | | | | | |
| PART II: FACILITY C | LASSIFICATION - Rule 62- | -213.300 FAC | | | | |
| | only one box in A) | 213.5001110 | | | | |
| transfer only, both types, x < (constructed b 3. Existing large dry-to-dry onl transfer only, both types, 14 (constructed b 5. Ineligible for d rop store/our | y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91) | | < 140 gal/yr 100 gal/yr 100 gal/yr 10 gal/yr 10 gal/yr 10 gal/yr 10 served | | | |
| B . The sum of the vecleaning facility vec | | (perc) purchases made in ea | ach of the previous 12 months by this dry | | | |

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC | | | check ox for o | | only o | | | |
|--|-------------|---------|-------------------|----|-------------|-----|--|--|
| 1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers? | | Yes | | No | \boxtimes | N/A | | |
| 2. Are all perc. containers leak free ? | | Yes | | No | | N/A | | |
| 3. Are all machine doors kept closed and secured except during loading/unloading? | | Yes | | No | | | | |
| 4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? | | Yes | | No | \boxtimes | N/A | | |
| 5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions. | | Yes | | No | \boxtimes | N/A | | |
| 6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds | _ | | _ | | _ | | | |
| maintain according to the manufacturer's specifications? | | Yes | | No | \boxtimes | N/A | | |
| | | | | | | | | |
| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) | | | | | | | | |
| | maga | od to D | Ont V | | | | | |
| 1. If the f acility classification is an <u>existing small area source</u> , no controls are required. P | roce | eu to P | art v | • | | | | |
| 2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | | | | | | |
| 3. If the fa cility classification is an existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 | | | | | | | | |
| 4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below. | | | | | | | | |
| A. Has the responsible official of all existing large area & new sources: | | | • | | only o | | | |
| 1. Equipped all machines with the appropriate vent controls? | \boxtimes | Yes | | No | | | | |
| 2. Equipped dry-to-dry machines with a closed-loop vapor venting system? | \boxtimes | Yes | | No | | N/A | | |
| 3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | \boxtimes | Yes | | No | \boxtimes | N/A | | |
| 4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | | Yes | | No | \boxtimes | N/A | | |
| 5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | | Yes | | No | \boxtimes | N/A | | |
| 6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | | Yes | \boxtimes | No | | | | |

| PA | ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued) | | | | | | |
|-------------------|--|-------------|---------------------------------|---|---|----------------|-------------------------------|
| В. | For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis? | | Yes | □ N | No | | |
| 2. | Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? | | Yes | | Vо | | N/A |
| | a) Is the temperature differential equal to, or greater than 20° F? | | Yes | | lo | | N/A |
| 3. | Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | | Yes | □ N | Vo | | N/A |
| | a) Is the perc concentration equal to, or less than 100 ppm? | | Yes | □ N | Ю | | N/A |
| 4. | Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | | Yes | | Vo | | N/A |
| 5. | Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils? | | Yes | | Vo | | N/A |
| _ | | | | | • | \Box | NT/ A |
| 6. | Is airflow routed to the carbon adsorber (if used) at all times? | Ш | Yes | ∐ N | Ю | Ш | N/A |
| 6. | Is airflow routed to the carbon adsorber (if used) at all times? | Ш | Yes | □N | No | | N/A |
| 6. | Is airflow routed to the carbon adsorber (if used) at all times? | | Yes | N | No | | N/A |
| | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC | | (| check ✓ check ✓ | Z or | nly o | ne |
| PA | | | (| check v | Z or | nly o | ne |
| P A | ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC | | (bo | check v | Z or ch qu | nly o | ne |
| 1. 2. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | | (bo | check various for each | Z or ch qu | nly o | ne |
| 1. 2. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | \boxtimes | (bo | check v for each | Z or ch qu | nly o | ne |
| 1. 2. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | \boxtimes | (bo Yes Yes | check various for each | Z or ch qu Vo | nly o estio | ne n) |
| 1. 2. 3. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | \boxtimes | Yes Yes Yes | check v for each N N N | Z or ch que lo lo | nly o estio | ne n) N/A |
| 1. 2. 3. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | | Yes Yes Yes | check x for each N N N N | Z or do | nnly o eestio | ne n) N/A N/A |
| 1. 2. 3. 4. 5. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | | Yes Yes Yes Yes | check v for each N N N N N N N N N N N N N N N N N N N | Z or do | nnly o eestio | ne n) N/A N/A N/A |
| 1. 2. 3. 4. 5. 6. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | | Yes Yes Yes Yes Yes Yes | check check X for each N N N N N N N | Z or ch que | nly o estio | ne n) N/A N/A N/A |
| 1. 2. 3. 4. 5. 6. | ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ———————————————————————————————————— | | Yes Yes Yes Yes Yes Yes Yes Yes | check check N N N N N N N N N N N N | Z or que lo | nnly o estio | ne n) N/A N/A N/A |

| PA | ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC | | (check 🗹 | only one |
|----|--|---------------------------------|--|---|
| 1. | What type of leak detection equipment is used to detect leaks? | bo | ox for each | question) |
| | ☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☒ None used | | | |
| 2. | Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to | | | |
| | the manufacturer's instructions (manual was available and RO could demonstrate | | | |
| | procedure) ? | Yes | ☐ No | |
| 3. | For major sources is the halogenated hydrocarbon detector or PCE gas analyzer | | | |
| | operated according to EPA Method 21 ? | Yes | ☐ No | N/A |
| 4. | Is the vapor leak inspection conducted by placing the probe inlet at the surface of | | | |
| | each component interface where leakage could occur and moving it slowly along | | | |
| | the interface periphery? | Yes | ☐ No | |
| 5. | Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or | | | |
| | infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per | | | |
| | million by volume (based on documented specifications) ? | Yes | ☐ No | N/A |
| 6. | Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations | | | |
| | of PCE of 25 parts per million by volume (based on documented specifications) and | | | |
| | indicating a concentration of 25 parts per million by volume or greater by emitting | | | |
| | an audible or visual signal that varies as the concentration changes? | Yes | ☐ No | N/A |
| 7. | Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm | nell or | touch) whi | le the |
| | system is in operation (§63.322(k))? | | | |
| | $(Inspection\ with\ a\ halogenated\ hydrocarbon\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ with\ a\ halogenated\ hydrocarbon\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ with\ a\ halogenated\ hydrocarbon\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ PCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ pCE\ gas\ analyzer\ also\ fulfills\ the\ requirement\ for\ inspection\ detector\ or\ pCE\ gas\ analyzer\ also\ fulfills\ detector\ or\ pCE\ gas\ analyzer\ also\ fulfill\ also\ fulfil$ | ection | of perceptib | le leaks) |
| | b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y | Yes Yes Yes Yes Yes | NoNoNoNoNoNo | N/AN/AN/AN/AN/AN/A |
| 8. | Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge | enated | hydrocarbo | on detector |
| | or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the system) | raph sl | hall satisfy th | ie |
| | requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l)) | | | |
| | b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y | Yes Yes Yes Yes Yes | NoNoNoNoNoNoNo | N/A N/A N/A N/A N/A N/A N/A |

| PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued) | | | | | | |
|---|-------------------------------------|--|--|--|--|--|
| 9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☒ other Explain other: | | | | | | |
| Jessica Lopez | 10-16-2012 | | | | | |
| Inspector's Name (Please Print) | Date of Inspection | | | | | |
| Inspector's Signature | Approximate Date of Next Inspection | | | | | |

COMMENTS: EPC staff stopped by this facility today. The business was closed with no lights turned on. There was a signed at the front door stating that the busines had closed. EPC staff called the the owner, Amin at 813-843-5734 which was the contact number posted on the sign. He states that the Westfargo bank took the property since it went under foreclosure. The owner also states that the perc machine is still inside. The owner will call me back with the contact name and phone number at the bank.