OWNERFUL PROTECTION	
Same Party	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	MPLAINT/DISCOVERY (CI)
AIRS ID#: 0112219 DATE: <u>10/17/2012</u> ARRI	VE: <u>1330</u> DEPART: <u>1430</u>
FACILITY NAME: PAYLESS QUALITY CLEANERS	
FACILITY LOCATION: 10016 W McNab Rd	
TAMARAC 33321-1815	
OWNER/AUTHORIZED REPRESENTATIVE: BERNADET Email: CONTACT NAME: Email: ENTITLEMENT PERIOD: / (effective date) (end date)	TE CARMELIUS* PHONE: (954)724-9939 Mobile: PHONE: Mobile:
PART I: INSPECTION COMPLIANCE STATUS (check I IN COMPLIANCE INCOMPLIANCE	
dry-to-dry only, x < 140 gal/yrdry-to-dry only, x < 140 gal/yrtransfer only, x < 200 gal/yrtboth types, x < 140 gal/yrt(constructed before 12/9/91)(dry-to-dry only, 140 \le x \le 2,100 gal/yr 3. Existing large area source4. Ndry-to-dry only, 140 \le x \le 2,100 gal/yrdrytransfer only, 200 \le x \le 1,800 gal/yrtboth types, 140 \le x \le 1,800 gal/yrt	New small area sourcedry-to-dry only, $x < 140$ gal/yrransfer only, $x < 200$ gal/yrpoth types, $x < 140$ gal/yrconstructed on or after 12/9/91)New large area sourcedry-to-dry only, $140 \le x \le 2,100$ gal/yrransfer only, $200 \le x \le 1,800$ gal/yrpoth types, $140 \le x \le 1,800$ gal/yr

cleaning facility was 30.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC		`	check x for e		only o questic	
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A
2. Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No		
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 		Yes		No	\boxtimes	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No		N/A
PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC						

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an **existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber . **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all <u>existing large area & new sources</u> :	·	check ☑ x for each c	only one question)
1.	Equipped all machines with the appropriate vent controls?	Yes	🗌 No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	🗌 No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	🗌 No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	🗌 No	N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	🗌 No	N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	🗌 No	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes	🗌 No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?	Yes Yes	D No	□ N/A □ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	`	check 🗹 x for each c	only one uestion)
1. Are receipts maintained for all perc purchased?	Yes	D No	
2. Are rolling monthly total s of yearly perc consumption maintained ?	Yes	🗌 No	
3. Are leak detection inspection and repair reports maintained for the following:			
a) Of any leaks repaired w/in 24 hrs? or;	Yes	🗌 No	N/A
 b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 	Yes	🗌 No	N/A
4. Is calibration data maintained for applicable direct reading instruments?	Yes	🗌 No	N/A
5. Is exhaust duct monitoring data on perc concentrations maintained?	Yes	🗌 No	N/A
6. Is a startup/shutdown/malfunction plan maintained for each machine?	Yes	🗌 No	
7. Are deviation reports maintained?	Yes	🗌 No	N/A
a) Problem corrected?	Yes	🗌 No	N/A
8. Is a compliance plan maintained, if applicable?	Yes	🗌 No	N/A

PA	ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?		ox for each	•
	Halogenated hydrocarbon detector PCE gas analyzer None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	<i>procedure)</i> ? 🖂	Yes	🗌 No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	🗌 No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	🗌 No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	🗌 No	N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? \square	Yes	🗌 No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or t	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection d	of perceptib	le leaks)
	b) Door gaskets and seating 🖾 Yes 🔲 No 🗍 N/A h) Stills 🖾		□ No □ No □ No □ No □ No	 □ N/A □ N/A □ N/A □ N/A □ N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage	graph sh	all satisfy th	ıe
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)			
	b) Door gaskets and seating Xes No N/A h) Stills c) Filter gaskets and seating Xes No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	□ No □ No □ No □ No □ No	 N/A N/A N/A N/A N/A N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)						
 9. What evidence suggests that leak checks are performed as required? Leak log documentation RO Assurances On-site observation other Explain other : 						
Elizabeth F. Susky	10/17/2012					
Inspector's Name (Please Print)	Date of Inspection					
Inspector's Signature	Approximate Date of Next Inspection					
COMMENTS: In a compliance inspection conducted on 10/1 Quality Cleaners. The facility has one PERC dry-cleaning machinspection. AQD staff discussed with Ms. Caremelius the necess citation for the permit expiration. On 11/27/2012 the permit was older machine that does not require a condensor. However, she	sity to renew her General Permit (#0112319). She was renewed and notification was sent by FDEP. Ms. Car	ring the s given a melius has an				

has a sniffer on-site. In a compliance inspection conducted on 10/17/2012, AQD staff (E. Susky) observed operations at Payless Quality Cleaners. The facility has one PERC dry-cleaning machine. Ms. Bernadette Carmelius (owner) was present during the inspection. AQD staff discussed with Ms. Caremelius the necessity to renew her General Permit (#0112319). She was given a citation for the permit expiration. On 11/27/2012 the permit was renewed and notification was sent by FDEP. Ms. Carmelius has an older machine that does not require a condensor. However, she did not have available her rolling PERC purchases. Ms. Carmelius has a sniffer on-site.