

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVE	RY (CI)			
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO) :			
AIRS ID#: 1270111 DA	TE: <u>07/07/2006</u>	ARRIVE: <u>12:35</u>	DEPART: <u>12:40</u>			
FACILITY NAME: TOMOKA PLAZA COIN-O-MATIC						
FACILITY LOCATION	N: 715 S Nova Road					
	ORMOND BEACH 32174					
RESPONSIBLE OFFICIAL: NICHOLAS BISSELL		PHONE: (904)677-0111				
CONTACT NAME:		PHONE:				
REMITTANCE YEAR:	2000 ENTITLE	EMENT PERIOD: 7/12/2001 (effective dat				
	COMPLIANCE STATUS (che					
☐ IN COMPLIAN	CE MINOR Non-COMP	LIANCE [SIGNIFICAN	NT Non-COMPLIANCE			
	CLASSIFICATION - Rule 62-21 ly one box in A)	13.300 FAC				
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 g both types, x < 140 gal (constructed on or after	0 gal/yr gal/yr /yr			
transfer only, both types, 14	e area source ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area source dry-to-dry only, $140 \le$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	x ≤ 2,100 gal/yr ≤ 1,800 gal/yr ,800 gal/yr			
drop store/ou	t of business/petroleum ds above limits					
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 0 gallons.						

	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check only one box		
Do	es the responsible official of the dry cleaning facility:	for each question)		
	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A		
2.	Examine the containers for leakage?	□Yes □ No □ N/A		
3.	Close and secure machine doors except during loading/unloading?	Yes No		
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes □ No ⊠ N/A		
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ⊠ N/A		
	ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)			
	1. If the facility classification is a Existing small area source, no controls are requ	uired. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.			
	 If the facility classification is a <u>Existing large area source</u>, the machine should refrigerated condenser or a carbon adsorber. Complete both sections A and B belomust have been installed prior to September 22, 1993 If the facility classification is a <u>New large area source</u>, the machine should be e condenser. Complete both sections A and B below. 	low. Carbon adsorber		
<u> </u>	Condition Conference and Conference			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)		
1.	Equipped all machines with the appropriate vent controls?	- No No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	□Yes □No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes No N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- □Yes □No		

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	Yes No No			
	a) Is the temperature differential equal to, or greater than $20^{\rm o}$ F?	☐Yes ☐ No ☐ N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	- Yes No N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A			
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for			
	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC best he responsible official:	(check ☑ only one box for each question)			
Do		each question)			
D o	pes the responsible official:	each question) Yes No			
1. 2.	Des the responsible official: Maintain receipts for perc purchased?	each question) Yes No			
1. 2.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption?	each question) Yes No Yes No			
1. 2.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following:	each question) Yes No Yes No			
1. 2. 3.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days	each question)			
1. 2. 3.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	each question)			
1. 2. 3. 4. 5.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Maintain calibration data? (for applicable direct reading instruments)	each question)			
1. 2. 3. 4. 5. 6.	Maintain receipts for perc purchased?	each question)			
1. 2. 3. 4. 5. 6.	Maintain receipts for perc purchased? Maintain rolling monthly total of yearly perc consumption? Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or;	each question)			
1. 2. 3. 4. 5. 6. 7.	Maintain receipts for perc purchased?	each question)			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	
2. Does the facility maintain a leak log?	Yes No
c) Filter gaskets and seating d) Pumps Yes No N/A i) Exhau Yes No N/A j) Divert	Yes
4. Which method(s) of detection (is/are) used by the responsible officials a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes e) Halogen leak detector	a)
**If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-500 2) Calibrated against a standard gas prior to and after each use (PID/R 3) Inspected for leaks and obvious signs of wear on a weekly basis? - 4) Kept in a clean and secure area when not in use?	O ppm? 1) Yes No FID only)? 2) Yes No 3) Yes No 4) Yes No
Inspector's Name (Please Print)	Date of Inspection
Inspector's Signature	Approximate Date of Next Inspection
COMMENTS:	