| ALL ALLO ALL                 |
|------------------------------|
| 1 Ser                        |
| FLORIDA                      |
| the first strategies and the |

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: ANNUAL (INS1, INS2)<br>RE-INSPECTION (FUI)   | COMPLAINT/DISCOVERY (CI)  |
|---|---|
| AIRS ID#: 0990386 DATE: <u>12/21/2006</u>   | ARRIVE: <u>11:50 AM</u> DEPART: <u>12:25 PM</u>   |
| FACILITY NAME: CRYSTAL CLEANERS   |   |
| FACILITY LOCATION: 1000 Linton Blvd Bay A   | A1  |
| DELRAY BEACH 334  | 444   |
| <b>RESPONSIBLE OFFICIAL:</b> JORGE DELGADO  | <b>PHONE:</b> (561)243-7994   |
| CONTACT NAME: Same  | <b>PHONE:</b> (   |
| REMITTANCE YEAR: 2005 ENTITL  | <b>EMENT PERIOD:</b> 11/9/2006 / 11/9/2011<br>(effective date) (end date)   |
| PART I: INSPECTION COMPLIANCE STATUS (ch  |   |
| PART II: FACILITY CLASSIFICATION - Rule 62-2<br>(check d only one box in A)   | 213.300 FAC   |
| A. 1. Existing small area source<br>dry-to-dry only, $x < 140$ gal/yr<br>transfer only, $x < 200$ gal/yr<br>both types, $x < 140$ gal/yr<br>(constructed before 12/9/91)                                  | 2. <u>New small area source</u><br>dry-to-dry only, $x < 140$ gal/yr<br>transfer only, $x < 200$ gal/yr<br>both types, $x < 140$ gal/yr<br>(constructed on or after 12/9/91)                              |
| 3. Existing large area source<br>dry-to-dry only, $140 \le x \le 2,100$ gal/yr<br>transfer only, $200 \le x \le 1,800$ gal/yr<br>both types, $140 \le x \le 1,800$ gal/yr<br>(constructed before 12/9/91) | 4. New large area source<br>dry-to-dry only, $140 \le x \le 2,100$ gal/yr<br>transfer only, $200 \le x \le 1,800$ gal/yr<br>both types, $140 \le x \le 1,800$ gal/yr<br>(constructed on or after 12/9/91) |
| 5. Ineligible for General Permit<br>drop store/out of business/petroleum<br>facility exceeds above limits   |   |
| B. The total quantity of perchloroethylene (perc) pucheaning facility was 30 gallons.   | rchased within the preceding 12 months by this dry  |

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC   | (check 🗹 only one box |
|---|-----------------------|
| Does the responsible official of the dry cleaning facility:   | for each question)    |
| 1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?   | Yes No N/A            |
| 2. Examine the containers for leakage?  | Yes No N/A            |
| 3. Close and secure machine doors except during loading/unloading?  | Yes No                |
| 4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?                        | Yes No N/A            |
| 5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds<br>according to the manufacturer's specifications? | ∐Yes □ No ⊠ N/A       |

| PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC<br>(Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form) |   |           |                     |                       |  |  |  |
|---|---|-----------|---------------------|-----------------------|--|--|--|
|   | 1. If the facility classification is a <b>Existing small area source</b> , no controls are required. <b>Proceed to Part V.</b>  |           |                     |                       |  |  |  |
|   | 2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>   |           |                     |                       |  |  |  |
|   | 3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i> |           |                     |                       |  |  |  |
|   | 4. If the facility classification is a <u>New large area source</u> , the machine should be equip condenser. Complete both sections A and B below.  | luipped v | vith a ref          | rigerated             |  |  |  |
| А.  | Has the responsible official of all <u>existing large area &amp; new sources</u> :  |           | ☑ only<br>each ques | one box for<br>stion) |  |  |  |
| 1.  | Equipped all machines with the appropriate vent controls?   | Yes       | No                  |                       |  |  |  |
| 2.  | Equipped dry-to-dry machines with a closed-loop vapor venting system?   | ⊠Yes      | No                  | □N/A                  |  |  |  |
| 3.  | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?   | ⊠Yes      | No                  | N/A                   |  |  |  |
| 4.  | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?   | ⊠Yes      | No                  |                       |  |  |  |
| 5.  | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?  | ⊠Yes      | No                  | □N/A                  |  |  |  |
| 6.  | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?  | ⊠Yes      | No                  |                       |  |  |  |

| PA | ART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)   |   |     |
|----|--|---|-----|
| B. | Does the responsible official of an existing large or new large area source also:  | (check 🗹 only one box for<br>each question) | Dr  |
| 1. | Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?   | Yes No                                      |     |
| 2. | Measure and record the washer exhaust temperature at the condenser<br>inlet and outlet weekly?   | Yes No N<br>Yes No N                        |     |
| 3. | Measure and record the perc concentration in the exhaust stream weekly<br>at the end of the final drying cycle while the machine is venting to the<br>adsorber, if machines are equipped exclusively with a carbon adsorber?   | □Yes □ No ⊠ N                               | N/A |
|    | a) Is the perc concentration equal to, or less than 100 ppm?   | Yes No No                                   | N/A |
| 4. | Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | - 🗌 Yes 🗌 No 🖾 M                            | √A  |
| 5. | Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?   | 🗌 Yes 🗌 No 🖾 N                              | N/A |
| 6. | Route airflow to the carbon adsorber (if used) at all times?   | Yes No X                                    | N/A |
|    |  |   |     |

| PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC   |  |
|--|--|
| Does the responsible official:   | (check 🗹 only one box for<br>each question)  |
| 1. Maintain receipts for perc purchased?   | - 🛛 Yes 🗌 No                                 |
| 2. Maintain rolling monthly total of yearly perc consumption?  | 🛛 Yes 🗌 No                                   |
| 3. Maintain leak detection inspection and repair reports for the following:  |  |
| a) documentation of leaks repaired w/in 24 hrs? or;  | - 🛛 Yes 🗌 No 🗌 N/A                           |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | Yes No N/A                                   |
| 4. Maintain calibration data? (for applicable direct reading instruments)  | Yes No N/A                                   |
| 5. Maintain exhaust duct monitoring data on perc concentrations?   | ☐ Yes ☐ No ⊠ N/A                             |
| 6. Maintain a startup/shutdown/malfunction plan?   | Yes 🗌 No                                     |
| 7. Maintain deviation reports?   | $\sim$ Yes $\square$ No $\square$ N/A        |
| a) Problem corrected?  | - $\boxtimes$ Yes $\square$ No $\square$ N/A |
| 8. Maintain a compliance plan, if applicable?  | Yes No N/A                                   |
|  |  |

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

| detection and repair inspection?   |
|--|
| 2. Does the facility maintain a leak log? Xes C Yes No   |
| <ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves XYes No N/A g) Muck cookers Yes No XN/A</li> <li>b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A</li> <li>c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Yes No XN/A</li> <li>d) Pumps Yes No N/A j) Diverter valves Yes No N/A</li> <li>e) Solvent tanks and containers Yes No N/A</li> <li>f) Water separators Yes No N/A</li> </ul> |
| 4. Which method(s) of detection (is/are) used by the responsible official?   |
| <ul> <li>a) Visual examination (condensed solvent on exterior surfaces) a) a</li> <li>b) Physical detection (airflow felt through gaskets) b) a</li> <li>c) Odor (noticeable perc odor) c) a</li> <li>d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) **(see below)</li> <li>e) Halogen leak detector e)</li> </ul>   |
| <ul> <li>**If using direct-reading instrumentation, is the equipment:</li></ul>  |
| Jeffrey Dizek 12/21/2006   |
| Inspector's Name (Please Print) Date of Inspection   |
| 12/2007  |

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: