NUMERIAL PROTECTION	
San Van	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY ARMS COMPLAINT NO:	ζ (CI)
AIRS ID#: 0112229 DAT	E: <u>08/19/09</u>	ARRIVE: <u>2:00PM</u>	DEPART: <u>2:45PM</u>
FACILITY NAME: THE	DRY CLEANER		
FACILITY LOCATION:	3097 NW 62nd Street		
	FT LAUDERDALE 33	309-1709	
OWNER/AUTHORIZED	REPRESENTATIVE: EHAI	B MAURAD PHONE:	(954)970-6020
CONTACT NAME:		PHONE:	
ENTITLEMENT PERIOI	D: 8/3/2006 / 8/3/2011 (effective date) (end date)		
PART I: INSPECTION COMPLIANCE STATUS (check I only one box) IN COMPLIANCE IN COMPLIANCE IN COMPLIANCE			
PART II: <u>FACILITY</u> CL. (check ☑ only	ASSIFICATION - Rule 62-21 one box in A)	.3.300 FAC	
A. 1. Existing small a dry-to-dry only transfer only, x both types, x < (constructed be	r, x < 140 gal/yr < 200 gal/yr 140 gal/yr	2. <u>New small area source</u> dry-to-dry only, x < 140 g transfer only, x < 200 gal both types, x < 140 gal/yr (constructed on or after 12	l/yr r
transfer only, 20	$x, 140 \le x \le 2,100$ gal/yr $00 \le x \le 1,800$ gal/yr $x \le 1,800$ gal/yr	4. New large area source dry-to-dry only, $140 \le x \le$ transfer only, $200 \le x \le 1$ both types, $140 \le x \le 1,80$ (constructed on or after 12)	,800 gal/yr 00 gal/yr
facility exceeds	of business/petroleum s above limits		
B . The total quantity cleaning facility wa		chased within the preceding 12 n	nonths by this dry

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	\forall Yes \Box No \Box N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)			
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>		
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped with a refrigerated	
А.	Has the responsible official of all <u>existing large area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	Yes No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes No	

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No			
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? a) Is the temperature differential equal to, or greater than 20° F?	- Yes No N/A Yes No N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A			
D A	DADE V. DECODDIZEEDING DECITIDEMENTS D_{1} (2, 212, 200/2) EAC				

PART V: <u>RECORDREEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(check \blacksquare only one box for	
Does the responsible official:		each question)	
1.	Maintain receipts for perc purchased?	Yes No	
2.	Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No	
3.	Maintain leak detection inspection and repair reports for the following:		
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A	
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No 🖾 N/A	
4.	Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A	
5.	Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A	
6.	Maintain a startup/shutdown/malfunction plan?	🛛 Yes 🗌 No	
7.	Maintain deviation reports?	Yes No N/A	
	a) Problem corrected?	Yes No N/A	
8.	Maintain a compliance plan, if applicable?	Yes No N/A	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No
2. Does the facility maintain a leak log?	Xes No
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps e) Solvent tanks and containers f) Water separators Yes □No □N/A Yes □No □N/A K) Cartrie Yes □No □N/A K) Cartrie 	st dampers XYes No N/A er valves XYes No N/A
4. Which method(s) of detection (is/are) used by the responsible official?	
 a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) e) Halogen leak detector 	b)
 **If using direct-reading instrumentation, is the equipment:	ppm? 1) Yes No 'ID only)? 2) Yes No 3) Yes No 4) Yes No
Elizabeth F. Susky	08/19/2009
Inspector's Name (Please Print)	Date of Inspection

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: