STATES .
1 - Jan
FLORIDA
10-0000000000

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	L (INS1, INS2)	COMPLAINT/DIS	
AIRS ID#: 0990391 DATE: <u>1/30/</u> 2	2008	ARRIVE: <u>1:00 PM</u>	DEPART: <u>1:30 PM</u>
FACILITY NAME: CELEBRITY	CLEANERS		
FACILITY LOCATION: 47:	51 W Atlantic Ave		
DE	ELRAY 33445		
OWNER/AUTHORIZED REPRE	SENTATIVE: JEFFI	REY CAHN P	HONE: (561)498-8900
CONTACT NAME: Same			HONE: (
			HONE: (
	29/2003 / 11/29/200 tive date) (end date)	18	
· · · · · · · · · · · · · · · · · · ·			
PART I: INSPECTION COMPLI	IANCE STATUS (che	eck 🗹 only one box)	
IN COMPLIANCE] MINOR Non-COMPL	LIANCE SIGNI	FICANT Non-COMPLIANCE
PART II: FACILITY CLASSIFIC (check ☑ only one box		3.300 FAC	
A. 1. Existing small area sour dry-to-dry only, x < 140 transfer only, x < 200 ga both types, x < 140 gal/y (constructed before 12/9) gal/yr al/yr yr	2. <u>New small area</u> dry-to-dry only, transfer only, x < both types, x < 1 (constructed on a	x < 140 gal/yr < 200 gal/yr 40 gal/yr
3. Existing large area sound dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1,3$ (constructed before 12/9)	a ≤ 2,100 gal/yr 1,800 gal/yr 800 gal/yr	transfer only, 20	$\begin{array}{l} 140 \leq x \leq 2,100 \text{ gal/yr} \\ 0 \leq x \leq 1,800 \text{ gal/yr} \\ \leq x \leq 1,800 \text{ gal/yr} \end{array}$
5. Ineligible for General F drop store/out of busines facility exceeds above li	ss/petroleum		
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 165 gallons.			

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A

PART IV: <u>PROCESS</u> <u>VENT</u> <u>CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	uipped with a refrigerated			
А.	Has the responsible official of all <u>existing large area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes No N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes No			

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)		
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- XYes No N/A Yes No N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for		
Does the responsible official:	each question)	
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No	
2. Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No	
3. Maintain leak detection inspection and repair reports for the following:		
a) documentation of leaks repaired w/in 24 hrs? or;	- 🛛 Yes 🗌 No 🗌 N/A	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A	
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A	
6. Maintain a startup/shutdown/malfunction plan?	Yes No	
7. Maintain deviation reports?	Yes No N/A	
a) Problem corrected?	- Xes No N/A	
8. Maintain a compliance plan, if applicable?	Yes No N/A	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No	
2. Does the facility maintain a leak log?	Xes No	
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves XYes No N/A g) Mu b) Door gaskets and seating Yes No N/A h) Stil c) Filter gaskets and seating Yes No N/A i) Exh d) Pumps Yes No N/A j) Div. e) Solvent tanks and containers f) Water separators Yes No N/A 	ls XYes No N/A aust dampers Yes No X/A erter valves XYes No N/A	
4. Which method(s) of detection (is/are) used by the responsible offici	al?	
 a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tub e) Halogen leak detector 	b)⊠ c)⊠ es) d)□**(see below)	
 **If using direct-reading instrumentation, is the equipment:		
Jeffrey Dizek	1/30/2008	
Inspector's Name (Please Print)	Date of Inspection	

1/2009

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: