NOWERTAL PROTECTION	
San Van	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCO ARMS COMPLAINT	
AIRS ID#: 1010332 DATE: <u>07.150.2010</u>	ARRIVE: <u>1435</u>	DEPART: <u>1525</u>
FACILITY NAME: CARRIAGE TRADE DRY CLEAN	ERS	
FACILITY LOCATION: 38225 12th Ave		
ZEPHYRHILLS 33540-	-	
OWNER/AUTHORIZED REPRESENTATIVE: DAN	IEL BENOIT PHC	DNE: (813)788-9808
CONTACT NAME: Daniel Benoit	РНС	DNE: (813)788-9808
ENTITLEMENT PERIOD: 8/5/2006 / 8/5/2011 (effective date) (end date)		
PART I: INSPECTION COMPLIANCE STATUS (che IN COMPLIANCE MINOR Non-COMPL		CANT Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION (check I only one box in A) - Rule 62-2	213.300 FAC	
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)3. Existing large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)5. Ineligible for General Permit \Box d rop store/out of business/petroleum / 		<pre>< 140 gal/yr 200 gal/yr 9 gal/yr after 12/9/91) urce $0 \le x \le 2,100$ gal/yr $\le x \le 1,800$ gal/yr $x \le 1,800$ gal/yr</pre>

B. The sum of the volume of all perchloroethylene (perc) purchases made in each of the previous 12 months by this dry cleaning facility was 20.00 gallons.

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			check ☑ x for each c	only one question)
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	🗌	Yes	🗌 No	N/A
2. Are all perc. containers leak free ?	🗌	Yes	🗌 No	N/A
3. Are all machine doors kept closed and secured except during loading/unloading?	🗌	Yes	🗌 No	
 Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal? 	🖂	Yes	🗌 No	N/A
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.	🛛	Yes	No	N/A
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	🛛	Yes	🗌 No	N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an <u>existing large area source</u>, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all <u>existing large area & new sources</u> :	•	check ☑ x for each c	only one question)
1.	Equipped all machines with the appropriate vent controls?	Yes	🗌 No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	🗌 No	N/A
	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	🗌 No	N/A
	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	🗌 No	N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	🗌 No	N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	🗌 No	

PA	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)					
	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	🗌 No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly? a) Is the temperature differential equal to, or greater than 20° F?		Yes Yes	□ No □ No		N/A N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	🗌 No	N N	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	🗌 No	N N	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	🗌 No	N N	N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	🗌 No	N N	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	🗌 No	N N	N/A

PA	RT V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			check 🗹	only one question)
1.	Are receipts maintained for all perc purchased?	\boxtimes	Yes	🗌 No	
2.	Are rolling monthly total s of yearly perc consumption maintained ?	\boxtimes	Yes	🗌 No	
3.	Are leak detection inspection and repair reports maintained for the following:				
	a) Of any leaks repaired w/in 24 hrs? or;	\boxtimes	Yes	🗌 No	N/A
	b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	\boxtimes	Yes	🗌 No	□ N/A
4.	Is calibration data maintained for applicable direct reading instruments?		Yes	🗌 No	N/A
5.	Is exhaust duct monitoring data on perc concentrations maintained?		Yes	🗌 No	N/A
6.	Is a startup/shutdown/malfunction plan maintained for each machine?		Yes	🗌 No	
7.	Are deviation reports maintained?		Yes	🗌 No	N/A
	a) Problem corrected?	\boxtimes	Yes	🗌 No	N/A
8.	Is a compliance plan maintained , if applicable?		Yes	🗌 No	N/A

P	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	(check	✓ only one
1.	What type of leak detection equipment is used to detect leaks?		each question)
	Halogenated hydrocarbon detector PCE gas analyzer None used		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to		
	the manufacturer's instructions (manual was available and RO could demonstrate		
	procedure) ?	Yes	No
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer		
	operated according to EPA Method 21 ?	Yes	No 🗌 N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of		
	each component interface where leakage could occur and moving it slowly along		
	the interface periphery?	Yes	No
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or		
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per		
	million by volume (based on documented specifications) ?	Yes	No 🛛 N/A
6.	Is the halogenated hydrocarbon detector capable of detecting vapor concentrations		
	of PCE of 25 parts per million by volume (based on documented specifications) and		
	indicating a concentration of 25 parts per million by volume or greater by emitting		
	an audible or visual signal that varies as the concentration changes? \square	Yes	No 🗌 N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or touch)	while the
	system is in operation (§63.322(k))?		
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection of perc	eptible leaks)
	b) Door gaskets and seating Yes No N/A h) Stills	Yes IN Yes IN Yes IN	Io X N/A Io N/A Io N/A Io N/A Io N/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halog	genated hydro	carbon detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph shall sati	sfy the
	requirements to conduct an inspection for perceptible leaks under $63.322(k)$ or (l)		
	b) Door gaskets and seating Yes No N/A h) Stills c) Filter gaskets and seating Yes No N/A i) Exhaust dampers	Yes I N Yes I N Yes I N	Io \boxtimes N/AIo \square N/AIo \square N/AIo \square N/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 6	2-213.300 FAC (continued)						
 9. What evidence suggests that leak checks are performed as required? 							
Joseph V. Panetta	07.15.2010						
Inspector's Name (Please Print)	Date of Inspection						
Inspector's Signature	Approximate Date of Next Inspection						
COMMENTS: Spoke with Mr. Benoit gave him copy of b Showed Mr. Benoit the expiration date on the inspection and e	blank inspection report and rule/registration form.	nod to Mr					

Showed Mr. Benoit the expiration date on the inspection and explained that his permit expires August 5, 2011. I explained to Mr. Benoit the registration form needs to be in Tallahassee at least 30 days prior to August 5, 2011. After inspecting facility using the inspection checklist facility seems to be in compliance.