NOWBILL PROTECTION	
on Val	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY ARMS COMPLAINT NO:	Ϋ́ (CI)
AIRS ID#: 0950289 DAT	E: <u>12/04/2008</u>	ARRIVE: <u>10:45 a.m.</u>	DEPART: <u>11:10 a.m.</u>
FACILITY NAME: ACM	IE CLEANERS		
FACILITY LOCATION:	600 N Westmoreland Dri	ve	
	ORLANDO 32805		
OWNER/AUTHORIZED	<b>REPRESENTATIVE:</b> JIM F	PARHAM <b>PHONE</b> :	(407)841-2301
CONTACT NAME: Jim	Parham	PHONE:	(407)841-2301
ENTITLEMENT PERIOI	<b>D:</b> 9/21/2006 / 9/21/2011 (effective date) (end date)		
PART I: INSPECTION COMPLIANCE STATUS (check I only one box)         □ IN COMPLIANCE □ MINOR Non-COMPLIANCE □ SIGNIFICANT Non-COMPLIANCE			
PART II: <u>FACILITY</u> CL (check ☑ only	ASSIFICATION - Rule 62-21 one box in A)	3.300 FAC	
A. 1. Existing small a dry-to-dry only, transfer only, x both types, x < (constructed be	, x < 140 gal/yr < 200 gal/yr 140 gal/yr	2. <u>New small area source</u> dry-to-dry only, x < 140 g transfer only, x < 200 gal both types, x < 140 gal/yn (constructed on or after 1	l/yr r
transfer only, 20 both types, 140 (constructed be	, $140 \le x \le 2,100$ gal/yr $00 \le x \le 1,800$ gal/yr $\le x \le 1,800$ gal/yr fore 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le$ transfer only, $200 \le x \le 1$ both types, $140 \le x \le 1.80$ (constructed on or after 1	l,800 gal/yr 00 gal/yr
facility exceeds	of business/petroleum s above limits	chased within the preceding 12 n	nonths by this dry
cleaning facility wa			

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be equip condenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated	
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each ques	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	□No	N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	No		

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)			
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A	
	a) Is the temperature differential equal to, or greater than 20° F?	Yes No N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC Does the responsible official:	(check ☑ only one box for each question)
1. Maintain receipts for perc purchased?	
<ol> <li>Maintain rolling monthly total of yearly perc consumption?</li> <li>Maintain leak detection inspection and repair reports for the following:</li> </ol>	Yes   No
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A
6. Maintain a startup/shutdown/malfunction plan?	- Yes No
7. Maintain deviation reports?	- $\bigotimes$ Yes $\square$ No $\bigotimes$ N/A
a) Problem corrected?	- $\Box$ Yes $\Box$ No $\boxtimes$ N/A
8. Maintain a compliance plan, if applicable?	- Yes No N/A

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Yes No		
2. Does the facility maintain a leak log?	Xes No		
	g) Muck cookers XYes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes No N/A		
4. Which method(s) of detection (is/are) used by the responsible official?			
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li></ul>			
Efren Vazquez	12/04/2008		
Inspector's Name (Please Print)	Date of Inspection		
	12/04/2009		
Inspector's Signature	Approximate Date of Next Inspection		

**COMMENTS:** Facility was in compliance during the annual inspection that was performed on this date.