

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2)  RE-INSPECTION (FUI)	COMPLAINT/D	AINT NO:
AIRS ID#: 0950293 DAT	TE: <u>1/19/2011</u>	ARRIVE: <u>10:40</u>	DEPART: <u>11:15</u>
FACILITY NAME: ORG	CHID CLEANERS		
FACILITY LOCATION	: 111 S Orlando Ave		
	MAITLAND 32751		
OWNER/AUTHORIZED Email: CONTACT NAME: Email: ENTITLEMENT PERIO	<b>DE:</b> 3/29/2007 / 3/29/2012 (effective date) (end date)		PHONE: (407)644-0210 Mobile: PHONE: Mobile:
PART I: INSPECTION  ☑ IN COMPLIANC	COMPLIANCE STATUS (ch	·	NIFICANT Non-COMPLIANCE
PART II: FACILITY CI (check ✓ o	LASSIFICATION - Rule 62- nly one box in A)	-213.300 FAC	
transfer only, 3 both types, x < (constructed be 3. Existing large dry-to-dry only transfer only, 2 both types, 14 (constructed be 5. Ineligible fo	y, x < 140 gal/yr x < 200 gal/yr (140  gal/yr) efore 12/9/91) e area source y, 140 $\leq$ x $\leq$ 2,100 gal/yr $(200)$ $\leq$ x $\leq$ 1,800 gal/yr $(0)$ $\leq$ x $\leq$ 1,800 gal/yr efore 12/9/91) r General Permit $(10)$ to of business/petroleum /	transfer only, both types, x (constructed of types).  4. New large ar dry-to-dry on transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)
	olume of all perchloroethylene was 60.0 gallons.	(perc) purchases made	e in each of the previous 12 months by this dry

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o	
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes		No		N/A
2.	Are all perc. containers leak free ?		Yes		No		N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes		No		
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	$\boxtimes$	Yes		No		N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	$\boxtimes$	N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds						
	maintain according to the manufacturer's specifications?		Yes		No	$\boxtimes$	N/A
PA	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC						
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)						
	1. If the f acility classification is an existing small area source, no controls are required. P	rocee	ed to P	art V	•		
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. <b>Complete section A. below.</b>	with a	a refrig	erateo	1		
	3. If the fa cility classification is an <b>existing large area source</b> , the machine should be equiprefrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Compute have been installed prior to September 22, 1993</i>				a		
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refrig	gerate	d		
<b>A.</b>	Has the responsible official of all existing large area & new sources:					only o	
1.	Equipped all machines with the appropriate vent controls?	$\boxtimes$	Yes		No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	$\boxtimes$	Yes		No		N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		No		N/A
1							
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	$\boxtimes$	Yes		No		N/A
	Measured and recorded the temperature of the outlet exhaust stream of a		Yes Yes		No No		N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No	_	N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual	П	Yes		No		N/A
condenser coils?	_					
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
		Yes		No		N/A
		Yes		No		N/A
		(	(check	<b>V</b> (	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?  PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC		(bo	check ox for each	☑ o	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	check	☑ ( ach q	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	check	☑ o	only o	ne
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes Yes	check	ach q No No	only o	ne n)
6. Is airflow routed to the carbon adsorber (if used) at all times?		(bo	(check   ox for each	☑ ( ach q	only o	ne
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check	nach q No No No No	only of uestion	ne n) N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check lox for each	izach q ach q No No No	only ouestion	ne n) N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check	oach quach q	only ouestion	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check	No	only of uestion	ne n) N/A N/A N/A
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  1. Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes	check lox for each	No No No No No No No	only ouestion	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? $\boxtimes$	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills X		<ul><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>
8.	Are the following dry cleaning system components inspected $\underline{monthly}$ for $\underline{vapor\ leaks}$ using a halogen $\underline{monthly}$ for $\underline{monthly}$ f	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the system)	raph sh	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating   Yes   No   N/A   N/A   N/A   Stills   Yes   Yes   No   N/A   N/A   N/A   N/A   N/A   N/A   Yes   Yes   Yes   Yes   Yes   N/A   N/A   Yes	Yes Yes Yes Yes Yes	<ul><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>

e 62-213.300 FAC (continued)	
as required?  On-site observation other	
1/19/20111	
Date of Inspection	
~1/2012	
1/2012	
	as required?  On-site observation other  1/19/20111  Date of Inspection