INCOMPANY PROTECTION	
and the	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)			
AIRS ID#: 0950294 DATE: <u>09/11/08</u>	ARRIVE: <u>9:30 a.m.</u> DEPART: <u>10:20 a.m.</u>			
FACILITY NAME: J'S CLEANERS				
FACILITY LOCATION: 2246 Semoran Blvd				
АРОРКА 32703				
OWNER/AUTHORIZED REPRESENTATIVE: JAY F	PATEL PHONE: (407)880-1933			
CONTACT NAME: Jay Patel	PHONE: (407)880-1933			
ENTITLEMENT PERIOD: 9/21/2006 / 9/21/2011 (effective date) (end date)				
PART I: INSPECTION COMPLIANCE STATUS (check I only one box) IN COMPLIANCE IN COMPLIANCE IN COMPLIANCE IN MINOR Non-COMPLIANCE				
PART II: FACILITY CLASSIFICATION - Rule 62-21. (check 🗹 only one box in A)	3.300 FAC			
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)			
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)			
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 45 gallons.				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	🖾 Yes 🗌 No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be equip condenser. Complete both sections A and B below.	luipped v	vith a ref	frigerated	
А.	Has the responsible official of all <u>existing large area & new sources</u> :		☑ only each que	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No		

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No		
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A Yes No N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A		

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for					
Does the responsible official:	each question)				
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No				
2. Maintain rolling monthly total of yearly perc consumption?	Yes No				
3. Maintain leak detection inspection and repair reports for the following:					
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A				
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	□ Yes □ No □ N/A				
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A				
5. Maintain exhaust duct monitoring data on perc concentrations?	- Yes No N/A				
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No				
7. Maintain deviation reports?	- 🗌 Yes 🗌 No 🖾 N/A				
a) Problem corrected?	🗌 Yes 🗌 No 🖾 N/A				
8. Maintain a compliance plan, if applicable?	- Yes No N/A				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No			
2. Does the facility maintain a leak log?	Xes No			
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps	Muck cookers Yes No N/A Stills Yes No N/A Exhaust dampers Yes No N/A Diverter valves Yes No N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
 a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor)	b) ⊠ c) ⊠ tubes) d) □**(see below) e) ⊠ e) ⊠ Image: a triangle a tri			
Efren Vazquez	09/11/08			
Inspector's Name (Please Print)	Date of Inspection			
	09/11/09			
Inspector's Signature	Approximate Date of Next Inspection			

COMMENTS: Facility was in compliance during the annual inspection that was performed on this date.