

PERCHLOROETHYLENE DRY CLEANERS

COMPLIANCE INSPECTION CHECKLIST

Environmental Compliance

	NNUAL (INS1, INS2)	COMPLAINT/DISCO ARMS COMPLAINT		
AIRS ID#: 0694809 DATE:	: <u>February 29, 2008</u>	ARRIVE: <u>11:00</u>	DEPART: <u>11:20</u>	
FACILITY NAME: A-1 CL	LEANERS			
FACILITY LOCATION:	2800-A S Bay St			
	EUSTIS 32726			
OWNER/AUTHORIZED R	EPRESENTATIVE: DAI	LLAS DUNCAN PHO	ONE: (352)357-5565	
CONTACT NAME:	CONTACT NAME: PHONE:			
ENTITLEMENT PERIOD:	: 8/21/2006 / 8/21/2011 (effective date) (end date)			
PART I: INSPECTION CC	MDI IANCE STATUS (a)	heek 🗹 only one hoy)		
PART I: <u>INSPECTION CC</u> \square IN COMPLIANCE	MINOR Non-COM		CANT Non-COMPLIANCE	
PART II: FACILITY CLAN (check I only on		213.300 FAC		
A. 1. <u>Existing small ar</u> dry-to-dry only, x transfer only, x < both types, x < 14 (constructed befo	x < 140 gal/yr 200 gal/yr 40 gal/yr	2. <u>New small area so</u> dry-to-dry only, x < transfer only, x < 2 both types, x < 140 (constructed on or	< 140 gal/yr 200 gal/yr) gal/yr	
	$140 \le x \le 2,100 \text{ gal/yr}$ $0 \le x \le 1,800 \text{ gal/yr}$ $(x \le 1,800 \text{ gal/yr})$ ore 12/9/91)	4. New large area so dry-to-dry only, 14 transfer only, $200 \le$ both types, $140 \le x$ (constructed on or	$40 \le x \le 2,100$ gal/yr $\le x \le 1,800$ gal/yr $x \le 1,800$ gal/yr	
8	business/petroleum bove limits			

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check 🗹 only one box		
Does the responsible official of the dry cleaning facility:	for each question)		
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A		
2. Examine the containers for leakage?	Yes No N/A		
3. Close and secure machine doors except during loading/unloading?	🖾 Yes 🔲 No		
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A		
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A		

	RT IV: <u>PROCESS VENT</u> <u>CONTROLS</u> – Rule 62-213.300 FAC				
(Refer to Part II-A.14. Classification: page $\underline{1}$ of $\underline{4}$, this form)					
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be equip condenser. Complete both sections A and B below.	luipped w	with a refi	rigerated	
А.	Has the responsible official of all <u>existing large area & new sources</u> :		only ach ques	one box for tion)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	No	N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	⊠Yes	No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	No		

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
B.	. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	Yes No N/A		
	a) Is the temperature differential equal to, or greater than 20° F?	Yes No N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	- Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A		
	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			
PA Do	(check ☑ only one box for each question)			
1.	Maintain receipts for perc purchased?	- Xes No		
2.	Maintain rolling monthly total of yearly perc consumption?	Yes 🗌 No		
3.	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	- Xes No N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A		
4.	Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A		

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

5. Maintain exhaust duct monitoring data on perc concentrations? -----

6. Maintain a startup/shutdown/malfunction plan? ------

7. Maintain deviation reports? -----

8. Maintain a compliance plan, if applicable? -----

a) Problem corrected? ------

(check ☑ only one box for each question)

 \Box Yes \Box No \boxtimes N/A

 \boxtimes Yes \square No \square N/A

Yes No N/A

 \Box Yes \Box No \boxtimes N/A

Yes No

detection and repair inspection?
2. Does the facility maintain a leak log? Xes I No
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves
4. Which method(s) of detection (is/are) used by the responsible official?
 a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) d) **(see below) e) Halogen leak detector e)
**If using direct-reading instrumentation, is the equipment: ** X/A
 Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) Yes Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) Yes Inspected for leaks and obvious signs of wear on a weekly basis? 3) Yes Kept in a clean and secure area when not in use? 4) Yes Verified for accuracy by use of duplicate samples (calorimetric only)? 5) Yes

Michael Young

Inspector's Name (Please Print)

February 29 2008

Date of Inspection

March 2009

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS: