NOWBILL PROTECTION	
on Nat	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:       ANNUAL (INS1, INS2)         RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)			
AIRS ID#: 0112244 DATE: <u>08/20/2009</u>	ARRIVE: <u>2:30PM</u> DEPART: <u>3:30PM</u>			
FACILITY NAME: JL DRY CLEANERS				
<b>FACILITY LOCATION:</b> 6081 West Sunrise Blvd				
PLANTATION 33313-	-6803			
OWNER/AUTHORIZED REPRESENTATIVE: HYE	EUK LEE <b>PHONE:</b> (954)584-0028			
CONTACT NAME:	PHONE:			
ENTITLEMENT PERIOD: 8/25/2006 / 8/25/2011 (effective date) (end date)				
[				
PART I: INSPECTION COMPLIANCE STATUS (ch	eck 🗹 only one box)			
IN COMPLIANCE IMINOR Non-COMP	LIANCE SIGNIFICANT Non-COMPLIANCE			
PART II:       FACILITY       CLASSIFICATION       - Rule 62-21         (check I only one box in A)	13.300 FAC			
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)			
<ul> <li>3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr (constructed before 12/9/91)</li> <li>5. Inclinible for Correct Permit</li> </ul>	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)			
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits				
<b>B</b> . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 20-40 gallons.				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	🛛 Yes 🗌 No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a <b>Existing small area source</b> , no controls are required. <b>Proceed to Part V.</b>				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped w	ith a ref	rigerated	
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only ach ques	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No		

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No			
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A Yes No N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A			
<b>D</b> 4	DE LA DECODDIZEEDING DECLUDENCENTS DI CAMAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA				

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check $\blacksquare$ only one box for		
Does the responsible official:	each question)		
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No		
2. Maintain rolling monthly total of yearly perc consumption?	Yes No		
3. Maintain leak detection inspection and repair reports for the following:			
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A		
<ul> <li>b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul>	Yes 🗌 No 🛛 N/A		
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A		
5. Maintain exhaust duct monitoring data on perc concentrations?	- Xes No N/A		
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No		
7. Maintain deviation reports?	- 🗌 Yes 🗌 No 🖾 N/A		
a) Problem corrected?	Yes No N/A		
8. Maintain a compliance plan, if applicable?	- 🛛 Yes 🗌 No 🗌 N/A		

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No		
2. Does the facility maintain a leak log?	Xes No		
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves Xes No N/A g) 1</li> <li>b) Door gaskets and seating Yes No N/A h) 5</li> <li>c) Filter gaskets and seating Yes No N/A i) E</li> <li>d) Pumps Yes No N/A j) 1</li> <li>e) Solvent tanks and containers</li> <li>f) Water separators Yes No N/A</li> </ul>	Muck cookers       Yes       No       N/A         Stills       Yes       No       N/A         Exhaust dampers       Yes       No       N/A         Diverter valves       Yes       No       N/A		
4. Which method(s) of detection (is/are) used by the responsible official?			
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li></ul>			
Elizabeth F. Susky	08/20/2009		
Inspector's Name (Please Print)	Date of Inspection		
	08/20/2010		
Inspector's Signature	Approximate Date of Next Inspection		

**COMMENTS:** In a compliance inspection on 08/20/09, AQD staff observed operations at JL Dry Cleaners (was Boston Man Cleaners). Mr. Lee was present for the inspection. Houskeeping was excellent and record-keeping was excellent.