

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVE	RY (CI)		
	RE-INSPECTION (FUI)	ARMS COMPLAINT NO):		
AIRS ID#: 0250715 DATE: <u>11/14/2008</u> ARRIVE: <u>1:45P.M.</u> DEPART: <u>2:10P.M.</u>					
FACILITY NAME: CROWN CUSTOM CLEANERS					
FACILITY LOCATION	N: 2025 NE 163 Street				
	NORTH MIAMI BEACH	H 33162-4901			
OWNER/AUTHORIZED REPRESENTATIVE: SOLOMON HASHIM PHONE: (305)944-5009					
CONTACT NAME:		PHONI	Ξ:		
ENTITLEMENT PERIOD: 12/21/2006 / 12/21/2011					
	(effective date) (end date)				
PART I: INSPECTION	COMPLIANCE STATUS (che	eck 🗹 only one box)			
☐ IN COMPLIANO	CE MINOR Non-COMPI	LIANCE SIGNIFICAL	NT Non-COMPLIANCE		
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check ☑ only one box in A)					
A. 1. Existing smal dry-to-dry on transfer only, both types, x	ll area source ly, x < 140 gal/yr x < 200 gal/yr	2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 gboth types, x < 140 gal (constructed on or after	0 gal/yr gal/yr /yr		
transfer only, both types, 14	e area source \Box ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ before $12/9/91)$	4. New large area source dry-to-dry only, $140 \le$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	x ≤ 2,100 gal/yr ≤ 1,800 gal/yr 1,800 gal/yr		
drop store/ou	t of business/petroleum ds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 60 gallons.					

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box					
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
	only one box for ach question)			
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	∕es □No			
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? T	∕es □ No □N/A			
a) Is the temperature differential equal to, or greater than 20° F?	Yes No N/A			
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes □ No □ N/A			
a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A			
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	∕es □ No □ N/A			
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?				
6. Route airflow to the carbon adsorber (if used) at all times?	∕es □ No □ N/A			
	1			
	☑ only one box for ach question)			
1. Maintain receipts for perc purchased?	Yes No			
2. Maintain rolling monthly total of yearly perc consumption?	Yes No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	Yes No No N/A			
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No No N/A			
6. Maintain a startup/shutdown/malfunction plan? 🖂	Yes No			
7. Maintain deviation reports?	Yes No N/A			
a) Problem corrected?	Yes No N/A			
8. Maintain a compliance plan, if applicable?	Yes No N/A			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?				
• •				
2. Does the facility maintain a leak log? \(\sum \text{Yes} \subseteq \text{No}				
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	Ils			
4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces)				
MARUFUL MALIK	11/14/08			
Inspector's Name (Please Print)	Date of Inspection			
	11/09			
Inspector's Signature	Approximate Date of Next Inspection			
	16			

COMMENTS: I visited this facility to conduct an annual inspection. Aziz Hoodbhoy, manager, assisted me with the inspection. No leaks were detected. PERC purchase records were available.