| C.C. |
|-----------|
| FLORIDA 1 |

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE: ANNUAL (INS1, INS2) | COMPLAINT/DISCOVERY (CI) | | | | |
|---|---|--|--|--|--|
| AIRS ID#: 0112245 DATE: 01/18/2007 | ARRIVE: <u>10:00</u> DEPART: <u>10:30</u> | | | | |
| FACILITY NAME: PORT ROYALCLEANERS | | | | | |
| FACILITY LOCATION: 6604 N Federal Hwy | | | | | |
| FT LAUDERDALE | 33308 | | | | |
| RESPONSIBLE OFFICIAL: DOK YUN | PHONE: (954)938-0836 | | | | |
| CONTACT NAME: | PHONE: | | | | |
| REMITTANCE YEAR: 2005 ENTIT | LEMENT PERIOD: 9/23/2004 / 9/23/2009 (effective date) (end date) | | | | |
| PART I: INSPECTION COMPLIANCE STATUS (check I only one box) IN COMPLIANCE IN COMPLIANCE IN COMPLIANCE | | | | | |
| PART II: FACILITY CLASSIFICATION - Rule 62 | -213.300 FAC | | | | |
| (check \blacksquare only one box in A) A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr | 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr both types, 140 ≤ x ≤ 1,800 gal/yr | | | | |
| (constructed before 12/9/91) 5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits | both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$) burchased within the preceding 12 months by this dry | | | | |

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC | (check 🗹 only one box |
|--|--|
| Does the responsible official of the dry cleaning facility: | for each question) |
| 1. Store perc, and wastes containing perc, in tightly sealed & impervious containers? | \bigvee Yes \square No \square N/A |
| 2. Examine the containers for leakage? | \bigvee Yes \square No \square N/A |
| 3. Close and secure machine doors except during loading/unloading? | Yes No |
| 4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal? | Yes No N/A |
| 5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications? | Yes No N/A |

| PART IV:PROCESSVENTCONTROLS– Rule 62-213.300 FAC(Refer to Part II-A.14. Classification: page 1 of 4, this form) | | | | |
|---|---|-----------|--------------------|-----------------------|
| | 1. If the facility classification is a Existing small area source, no controls are required. Proceed to Part V. | | | |
| | 2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | |
| | 3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i> | | | |
| | 4. If the facility classification is a <u>New large area source</u> , the machine should be eacondenser. Complete both sections A and B below. | quipped v | with a ref | frigerated |
| А. | Has the responsible official of all <u>existing large area & new sources</u> : | | ☑ only each que | one box for stion) |
| 1. | Equipped all machines with the appropriate vent controls? | Yes | No | |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system? | Yes | No | □N/A |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | Yes | No | □N/A |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | Yes | No | |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | Yes | No | □N/A |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | Yes | No | |

| PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued) | | | | |
|---|--|---|--|--|
| B. | Does the responsible official of an existing large or new large area source also: | (check ☑ only one box for each question) | | |
| 1. | Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? | Yes No | | |
| | Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? | - Yes No N/A Yes No N/A | | |
| 3. | Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | Yes No N/A | | |
| | a) Is the perc concentration equal to, or less than 100 ppm? | Yes No N/A | | |
| 4. | Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | Yes No N/A | | |
| 5. | Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? | - Yes No N/A | | |
| 6. | Route airflow to the carbon adsorber (if used) at all times? | Yes No N/A | | |
| | | | | |
| D 4 | | | | |

| PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC | | (check 🗹 only one box for | | |
|--|---|---------------------------|--|--|
| Does the responsible official: | | each question) | | |
| 1. | Maintain receipts for perc purchased? | Yes 🗌 No | | |
| 2. | Maintain rolling monthly total of yearly perc consumption? | 🖂 Yes 🗌 No | | |
| 3. | Maintain leak detection inspection and repair reports for the following: | | | |
| | a) documentation of leaks repaired w/in 24 hrs? or; | - Yes No N/A | | |
| | b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | ☐ Yes ☐ No 🖾 N/A | | |
| 4. | Maintain calibration data? (for applicable direct reading instruments) | Yes No N/A | | |
| 5. | Maintain exhaust duct monitoring data on perc concentrations? | Yes No N/A | | |
| 6. | Maintain a startup/shutdown/malfunction plan? | 🛛 Yes 🗌 No | | |
| 7. | Maintain deviation reports? | Yes No N/A | | |
| | a) Problem corrected? | - Yes No N/A | | |
| 8. | Maintain a compliance plan, if applicable? | Yes No N/A | | |
| | | | | |

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

| detection and repair inspection? | Xes No |
|---|--|
| 2. Does the facility maintain a leak log? | Xes No |
| 3. Does the responsible official check the following areas for leaks a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps e) Solvent tanks and containers f) Water separators 3. Does the responsible official check the following areas for leaks a) Hose connections, fittings, C) Solvent tanks and containers f) Water separators | Muck cookers Yes No N/A Stills Yes No N/A Exhaust dampers Yes No N/A Diverter valves Yes No N/A |
| 4. Which method(s) of detection (is/are) used by the responsible of | fficial? |
| a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) | b) c: : : |
| Elizabeth F. Susky | 01/18/2007 |
| Inspector's Name (Please Print) | Date of Inspection |
| | 01/18/2008 |
| Inspector's Signature | Approximate Date of Next Inspection |

COMMENTS: In a compliance inspection conducted on 01/18/2007, AQD staff observed operations at Port Royale Cleaners. The faciility has excellent housekeeping. Mr.Yun (owner) accompaned AQD staff on the inspection. Mr. Yun recently replaced the epoxy paint around the machine and makes an effort to keep his facility in good order.

No records for a chiller temperatures is required since this is a existing small facility and no controls are required.