

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, IN	SS2) COMPLAINT/DISCOVERY (CI)			
RE-INSPECTION (FUI) ARMS COMPLAINT NO:			
AIRS ID#: 0550039 DATE: <u>02/15/2007</u>	ARRIVE: 1:15 p.m. DEPART: 1:50 p.m.			
FACILITY NAME: FEATHERS' DRY CLEANING				
FACILITY LOCATION: 161 S Commerce Ave				
SEBRING 3	3870			
RESPONSIBLE OFFICIAL: MEL FEATHE	PHONE: (863)382-0771			
CONTACT NAME: PHONE:				
REMITTANCE YEAR: 2005	ENTITLEMENT PERIOD: 8/26/2006 / 8/26/2011 (end date) (end date)			
PART I: INSPECTION COMPLIANCE ST				
☐ IN COMPLIANCE ☐ MINOR N	Non-COMPLIANCE SIGNIFICANT Non-COMPLIANCE			
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check ✓ only one box in A)				
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source	 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source 			
dry-to-dry only, $140 \le x \le 2,100$ ga transfer only, $200 \le x \le 1,800$ gal/y both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$)	dry-to-dry only, $140 \le x \le 2{,}100$ gal/yr			
5. Ineligible for General Permit drop store/out of business/petroleur facility exceeds above limits] n			
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 95 gallons.				

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box	
Does the responsible official of the dry cleaning facility: for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No □N/A	
2.	Examine the containers for leakage?	☐Yes ☐ No ☐ N/A	
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No	
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A	
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)		
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B below <i>must have been installed prior to September 22, 1993</i>		
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated	
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	Yes No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ⊠Yes □No □N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No	

B. Does the responsible official of an existing large or new large area source also: (check ☑ only one box for each question)	
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? ✓ Yes ✓ No	
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? a) Is the temperature differential equal to, or greater than 20° F? Yes □ No □ N/A □ Yes □ No □ N/A	
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? Yes No N/A	
a) Is the perc concentration equal to, or less than 100 ppm?	
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	
6. Route airflow to the carbon adsorber (if used) at all times? Yes No N/A	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: (check ☑ only one box for each question)	
Maintain receipts for perc purchased? □ Yes ☑ No	
2. Maintain rolling monthly total of yearly perc consumption? Yes No	
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or; Yes No N/A	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Yes No N/A	
A Market with section 1 and (C P. 11. P P	
4. Maintain calibration data? (for applicable direct reading instruments) Yes No N/A	
4. Maintain calibration data? (for applicable direct reading instruments)	
, , , , , , , , , , , , , , , , , , ,	
5. Maintain exhaust duct monitoring data on perc concentrations? Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations? Yes No N/A 6. Maintain a startup/shutdown/malfunction plan? Yes No	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?			
2. Does the facility maintain a leak log?			
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	ills		
4. Which method(s) of detection (is/are) used by the responsible official?			
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————			
ROBERT J. STEWART 02/15/2007			
Inspector's Name (Please Print)	Date of Inspection		
	02/08		
Inspector's Signature	Approximate Date of Next Inspection		

COMMENTS: Missing PERC receipt for June 2006 for PERC purchased as indicated on DEP Compliance Calendar. Owner will fax copy of receipt to Department office along with Annual Statement of Compliance. Also discussed EPA requirement for portable leak devices be in use at the facility by July 27, 2008 for existing dry cleaners as defined by the rule.