

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

<u>INSPECTION</u> <u>TYPE</u> : AN	NUAL (INS1, INS2)	COMPLAINT/DISCOVE	ERY (CI)		
RE	-INSPECTION (FUI)	ARMS COMPLAINT NO):		
AIRS ID#: 0250721 DATE: <u>12/19/008</u> ARRIVE: <u>12:35PM</u> DEPART: <u>12:49PM</u>					
FACILITY NAME: LAGUNA PLAZA CLEANERS					
FACILITY LOCATION: 10735 W Flagler Street					
	MIAMI 33174-1421				
OWNER/AUTHORIZED R	EPRESENTATIVE: ADA	MORALES PHONI	E: (305)221-1335		
CONTACT NAME:		PHONI	E:		
ENTITLEMENT PERIOD: 8/15/2003 / 8/15/2008 (effective date) (end date)					
DADEL INCORPORAÇÃO ANA LANCE CITATRICA (1. 1. 7. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.					
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
MY COM EMICE	MINOR Non COM	Entitle Stotulien	TO THE COMMENTAL		
PART II: FACILITY CLAS	CCIEICATION Dule 62 21	2 200 EAC			
(check v only on		3.300 FAC			
A. 1. Existing small are dry-to-dry only, x transfer only, x < both types, x < 14 (constructed before	< 140 gal/yr 200 gal/yr 0 gal/yr	2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 both types, x < 140 ga (constructed on or after	40 gal/yr gal/yr l/yr		
transfer only, $200 \le x \le 1,800 \text{ gal/yr}$ transfer of both types, $140 \le x \le 1,800 \text{ gal/yr}$ both types			e		
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits					
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 105 gallons.					

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a <u>Existing large area source</u> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area</u> & <u>new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ⊠Yes □No □N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ∐Yes ∐No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)	
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)
1. Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	□Yes □No
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A
a) Is the temperature differential equal to, or greater than 20° F?	□Yes □ No □ N/A
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No □ N/A
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No No
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A
6. Route airflow to the carbon adsorber (if used) at all times?	□Yes □ No □ N/A
PART V: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC	(1 1 [] 1
Does the responsible official:	(check ✓ only one box for each question)
1. Maintain receipts for perc purchased?	- Xes No
2. Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or;	- Yes No N/A
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A
4. Maintain calibration data? (for applicable direct reading instruments)	
	Yes No No N/A
5. Maintain exhaust duct monitoring data on perc concentrations?	
5. Maintain exhaust duct monitoring data on perc concentrations?6. Maintain a startup/shutdown/malfunction plan?	Yes No N/A
	Yes No No
6. Maintain a startup/shutdown/malfunction plan?	Yes
6. Maintain a startup/shutdown/malfunction plan?	Yes

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?		
2. Does the facility maintain a leak log?		
3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves	Muck cookers ⊠Yes □No □N/A	
4. Which method(s) of detection (is/are) used by the responsible off a) Visual examination (condensed solvent on exterior surfaces) - b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric te) Halogen leak detector **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of (2) Calibrated against a standard gas prior to and after each use (I 3) Inspected for leaks and obvious signs of wear on a weekly base 4) Kept in a clean and secure area when not in use?	a)	
MARQURS LOPEZ	2/19/08	
Inspector's Name (Please Print)	Date of Inspection	
	2/09	
Inspector's Signature	Approximate Date of Next Inspection	

COMMENTS: ON FEBRUARY 19, 2008 I VISITED THIS FACILITY TO CONDUCT THE ANNUAL COMPLIANCE INSPECTION. ON SITE I MET ADA MORALES, THE OWNER OF THE FACILITY. THERE WERE NO LEAKS IN THE DRY CLEANING MACHINE AND ALL RECORDS WERE AVAILABLE. THE TWELVE MONTH TOTAL OF PERC PURCHASED WAS 105 GALLONS.