

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE :	ANNUAL (INS1, INS2)	COMPLAINT/DISCOV	ERY (CI)				
	RE-INSPECTION (FUI)	ARMS COMPLAINT N	O:				
AIRS ID#: 0950300 DA 7	TE: <u>6/25/09</u>	ARRIVE: <u>09:00</u>	DEPART: <u>09:20</u>				
FACILITY NAME: ACE QUALITY CLEANERS							
FACILITY LOCATION: 431 E Michigan Street							
	ORLANDO 32806						
OWNER/AUTHORIZE	OWNER/AUTHORIZED REPRESENTATIVE: AJAY PATEL PHONE: (407)422-5735						
CONTACT NAME:		PHON	IE:				
ENTITLEMENT PERIOD: 10/16/2006 / 10/16/2011 (effective date) (end date)							
DADTI. INCRECTION	COMPLIANCE STATUS (che	valt 🗹 anly and have)					
IN COMPLIANCE	<u>_</u>	_	ANT Non-COMPLIANCE				
M COMPLIANC	CE MINOR Non-COMPT	LIANCE SIGNIFICA	INT NOIFCOMFEIANCE				
	T A CONTROL TO A CA AA	2 200 714 6					
	<u>LASSIFICATION</u> - Rule 62-21: y one box in A)	3.300 FAC					
transfer only, both types, x	ly, x < 140 gal/yr x < 200 gal/yr	2. New small area sour dry-to-dry only, x < 1 transfer only, x < 200 both types, x < 140 gr (constructed on or aft	40 gal/yr) gal/yr al/yr				
transfer only, both types, 14	e area source ly, $140 \le x \le 2,100 \text{ gal/yr}$ $200 \le x \le 1,800 \text{ gal/yr}$ $40 \le x \le 1,800 \text{ gal/yr}$ perfore $12/9/91)$	4. New large area sourdry-to-dry only, $140 \le x \le 100$ transfer only, $200 \le x \le 100$ types, $140 \le x \le 100$ (constructed on or after the source of the sou	\leq x \leq 2,100 gal/yr \leq 1,800 gal/yr 1,800 gal/yr				
drop store/out	General Permit t of business/petroleum ds above limits						
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 28.6 gallons.							

PA	PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box				
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ☑ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped with a refrigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- Yes No N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- Yes No N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- Yes No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes No N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	☐Yes ☐No			

B. Does the responsible official of an existing large or new large area source also: (check ☑ only one box for each question)	
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? Yes No	
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? Yes No N/A	
a) Is the perc concentration equal to, or less than 100 ppm?	
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	
6. Route airflow to the carbon adsorber (if used) at all times? Yes No N/A	
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: (check ☑ only one box for each question)	
1. Maintain receipts for perc purchased? Yes No	
2. Maintain rolling monthly total of yearly perc consumption? Yes No	
3. Maintain leak detection inspection and repair reports for the following:	
a) documentation of leaks repaired w/in 24 hrs? or; Yes No N/A	
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Yes No N/A	
4. Maintain calibration data? (for applicable direct reading instruments) Yes No N/A	
5. Maintain exhaust duct monitoring data on perc concentrations? Yes No N/A	
6. Maintain a startup/shutdown/malfunction plan? Yes No	
7. Maintain deviation reports?	
a) Problem corrected?	

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?				
b) Door gaskets and seating c) Filter gaskets and seating d) Pumps EYes No N/A h) St Yes No N/A i) Ex Yes No N/A j) Di	fluck cookers Yes No N/A tills Yes No N/A shaust dampers Yes No N/A iverter valves Yes No N/A artridge filter housings Yes No N/A			
4. Which method(s) of detection (is/are) used by the responsible office.	<u></u>			
a) Visual examination (condensed solvent on exterior surfaces)b) Physical detection (airflow felt through gaskets)	b) 🖾			
c) Odor (noticeable perc odor)	c) 🖂			
d) Use of direct-reading instrumentation (FID/PID/calorimetric tu				
e) Halogen leak detector				
**If using direct-reading instrumentation, is the equipment: — ** N/A 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? — 1) Yes No 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? — 2) Yes No 3) Inspected for leaks and obvious signs of wear on a weekly basis? — 3) Yes No 4) Kept in a clean and secure area when not in use? — 4) Yes No 5) Verified for accuracy by use of duplicate samples (calorimetric only)? — 5) Yes No				
Assefa Hailemariam	6/25/2009			
Inspector's Name (Please Print)	Date of Inspection			
	~6/2010			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS: Facility was in compliance during the inspection.				