

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2)  RE-INSPECTION (FUI)	COMPLAINT/DIS	, , , <u>—</u>					
AIRS ID#: 0571056 DAT	E: <u>11-2-2012</u>	ARRIVE: <u>10:50AM</u>	<u>I</u> DEPART: <u>11</u>	:35AM				
FACILITY NAME: FAE	BRICARE CLEANERS							
FACILITY LOCATION	: 13541 N FLORIDA AV	'E						
	TAMPA 33613-3214							
OWNER/AUTHORIZED Email: CONTACT NAME: Email: ENTITLEMENT PERIO	DREPRESENTATIVE: AWA	M F	PHONE: (813)961-6423 Mobile: PHONE: Mobile:					
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)  ☐ IN COMPLIANCE ☑ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE								
	PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC  (check only one box in A)							
transfer only, 3 both types, x < (constructed be 3. Existing large dry-to-dry only transfer only, 2 both types, 146 (constructed be 5. Ineligible fo	y, x < $\overline{140}$ gal/yr x < $200$ gal/yr < $140$ gal/yr efore $12/9/91$ ) e area source y, $140 \le x \le 2,100$ gal/yr $200 \le x \le 1,800$ gal/yr $0 \le x \le 1,800$ gal/yr efore $12/9/91$ ) or General Permit $\Box$ t of business/petroleum /	4. New large area dry-to-dry only, transfer only, 20 both types, 140	, x < 140 gal/yr < 200 gal/yr 140 gal/yr or after 12/9/91)					
	volume of all perchloroethylene of all perchlo	(perc) purchases made i	n each of the previous 12 m	onths by this dry				

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check ox for each		only o		
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes		No		N/A	
2. Are all perc. containers leak free ?	$\boxtimes$	Yes		No		N/A	
3. Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes		No			
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No	$\boxtimes$	N/A	
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	$\boxtimes$	N/A	
6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No	$\boxtimes$	N/A	
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)  1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.  2. If the facility classification is a new small area source, the machine should be equipped with a refrigerated condenser. Complete section A. below.  3. If the facility classification is an existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993  4. If the facility classification is a new large area source, the machine should be equipped with a refrigerated							
A. Has the responsible official of all existing large area & new sources:			check l		•		
1. Equipped all machines with the appropriate vent controls?	$\boxtimes$	Yes	_	No	7	,	
Equipped an inactimes with the appropriate vent controls:      Equipped dry-to-dry machines with a closed-loop vapor venting system?				No		N/A	
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	$\boxtimes$	Yes		No		N/A	
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		No	$\boxtimes$	N/A	
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No	$\boxtimes$	N/A	
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	$\boxtimes$	Yes		No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)							
	For all existing large or new large area sources:						
1.	Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	$\bowtie$	No		
	Tooldinor, and dryer machines measures and recorded on a meeting case.		100		110		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured		<b>T</b> 7		NT.		3T/A
	and recorded weekly?		Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?	Ш	Yes	Ш	No	$\bowtie$	N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly						
	at the end of the final drying cycle while the machine is venting to the adsorber,	_		_		_	
	if machines are equipped exclusively with a carbon adsorber?		Yes		No	$\boxtimes$	N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No	$\boxtimes$	N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring						
	perc concentrations at least 8 duct diameters downstream of any bend,						
	contraction, or expansion; is at least 2 duct diameters upstream from any bend,						~ · · ·
	contraction, or expansion; and downstream from no other inlet?	Ш	Yes	Ш	No	$\bowtie$	N/A
5	Are transfer machines equipped (dryers, reclaimers, and washers) with individual						
$\sim$ .	condenser coils?	П	Yes		No	$\boxtimes$	N/A
-	condenser coils?	ш	105	_			
		_			No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?	_			No		N/A
		_			No		N/A
		_			No		N/A
6.		_	Yes	Check		only o	
6.	Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		<b>V</b>	only o	one
6. <b>P</b> A	Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		<b>V</b>	-	one
6. <b>P</b> A	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo		☑ each o	-	one
6. PA	Is airflow routed to the carbon adsorber (if used) at all times?		Yes (bo		☑ each c	-	one
6. PA	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo		Mo No	questic	one on)
6. PA	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo		☑ each o	-	one
6. PA	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo		Mo No	questic	one on)
1. 2. 3.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo Yes Yes		Meach of No	questic	one on)
1. 2. 3.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes  (bo Yes Yes Yes Yes		No No No	questic	one on) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes  (bo Yes Yes Yes Yes Yes		No No No No No	questic	one on) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased?  Are rolling monthly total s of yearly perc consumption maintained?  Are leak detection inspection and repair reports maintained for the following:  a) Of any leaks repaired w/in 24 hrs? or;  b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?  Is calibration data maintained for applicable direct reading instruments?  Is exhaust duct monitoring data on perc concentrations maintained?		Yes  Yes  Yes  Yes  Yes  Yes  Yes  Yes		No No No No No No No No No	questic	one on) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes  Yes  Yes  Yes  Yes  Yes  Yes  Yes		No	questic	nne nn) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one	
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)	
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used				
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to				
	the manufacturer's instructions (manual was available and RO could demonstrate				
	procedure) ?	Yes	☐ No		
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer				
	operated according to EPA Method 21 ?	Yes	☐ No	N/A	
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of				
	each component interface where leakage could occur and moving it slowly along				
	the interface periphery?	Yes	No No		
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or				
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per				
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A	
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations				
	of PCE of 25 parts per million by volume (based on documented specifications) and				
	indicating a concentration of 25 parts per million by volume or greater by emitting				
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A	
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the	
	system is in operation (§63.322(k))?				
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)	
	b) Door gaskets and seating Yes No N/A h) Stills Y		<ul><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li></ul>	N/A N/A N/A N/A N/A N/A	
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector	
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	ne	
	requirements to conduct an inspection for perceptible leaks under $\S63.322(k)$ or $(l)$ )				
	b) Door gaskets and seating   Yes   No   N/A   N/A   N/A   Stills   Yes   N/A   N/A   N/A   Yes   Yes   N/A   N/A   Yes   Yes	Yes Yes Yes Yes Yes	<ul><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li><li>□ No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>	

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)						
9. What evidence suggests that leak checks are performed as required?  ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other  Explain other:						
Jessica Lopez	11-2-2012					
Inspector's Name (Please Print)	Date of Inspection					
Inspector's Signature	Approximate Date of Next Inspection					

**COMMENTS:** The calendar was completed for both machines today. The temperature for both perc machines was recorded today. EPC staff and Mr. Antonio, who operates the perc machine, looked in the manual to see how to read the cool down cycle and the temperature meter for both machines. However, his temperature meter read -20 degrees for the white. He contacted the manufacturer during this visit. They will be calling him back to see if it should be reading as such. Also, the temperature meter on the white Union perc machine was reading too low (10 degrees F). He was advised to check into it. He will then contact EPC staff to advise. EPC staff spoke with the owner's brother-in-law, Fioazh Hasan who currently runs the business. Apparently, the corporation is still owned by Awad Hasan which is the name reflected on the permit. Therefore, the permit is in compliance.