

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE : ANNUAL	L (INS1, INS2)	COMPLAINT/DISCOV	VERY (CI)			
RE-INSP	ECTION (FUI)	ARMS COMPLAINT N	NO:			
AIRS ID#: 0990411 DATE: <u>3/11/2</u>	<u>2008</u>	ARRIVE: <u>11:15 AM</u>	DEPART: <u>11:55 AM</u>			
FACILITY NAME: CRICKET CLEANERS						
FACILITY LOCATION: 634	FACILITY LOCATION: 6346-70 Lantana Road					
LA	KE WORTH 33463					
OWNER/AUTHORIZED REPRE	SENTATIVE: MICH	HAEL STERNSHEIN	PHONE: (561)434-1662			
CONTACT NAME: Same	CONTACT NAME: Same PHONE: (
ENTITLEMENT PERIOD: 8/14/2006 / 8/14/2011 (effective date) (end date)						
PART I: INSPECTION COMPLI						
	MINOR Non-COMPI	LIANCE SIGNIFIC	ANT Non-COMPLIANCE			
PART II: FACILITY CLASSIFIC (check ☑ only one box		3.300 FAC				
 A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91) 3. Existing large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr 		 2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91) 4. New large area source dry-to-dry only, 140 ≤ x ≤ 2,100 gal/yr transfer only, 200 ≤ x ≤ 1,800 gal/yr 				
 both types, 140 ≤ x ≤ 1,5 (constructed before 12/9 5. Ineligible for General I drop store/out of busines facility exceeds above li 	Permit Ss/petroleum	both types, $140 \le x \le$ (constructed on or at				
 B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 180 gallons. 						

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box		
Do	es the responsible official of the dry cleaning facility:	for each question)		
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A		
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A		
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No		
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A		
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A		
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)			
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Proceed to Part V.		
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.			
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993			
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped with a refrigerated		
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)		
1.	Equipped all machines with the appropriate vent controls?	Yes No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- ⊠Yes □No □N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ⊠Yes □No □N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ⊠Yes □No □N/A		
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No		

PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- ⊠Yes □ No □N/A		
	a) Is the temperature differential equal to, or greater than $20^{\rm o}{\rm F?}$	⊠Yes □ No □ N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No □ N/A		
5	Equip transfer machines (dryers, reclaimers, and washers) with individual			
٥.	condenser coils?	- ☐Yes ☐ No ☒ N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A		
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for				
Do	es the responsible official:	each question)		
1.	Maintain receipts for perc purchased?	Yes No		
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No		
3.	Maintain leak detection inspection and repair reports for the following:			
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No N/A		
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A		
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☐ N/A		
5.				
6.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☒ N/A		
	Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No		
	Maintain a startup/shutdown/malfunction plan? Maintain deviation reports?	Yes □ No □ N/A		
	Maintain a startup/shutdown/malfunction plan?	Yes □ No □ N/A		

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check **☑** only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?	X Yes No			
d) Pumps \bigve{\sum}Yes \bigve{\subset}No \bigve{\subset}N/A j) Diver				
4. Which method(s) of detection (is/are) used by the responsible official (s). Visual examination (condensed solvent on autorior purfecces)	<u>_</u>			
a) Visual examination (condensed solvent on exterior surfaces)				
**If using direct-reading instrumentation, is the equipment:	**			
1) Capable of detecting perc vapor concentrations in a range of 0-500	0 ppm? 1) ☐ Yes ☐ No			
2) Calibrated against a standard gas prior to and after each use (PID/				
3) Inspected for leaks and obvious signs of wear on a weekly basis?4) Kept in a clean and secure area when not in use?				
5) Verified for accuracy by use of duplicate samples (calorimetric on				
5) Volified for decardey by disc of duplicate samples (carefilles)				
Jeffrey Dizek	3/11/2008			
Inspector's Name (Please Print)	Date of Inspection			
•	3/2009			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS:				