

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2)	COMPLAINT/D		/ (CI) [			
AIRS ID#: 1170067 DATE	E: <u>03/23/2011</u>	ARRIVE: <u>9.25 A</u>	<u>M</u>	DEPART: <u>10.15 AM</u>			
FACILITY NAME: 436 C	LEANERS						
FACILITY LOCATION:	1034 E Semoran Blvd						
	CASSELBERRY 32707	7					
OWNER/AUTHORIZED DE Email: CONTACT NAME: Sam Email: ENTITLEMENT PERIOD	-	JNG HWANG	PHONE: Mobile: PHONE: Mobile:	(407)331-4879			
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)  ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION (check only one box in A) - Rule 62-213.300 FAC							
transfer only, 20 both types, 140 (constructed bef	x < 140  gal/yr < 200  gal/yr 140  gal/yr Fore $12/9/91$ ) Frea source $140 \le x \le 2,100 \text{ gal/yr}$ $100 \le x \le 1,800 \text{ gal/yr}$ $100 \le x \le 1,800 \text{ gal/yr}$ Fore $12/9/91$ ) General Permit $100$ of business/petroleum /		ly, x < 140 g x < 200 gal/yr < 140 gal/yr on or after 12 <b>ea source</b> ly, $140 \le x$ $200 \le x \le$ $40 \le x \le$	/yr 2/9/91) ====================================			
<b>B</b> . The sum of the vol cleaning facility wa		(perc) purchases made	e in each of t	the previous 12 months by this dry			

PA	ART III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC			check 🗹 x for each	only one question)				
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	$\boxtimes$	Yes	☐ No	□ N/A				
	Are all perc. containers leak free?	$\boxtimes$	Yes	— □ No					
	Are all machine doors kept closed and secured except during loading/unloading?	$\boxtimes$	Yes	— □ No					
	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes	☐ No	□ N/A				
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	⊠ No	□ N/A				
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	□ No	⊠ N/A				
	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)								
	1. If the f acility classification is an <b>existing small area source</b> , no controls are required. <b>P</b> 1	rocee	ed to P	art V.					
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>								
	3. If the fa cility classification is an <b>existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993								
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated					
Α.	Has the responsible official of all <u>existing large area &amp; new sources</u> :			check 🗹 x for each	•				
1.	Equipped all machines with the appropriate vent controls?		Yes	☐ No					
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes	☐ No	□ N/A				
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes	□ No	□ N/A				
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes	□ No	□ N/A				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes	☐ No	□ N/A				
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	☐ No					

PART IV: PROCESS VENT CONTROLS - Rule 62-213 300 FAC (continued)								
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)								
	For all existing large or new large area sources:  Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No			
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No		N/A	
	a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?	Ш	Yes		No	Ш	N/A	
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A	
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A	
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes		No		N/A	
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A	
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A	
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A	
							N/A	
	Is airflow routed to the carbon adsorber (if used) at all times?		(	check x for e	<b>V</b> (	only o	ne	
PA	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC		(	check x for e	<b>V</b> (	•	ne	
1.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check x for e	☑ ( ach q	•	ne	
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC	$\boxtimes$	(u bo.	check x for e	☑ (ach qu	•	ne	
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————	$\boxtimes$	(u bo.	check x for e	☑ (ach qu	•	ne	
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————	$\boxtimes$	Yes Yes	check x for e	☑ α ach q No No	•	ne n)	
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————	$\boxtimes$	Yes Yes Yes	check x for e	of ach quality No No No	westio	ne n) N/A	
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check x for e	Mo Ach qu No No No	westio	ne n) N/A N/A	
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes	check x for e	Mo No No No No No	westio	ne n) N/A N/A N/A	
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased?  Are rolling monthly total s of yearly perc consumption maintained?  Are leak detection inspection and repair reports maintained for the following:  a) Of any leaks repaired w/in 24 hrs? or;  b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?  Is calibration data maintained for applicable direct reading instruments?  Is exhaust duct monitoring data on perc concentrations maintained?		Yes Yes Yes Yes Yes Yes Yes	check x for e	Mo No No No No No No No	westion	ne n) N/A N/A N/A	
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC  Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes Yes	check x for e	Mo No No No No No No No No No	westion	ne n) N/A N/A N/A	

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one	
1.	What type of leak detection equipment is used to detect leaks?	be	ox for each	question)	
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used				
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to				
	the manufacturer's instructions (manual was available and RO could demonstrate				
	procedure) ?	Yes	☐ No		
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer				
	operated according to EPA Method 21 ?	Yes	☐ No	N/A	
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of				
	each component interface where leakage could occur and moving it slowly along				
	the interface periphery? $\  \  \  \  \  \  \  \  \  \  \  \  \ $	Yes	☐ No		
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or				
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per				
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A	
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations				
	of PCE of 25 parts per million by volume (based on documented specifications) and				
	indicating a concentration of 25 parts per million by volume or greater by emitting				
	an audible or visual signal that varies as the concentration changes? $$	Yes	☐ No	N/A	
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn	nell or	touch) while	le the	
	system is in operation (§63.322(k))?				
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection of the properties	pection	of perceptib	le leaks)	
	b) Door gaskets and seating Yes No N/A h) Stills S		<ul><li>No</li><li>No</li><li>No</li><li>No</li><li>No</li><li>No</li><li>No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>	
8.	Are the following dry cleaning system components inspected <u>monthly</u> for <u>vapor leaks</u> using a halog	enated	hydrocarbo	on detector	
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	graph sh	hall satisfy th	ne	
	requirements to conduct an inspection for perceptible leaks under $\S63.322(k)$ or $(l)$ )				
	b) Door gaskets and seating  Yes  No N/A h) Stills Yes  No N/A i) Exhaust dampers	Yes Yes Yes Yes Yes	<ul><li> No</li><li> No</li><li> No</li><li> No</li><li> No</li><li> No</li><li> No</li></ul>	<ul><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li><li>N/A</li></ul>	

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as required?  ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other  Explain other:					
Sangeeta Sharma	03/23/2011				
Inspector's Name (Please Print)	Date of Inspection				
Inspector's Signature	Approximate Date of Next Inspection				

**COMMENTS:** Perc solvent was not in the secondry containment. It was corrected during the inspection. The bottle says it contained perc was leaking. The bottle was put in the containment structure immediately. At the time of the inspection, it was noted that they need to clean up the floor immediately any rags, paper towels or mop water can be used to clean and spill needs to be disposed off properly.

Also, It was noted that the floor surrounding the perc machine and hazardous waste area need to be resealed. The cleaned and resealed pictures of the floor were received by the department on April 4<sup>th</sup>, 2011. The permit is going to expire on August 5<sup>th</sup>, 2011. So they need to submit a permit renewal form at least 30 days prior to that form.