

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

<u>INSPECTION</u> <u>TYPE</u> : AN	NUAL (INS1, INS2)	COMPLAINT/E	DISCOVERY	(CI)			
RE-	INSPECTION (FUI)	ARMS COMPL	AINT NO:				
AIRS ID#: 0950302 DATE:	<u>8/14/08</u>	ARRIVE: <u>10:00</u> :	<u>a.m.</u>	DEPART: <u>10:30 a.m.</u>			
FACILITY NAME: VALET CLEANERS							
FACILITY LOCATION: 1455 South Orlando Ave							
	MAITLAND 32751						
OWNER/AUTHORIZED RE	EPRESENTATIVE: N	MIKE PAROO	PHONE:	(407)539-1155			
CONTACT NAME: Mike F	Paroo		PHONE: (407)539-1155				
ENTITLEMENT PERIOD: 8/31/2006 / 8/31/2011 (effective date) (end date)							
DARK NICHECTION CO.		(1.1 5 /1.1.1	`				
PART I: INSPECTION COM		-		N. GOLDINANGE			
☑ IN COMPLIANCE	MINOR Non-CC	OMPLIANCE SIC	BNIFICANT	Non-COMPLIANCE			
PART II: FACILITY CLAS (check only one		2-213.300 FAC					
A. 1. Existing small are dry-to-dry only, x < 2 both types, x < 140 (constructed before	dry-to-dry on transfer only, both types, x	2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91)					
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$)			800 gal/yr 0 gal/yr				
5. Ineligible for Gen drop store/out of b facility exceeds ab	usiness/petroleum						
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 118 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box					
Do	es the responsible official of the dry cleaning facility:	for each question)					
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes	□No	□N/A			
2.	Examine the containers for leakage?	⊠Yes	☐ No	□ N/A			
3.	Close and secure machine doors except during loading/unloading?	Yes Yes	☐ No				
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	□Yes	□ No	⊠ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes	□ No	⊠ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)						
	1. If the facility classification is a Existing small area source, no controls are requi	ired. Pro	ceed to I	Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.						
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993						
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated			
A.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :		(check ☑ only one box for each question)				
1.	Equipped all machines with the appropriate vent controls?	⊠Yes	□No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	□No	□N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	□No	□N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	□No				
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- Yes	□No	⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes	□No				

B. Does the responsible official of an existing large or new large area source also: (check ☑ only one box for each question)				
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? Yes No				
2. Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?				
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? Yes No N/A				
a) Is the perc concentration equal to, or less than 100 ppm?				
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?				
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?				
6. Route airflow to the carbon adsorber (if used) at all times? Yes No N/A				
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Does the responsible official: (check ☑ only one box for each question)				
1. Maintain receipts for perc purchased? Yes No				
2. Maintain rolling monthly total of yearly perc consumption? Yes No				
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or; Yes No N/A				
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Yes No N/A				
4. Maintain calibration data? (for applicable direct reading instruments) Yes No N/A				
5. Maintain exhaust duct monitoring data on perc concentrations? Yes No N/A				
6. Maintain a startup/shutdown/malfunction plan? Yes No				
7. Maintain deviation reports?				
a) Problem corrected?				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?				
c) Filter gaskets and seating d) Pumps Yes No N/A i) Exhau Yes No N/A j) Divert	Yes No N/A Yes No N/A ast dampers Yes No N/A In N/A			
4. Which method(s) of detection (is/are) used by the responsible official?	?			
a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes e) Halogen leak detector **If using direct-reading instrumentation, is the equipment: 1) Capable of detecting perc vapor concentrations in a range of 0-500 2) Calibrated against a standard gas prior to and after each use (PID/R 3) Inspected for leaks and obvious signs of wear on a weekly basis? - 4) Kept in a clean and secure area when not in use? 5) Verified for accuracy by use of duplicate samples (calorimetric on	b)			
Efren Vazquez	8/14/08			
Inspector's Name (Please Print)	Date of Inspection			
8	3/14/09			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS: Facility was in compliance during the annual inspection performed on this date.				