

## PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE:</b> ANNUAL (INS1, INS2)	COMPLAINT/DISCOVERY (CI)			
RE-INSPECTION (FUI)	ARMS COMPLAINT NO:			
AIRS ID#: 1030316 DATE: <u>2/11/2008</u>	ARRIVE: <u>2:35PM</u> DEPART: <u>3:05PM</u>			
FACILITY NAME: BRISTOL CLEANERS & LAUND	RY			
<b>FACILITY LOCATION:</b> 120 107TH AVE				
TREASURE ISLAND	33706-4716			
OWNER/AUTHORIZED REPRESENTATIVE: BAS	SAM MUSA <b>PHONE:</b> (727)360-2194			
CONTACT NAME: Same	PHONE:			
ENTITLEMENT PERIOD: 10/11/2007 / 10/11/2012 (effective date) (end date)				
PART I: INSPECTION COMPLIANCE STATUS (ch	and Manus and hou			
IN COMPLIANCE MINOR Non-COMP	_			
MINOR NOI-COM	LIANCE SIGNIFICANT NOII-COMFLIANCE			
DADT II. FACILITY OF ACCIDICATION Dule (2.2)	12 200 EAC			
PART II: <u>FACILITY CLASSIFICATION</u> - Rule 62-22 (check ✓ only one box in A)	13.300 FAC			
A. 1. Existing small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed before 12/9/91)	2. New small area source dry-to-dry only, x < 140 gal/yr transfer only, x < 200 gal/yr both types, x < 140 gal/yr (constructed on or after 12/9/91)			
3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$ )	4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$ )			
5. Ineligible for General Permit				
drop store/out of business/petroleum facility exceeds above limits				

PA	PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC (check ☑ only one box				
Does the responsible official of the dry cleaning facility:		for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
5.	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	☐Yes ☐ No ☒ N/A			
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a <b>Existing small area source</b> , no controls are requi	ired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. <b>Complete section A. below.</b>				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> Carbon adsorber must have been installed prior to September 22, 1993				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped with a refrigerated			
<b>A.</b>	Has the responsible official of all <u>existing large</u> <u>area &amp; new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	Yes No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	- □Yes □No ⊠N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- ∐Yes ∐No ⊠N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- ∐Yes □No ⊠N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No			

PA	PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)				
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)			
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No			
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?a) Is the temperature differential equal to, or greater than 20° F?	Yes No No N/A			
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ☑ N/A			
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☐ N/A			
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ⊠ N/A			
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A			
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A			
PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ✓ only one box for					
Do	es the responsible official:	each question)			
1.	Maintain receipts for perc purchased?				
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No			
3.	Maintain leak detection inspection and repair reports for the following:				
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No No			
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No     N/A			
4.	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No     N/A			
5.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A			
	Maintain a startup/shutdown/malfunction plan?	⊠ Yes □ No			
7.	Maintain deviation reports?				
	a) Problem corrected?	Yes No N/A			
8.	Maintain a compliance plan, if applicable?	Yes No No N/A			

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check  $\square$  only one box for each question)

det	letection and repair inspection?	X Yes			
2. Do	Ooes the facility maintain a leak log?	🛚 Yes 🗌 No			
<ul><li>a)</li><li>b)</li><li>c)</li><li>d)</li><li>e)</li></ul>	Does the responsible official check the following areas for leaks?  a) Hose connections, fittings, couplings, and valves				
4. Wh	4. Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces) ————————————————————————————————————					
Shea Jackson 2/11/2008					
	Inspector's Name (Please Print)  Date	of Inspection			
	2009				
	Inspector's Signature App	roximate Date of Next Inspection			

## **COMMENTS:**

- I met with Mr. Musa the responsible official and observed the dry to dry was not in operation at this time.
- I observed his calendar was a 2008 which he had added the checks into him self. I explained the calendars were no longer mailed out by SBEAP. I gave him the information for the internet link, so he could print out their calendar for record use. The most recent purchase was 12/26/2007 30 gal perc
- I inquired if he had purchased a halogen detector for his leak checks. He stated he had not obtain yet. I informed him that it must be obtained by 7/28/2008. I caution him could be a violation which would result in penalties if not purchased for use before date. I noted this requirement on the inspection summary sheet.
- The front panel temperature read out is what has now been approved for the observation and monitoring of the temperature for the cool down cycle. This shows the correct temperature for the solvent (Perc), according to the Multi Matic manufacturer.
- The temperature has been registering as 20°F during the cool down cycles.
- The maintenance man; Timothy Barnes, a local self employed, mechanic has set the dry to dry equipment for the correct temperature operations.
- I did not detect any perchloroethylene odors as observing the equipment during the inspection
- The Hazardous waste containers were located in the secondary containment area.
- The boiler and evaporator are located in a outside storage shed.
- I gave Mr. Musa the P2R2 booklet, separator guidance memo.
- He signed the annual certification.