

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

| INSPECTION TYPE : | ANNUAL (INS1, INS2) | COMPLAINT/DISCOVE | CRY (CI) | | | |
|--|---|---|-----------------------------|--|--|--|
| | RE-INSPECTION (FUI) | ARMS COMPLAINT NO |): | | | |
| | | | | | | |
| AIRS ID#: 0950306 DA ' | TE: <u>2/12/08</u> | ARRIVE: <u>10:45</u> | DEPART: <u>11:30</u> | | | |
| FACILITY NAME: TINKERBELL CLEANERS | | | | | | |
| FACILITY LOCATION | 533 S Semoran Blvd | | | | | |
| | WINTER PARK 32792 | 2 | | | | |
| OWNER/AUTHORIZED REPRESENTATIVE: ELIA SAM PHONE: (407)679-5888 | | | | | | |
| CONTACT NAME: | | PHON | Ε: | | | |
| ENTITLEMENT PERIOD: 3/2/2007 / 3/2/2012 (effective date) (end date) | | | | | | |
| DADTI. INCRECTION | COMPLIANCE CTATUS (-1 | | | | | |
| IN COMPLIANCE | COMPLIANCE STATUS (ch | | NT Non-COMPLIANCE | | | |
| M COMPLIANC | CE MINOR Non-COMP | EIANCE SIGNIFICA | NT NOIF-COMFLIANCE | | | |
| | T A GOVERNO A TOTAL OF A SA | 12 200 71 9 | | | | |
| | <u>LASSIFICATION</u> - Rule 62-21 y one box in A) | 13.300 FAC | | | | |
| transfer only, both types, x | ly, x < 140 gal/yr x < 200 gal/yr | 2. New small area source dry-to-dry only, x < 14 transfer only, x < 200 both types, x < 140 ga (constructed on or after | 40 gal/yr gal/yr l/yr | | | |
| 3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before $12/9/91$) 4. New large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after $12/9/91$) | | | | | | |
| | | | | | | |
| (constructed by 5. Ineligible for drop store/out | | | | | | |

| PA | RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC | (check | only or | ne box | | | | |
|----|--|------------------|----------------|--------------------|--|--|--|--|
| Do | es the responsible official of the dry cleaning facility: | for ea | ich questi | ion) | | | | |
| 1. | Store perc, and wastes containing perc, in tightly sealed & impervious containers? | ⊠Yes | □No | □N/A | | | | |
| 2. | Examine the containers for leakage? | ⊠Yes | ☐ No | □ N/A | | | | |
| 3. | Close and secure machine doors except during loading/unloading? | X Yes | ☐ No | | | | | |
| | Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal? | ⊠Yes | □ No | □ N/A | | | | |
| | Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications? | ∐Yes | □ No | ⊠ N/A | | | | |
| | PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) | | | | | | | |
| | 1. If the facility classification is a Existing small area source , no controls are required. | red. Pr o | ceed to l | Part V. | | | | |
| | 2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below. | | | | | | | |
| | If the facility classification is a Existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 If the facility classification is a New large area source, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below. | | | | | | | |
| A. | Has the responsible official of all <u>existing large</u> <u>area & new sources</u> : | | only each ques | one box for stion) | | | | |
| 1. | Equipped all machines with the appropriate vent controls? | ⊠Yes | □No | | | | | |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system? | ⊠Yes | □No | □N/A | | | | |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? | ⊠Yes | □No | □N/A | | | | |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis? | ⊠Yes | □No | | | | | |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F? | □Yes | □No | ⊠N/A | | | | |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | ⊠Yes | □No | | | | | |

| PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued) | | | | | | |
|---|-----------------------------|--|--|--|--|--|
| | ly one box for uestion) | | | | | |
| Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis? Yes [Yes] | □No | | | | | |
| Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? Yes [| □ No □N/A | | | | | |
| a) Is the temperature differential equal to, or greater than 20° F? Yes [| □ No □ N/A | | | | | |
| 3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber? | □ No □ N/A | | | | | |
| a) Is the perc concentration equal to, or less than 100 ppm? | □ No □ N/A | | | | | |
| 4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet? | □ No □ N/A | | | | | |
| 5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils? | □ No □ N/A | | | | | |
| 6. Route airflow to the carbon adsorber (if used) at all times? Yes [| □ No □ N/A | | | | | |
| | | | | | | |
| DADEN DECORDATEDING DECLUDENCE D. L. (2.212.200/2) E. C. | | | | | | |
| | lly one box for uestion) | | | | | |
| 1. Maintain receipts for perc purchased? Yes [| □ No | | | | | |
| 2. Maintain rolling monthly total of yearly perc consumption? Yes | □No | | | | | |
| 3. Maintain leak detection inspection and repair reports for the following: | | | | | | |
| a) documentation of leaks repaired w/in 24 hrs? or; Yes [| □ No □ N/A | | | | | |
| b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Yes [| □ No ⊠ N/A | | | | | |
| 4. Maintain calibration data? (for applicable direct reading instruments) Yes | □ No □ N/A | | | | | |
| 5. Maintain exhaust duct monitoring data on perc concentrations? Yes | □ No □ N/A | | | | | |
| 6. Maintain a startup/shutdown/malfunction plan? Yes [| □ No | | | | | |
| 7. Maintain deviation reports? Yes [| □ No □ N/A | | | | | |
| a) Problem corrected? Yes [| □ No □ N/A | | | | | |
| 8. Maintain a compliance plan, if applicable? Yes [| □ No ⊠ N/A | | | | | |

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

| detection and repair inspection? | | | | | |
|---|-------------------------------------|--|--|--|--|
| 2. Does the facility maintain a leak log? | | | | | |
| 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves | | | | | |
| 4. Which method(s) of detection (is/are) used by the responsible official? | | | | | |
| a) Visual examination (condensed solvent on exterior surfaces) | | | | | |
| Assefa Hailemariam | 2/12/08 | | | | |
| Inspector's Name (Please Print) | Date of Inspection | | | | |
| | ~2/12/09 | | | | |
| Inspector's Signature | Approximate Date of Next Inspection | | | | |
| COMMENTS: | | | | | |