

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

<b>INSPECTION TYPE:</b> ANNUAL (IN	IS1, INS2) 🛛 COMPLAINT/DISCOVER	XY (CI)
RE-INSPECT	TION (FUI) ARMS COMPLAINT NO:	
AIRS ID#: 0112271 DATE: 09/22/200	6 ARRIVE: <u>9:30 AM</u>	DEPART: <u>10:00 PM</u>
		DEFART. <u>10.00 FM</u>
FACILITY NAME: JOLT TECHNOL	OGY INC	
FACILITY LOCATION: 6801 N	IW 15th AVE	
FT LA	UDERDALE 33309	
<b>RESPONSIBLE OFFICIAL:</b> MITCH	MORHAIM PHONE:	: (954)968-8526
CONTACT NAME:	PHONE:	:
<b>REMITTANCE YEAR:</b> 2005	ENTITLEMENT PERIOD: 7/29/2006 (effective date)	/ 7/29/2011 (end date)
PART I: INSPECTION COMPLIANCE	CE STATUS (check 🗹 only one box)	
IN COMPLIANCE IMI	NOR Non-COMPLIANCE	T Non-COMPLIANCE
PART II: <u>NOTIFICATION</u> – Rule 62 (check ☑ appropriate box(es))	-210.300 FAC	
1. Halogenated solvent used at		
perchloroethylene methylene chloride	- following machine type(s)	
trichloroethylene	- $\square$ Batch Vapor, x > 1	1.21 m <sup>2</sup>
1,1,1-trichloroethane carbon tetrachloride		
chloroform	- Batch Cold	
PART III: <u>CLASSIFICATION</u> – Rule		
Indicate the machine type(s) observ	red at the facility:	
Batch Vapor, $x \le 1.21 \text{ m}^2$ $\bigotimes$	New In-line I	Batch Cold (immersion)
Batch Vapor, $x > 1.21 \text{ m}^2$		

PART IV: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			
A. <u>Batch Vapor and In-Line Machines</u>			
1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	No	
2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	No	
3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	No	
5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	Yes	No	
6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	r ⊠Yes	No	□N/A
<ul><li>7. Does the facility have each machine equipped with:</li><li>a. a device to shut off sump heat if the solvent level drops to the heater coils?</li></ul>		No	
<ul><li>b. a device to shut off sump heat if the vapor level rises above the height of the vapor condenser?</li><li>c. a primary condenser?</li></ul>		□N □N	
8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	Yes	No	
<ul> <li>B. <u>Batch Cold Cleaning Machines</u></li> <li>1. Does the facility collect and store all waste solvent in closed containers?</li> <li>2. Does the facility use a flexible hose or flushing device only within the</li> </ul>	Yes	No	
<ul> <li>freeboard area?</li></ul>		□No	
		∐No	
the fill line? 5. Does the facility immediately clean up spills during solvent transfer?	_	□No	
Store wipe rags in a covered container?	∐Yes	□No	
<i>only when air or pump agitated solvent bath used</i> )7. Does the facility ensure that the machine is not exposed to drafts greater than	☐Yes		∐N/A
<ul> <li>40 m/min (132 ft/min) when the cover is open?</li></ul>	□Yes	□No □No	
<ul> <li><u>Remote Reservoir Type Only</u></li> <li>9. Does the facility employ a tightly fitting cover over the solvent sump?</li> </ul>			
The cover must be closed at all times except during parts cleaning	Yes	No	□N/A
10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio			
of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal	Yes	No	□N/A

Facility chose control o alternati idling er	e <u>to meet</u> <u>requirements</u> using levice combination / work pra ve solvent emission limit ( <i>pro</i>	g: actice standards oceed to Part VI)	t applicable to batch cold cleaning machines)
(Select control combination)		<u>DEVICE IN USE</u>	
1. □g 2. □g 3. □g 4. □g 5. ⊠g 6. □g 7. □g 8. □g	working mode cover reduced room draft reduced room draft freeboard refrig. device freeboard refrig. device freeboard refrig. device freeboard refrig. device freeboard refrig. device	1.0 freeboard ratio -         1.0 freeboard ratio -         1.0 freeboard ratio -         superheated vapor         working mode cover         reduced room draft         1.0 freeboard ratio -         dwell	superheated vapor
9. □g 10. □g	freeboard refrig. device	carbon adsorber  1.0 freeboard ratio -	superheated vapor
B. <u>Batch Vapor</u>	<u>Machines</u> , $x > 1.21 \text{ m}^2$		
( <u>Select</u> contro combination)		<u>DEVICE IN USE</u>	
1. g 2. g 3. g 4. g 5. g 6. g 7. g	freeboard refrig. device freeboard refrig. dev	superheated vapor superheated vapor superheated vapor superheated vapor reduced room draft - reduced room draft - reduced room draft -	1.0 freeboard ratio         working mode cover         reduced room draft         carbon adsorber         dwell         1.0 freeboard ratio         superheated vapor
C. <u>Existing</u> In-L	<u>Line Machines</u>		
(Select control combination)		<u>DEVICE IN USE</u>	
1. g 2. g 3. g 4. g	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -      1.0 freeboard ratio -      dwell      dwell	
D. <u>New In-Line</u>	<u>Machines</u>		
(Select control combination)		<u>DEVICE IN USE</u>	
	freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor -	

## PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC

## Has the responsible official maintained the following:

1. Owner's manuals, design specifications, and other instructional materials for cleaning			
machine and control equipment?	⊠Yes	No	
2. Date of installation for cleaning machine and all control devices? If the exact date is	_	_	
unknown, they must have a letter stating installation occurred before or after 11/29/93	⊠Yes	□No	
3. Halogenated solvent content for each solvent used? ( <i>exempt if &lt;5% by weight</i> )	⊠Yes	No	
4. Estimates of annual solvent consumption for each machine?	⊠Yes	No	
5. Dates of solvent additions and amounts added to each machine? (applicable only to			
those using an alternative emission limit)	Yes	No	⊠N/A
6. Idling emissions limit tests, including values obtained during the initial performance			
test? (applicable only to those using an idling emissions limit)	Yes	No	⊠N/A
7. All control device and parameter monitoring? (applicable only to batch vapor and			
in-line machines)	⊠Yes	No	N/A
8. Information on remedial actions in the event of exceedances or other repairs and			
subsequent monitoring of affected parameters?	Yes	No	⊠N/A
9. Monthly emissions calculations (applicable only to those using an alternative or idling			
emission limit)	Yes	No	⊠N/A
10. 3-month rolling average emissions calculations? (applicable only to those using an			
alternative emission limit)	Yes	No	N/A
11. Cleaning capacity calculations? (applicable only to those using an alternative emission	_		
limit without a solvent-air interface)	Yes	No	N/A

Elizabeth F. Susky

Inspector's Name (Please Print)

09/22/2006

Date of Inspection

09/22/2007

Inspector's Signature

Approximate Date of Next Inspection

**COMMENTS:** In a compliance inspection conducted on 09/22/2006, AQD observed activities at Jolt Technology. This facility has a batch vapor mchine with working mode cover. Mr. Jamison accompanied staff on the inspection. Mr. Jamision stated that they had now been classified as an conditionally exempt generator.

The facility has excellent housekeeping and staff was helpful.