

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOV ARMS COMPLAINT N				
AIRS ID#: 0112271 DA	TE: <u>10/29/2008</u>	ARRIVE: 1:00PM	DEPART: <u>2:00PM</u>			
FACILITY NAME: JOI	LT TECHNOLOGY INC					
FACILITY LOCATION	N: 6801 NW 15th AVE					
	FT LAUDERDALE	33309-1506				
OWNER/AUTHORIZED REPRESENTATIVE: MITCH MORHAIM PHONE: (954)968-8526						
CONTACT NAME:		PHON	IE:			
ENTITLEMENT PERIO	OD: 7/29/2006 / 7/29/2 (effective date) (end date					
☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE						
PART II: NOTIFICATION – Rule 62-210.300 FAC (check ☑ appropriate box(es))						
1. Halogenated solvent used at facility: perchloroethylene trichloroethylene 1,1,1-trichloroethane carbon tetrachloride chloroform 1. Halogenated solvent used at facility: perchloroethylene						
	ATTON D 1 (2 212 200 1	n. a				
PART III: <u>CLASSIFICATION</u> – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:						
Batch Vapor, x ≤	$\leq 1.21 \text{ m}^2 - \square$	New In-line	Batch Cold (immersion)			
Batch Vapor, x >	· 1.21 m ²	Existing In-line	Batch Cold (remote reservoir)			

	T IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC . Batch Vapor and In-Line Machines			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed	⊠Yes		
	with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?		□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	⊠Yes	□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	□N/A
	7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils? b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser?c. a primary condenser?	⊠Yes □Yse	□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	□Yes	□No	
В. <u>В</u>	 atch Cold Cleaning Machines Does the facility collect and store all waste solvent in closed containers? Does the facility use a flexible hose or flushing device only within the 	□Yes	□No	
	freeboard area?		□No	
			□No	
	4. Does the facility maintain the solvent level inside the machine at or below the fill line?	□Yes	□No	
	5. Does the facility immediately clean up spills during solvent transfer? Store wipe rags in a covered container?	□Yes	□No	
	6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used).	□Yes	□No	□N/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	□Yes	□No	
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
	9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning	□Yes	□No	□N/A
_	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal	□Yes	□No	□N/A

PA	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines) Facility chose to meet requirements using: control device combination / work practice standards						
A.	Batch Vapor	Machines, $x \le 1.21 \text{ m}^2$					
	(Select control combination)		<u>DEVICE IN USE</u>				
	1.	working mode cover reduced room draft reduced room draft freeboard refrig. device freeboard refrig. device	1.0 freeboard ratio -	superheated vapor superheated vapor dwell			
	9.	carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor			
В.	Batch Vapor	Machines, $x > 1.21 \text{ m}^2$					
	(Select contro						
	combination)	<u>DEVICE IN USE</u>				
	 □g 	freeboard refrig. device freeboard ratio	superheated vapor superheated vapor superheated vapor superheated vapor reduced room draft - reduced room draft - reduced room draft -	1.0 freeboard ratio working mode cover reduced room draft carbon adsorber dwell 1.0 freeboard ratio superheated vapor			
C.	Existing In-I	Line Machines					
	(Select control combination)		<u>DEVICE IN USE</u>				
	1.	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -				
D.	New In-Line	Machines					
	(Select control combination)		<u>DEVICE IN USE</u>				
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber				

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC							
Has the responsible official maintained the following:							
1. Owner's manuals, design specifications, and other instructional materials for cleaning machine and control equipment? 2. Date of installation for cleaning machine and all control devices? If the exact date is unknown, they must have a letter stating installation occurred before or after 11/29/93 3. Halogenated solvent content for each solvent used? (exempt if <5% by weight) 4. Estimates of annual solvent consumption for each machine? 5. Dates of solvent additions and amounts added to each machine? (applicable only to those using an alternative emission limit)		<pre></pre>	No	 N/A N/A N/A N/A N/A N/A N/A N/A 			
Elizabeth F. Susky	10/29/2008						
<u>.</u>							
Inspector's Name (Please Print)	Date of Inspection						
	10//29/2009						
Inspector's Signature Approximate Date of Next I		Inspection	n				

COMMENTS: In a compliance inspection conducted on 10/29/2008, AQD staff observed operations at Jolt Technology. The facility utilizes a halogenated solvent degreaser. Mr. Rodney Jamison (Senior Process Engineer) accompanied staff on the inspection. The facility housekeeping is excellent and Mr. Jamison stated that the facility has been designated as conditionally exempt.

The degreaser was working properly during the inspection and Mr. Jamison keeps records of all maintenance. He did state that on 03/21/2008 a repair was conducted on the chiller (freon).