

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D  ARMS COMPLA	ISCOVERY (CI)	
<b>AIRS ID#:</b> 0112271 <b>DA</b> 7	ГЕ: <u>07/28/2010</u>	ARRIVE: <u>1430</u>	DEPART: <u>1530</u>	
FACILITY NAME: JOI	LT TECHNOLOGY INC			
FACILITY LOCATION	6801 NW 15th AVI	Ξ		
	FT LAUDERDALE	E 33309-1506		
OWNER/AUTHORIZED Email: CONTACT NAME: Email: ENTITLEMENT PERIC	<b>D REPRESENTATIVE: DD:</b> 7/29/2006 / 7/29/2006 (effective date) (end date)	2011	PHONE: (954)968-8526 Mobile: PHONE: Mobile:	
PART NGPECTON	COMPLIANCE OF A FUI	S / 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	·	
PART I: INSPECTION COMPLIANCE STATUS (check ✓ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE				
PART II: NOTIFICATION – Rule 62-210.300 FAC (check ☑ appropriate box(es))				
1. Halogenated solvent used at facility:  perchloroethylene  methylene chloride  trichloroethylene  1,1,1-trichloroethane  carbon tetrachloride  chloroform  2. Indication on notification form that facility has the following machine type(s).  Batch Vapor, x ≤ 1.21 m²				
PART III: <u>CLASSIFICATION</u> – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:				
Batch Vapor, x ≤	• • • • • • • • • • • • • • • • • • • •	New In-line	Batch Cold (immersion)	🗌
Batch Vapor, x >	1.21 m <sup>2</sup>	Existing In-line	Batch Cold (remote reserv	voir)

	T IV: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC <u>Batch Vapor and In-Line Machines</u>			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	⊠Yes	□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	□N/A
	7. Does the facility have each machine equipped with:  a. a device to shut off sump heat if the solvent level drops to the heater coils?  b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser?  c. a primary condenser?		□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
В. <u>В</u>	1. Does the facility collect and store all waste solvent in closed containers?  2. Does the facility use a flexible hose or flushing device only within the	Yes	□No	
	freeboard area?  3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?  4. Does the facility maintain the solvent level inside the machine at or below		□No	
			□No	
	the fill line?	Yes	□No	
	5. Does the facility immediately clean up spills during solvent transfer?  Store wipe rags in a covered container?	□Yes	□No	
	6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	□Yes	□No	□N/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	Yes	□No	
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
	9. Does the facility employ a tightly fitting cover over the solvent sump?  The cover must be closed at all times except during parts cleaning	∐Yes	□No	□N/A
=	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	□Yes	□No	□N/A

Facility chose to meet requirements using:   control device combination / work practice standards   alternative solvent emission limit (proceed to Part VI)	PA	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)					
alternative solvent emission limit (proceed to Part VI)							
A. Batch Vapor Machines, x \leq 1.21 m²							
A.   Batch Vapor Machines, x \leq 1.21 m <sup>2</sup>		idling er	nission limit / work practice s	standards (proceed to Part V.	I)	H	
Select control combination   DEVICE IN USE		Toming of	moston mine, worm practice of	various (proceeds to 1 arr vi			
Select control combination   DEVICE IN USE							
DEVICE IN USE	A.	Batch Vapor	Machines, $x \le 1.21 \text{ m}^2$				
1.			<u>[</u>				
2.		combination)		<u>DEVICE IN USE</u>			
2.		1 Πσ	working mode cover	1.0 freeboard ratio -	superheated vapor		
3.		<b>—</b> -					
5.		==		=			
reduced room draft   1.0 freeboard refrig. device   1.0 freeboard ratio   1.0 freeboar							
7.		_					
8. g freeboard refrig. device   carbon adsorber   superheated vapor		_ =="	<u> </u>				
9.		- <b>=</b> ~		==			
B. Batch Vapor Machines, x > 1.21 m²  (Select control combination)  DEVICE IN USE  1.		==		<u>—</u>			
Select control combination   DEVICE IN USE		=-			superheated vapor		
Select control combination   DEVICE IN USE		_	2				
DEVICE IN USE	В.	Batch Vapor	Machines, $x > 1.21 \text{ m}^2$				
DEVICE IN USE		(Select contro	<u>ol</u>				
2.				<u>DEVICE IN USE</u>			
2.		1 🗖	C 1 1 C		1.0 ()		
3. g freeboard refrig. device superheated vapor carbon adsorber dwell carbon adsorber carbon ad		==					
4. g freeboard refrig. device superheated vapor dwell dw		- <b>=</b> ~	<u> </u>				
6.		. =~					
7.		5. <u>□</u> g		reduced room draft -	<b>—</b>		
C. Existing In-Line Machines    Select control combination   DEVICE IN USE		_ = °		<b>=</b>	<b></b>		
(Select control combination)  DEVICE IN USE  1.		7. <b>∟</b> g	1.0 freeboard ratio	reduced room draft -	superheated vapor		
DEVICE IN USE	C.	Existing In-I	Line Machines				
DEVICE IN USE		(Select control					
2.			•	<u>DEVICE IN USE</u>			
2.		1 Πσ	freeboard refrig device	1.0 freeboard ratio -			
3.		===					
D. New In-Line Machines  (Select control combination)  DEVICE IN USE  freeboard refrig. device superheated vapor - freeboard refrig. device carbon adsorber							
(Select control combination)  DEVICE IN USE  freeboard refrig. device superheated vapor - freeboard refrig. device carbon adsorber		4.	carbon adsorber	dwell			
combination)  DEVICE IN USE  freeboard refrig. device superheated vapor - freeboard refrig. device carbon adsorber	D.	New In-Line	<u>Machines</u>				
combination)  DEVICE IN USE   freeboard refrig. device □ superheated vapor - □ carbon adsorber □		(Select control					
freeboard refrig. device carbon adsorber			-	<u>DEVICE IN USE</u>			
freeboard refrig. device carbon adsorber			freeboard refrig. device	superheated vapor -			
superheated vanor Carbon adsorber			freeboard refrig. device	carbon adsorber			
superincated vapor carbon ausorber			superheated vapor	carbon adsorber			
superheated vanor   carbon adsorber			freeboard refrig. device	carbon adsorber			

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC						
T						
Has the responsible official maintained the following:						
1. Owner's manuals, design specifications, and other instrumachine and control equipment?		⊠Yes	□No			
<ul> <li>2. Date of installation for cleaning machine and all control devices? If the exact date is unknown, they must have a letter stating installation occurred before or after 11/29/93</li> <li>3. Halogenated solvent content for each solvent used? (exempt if &lt;5% by weight)</li> <li>4. Estimates of annual solvent consumption for each machine?</li></ul>			□No □No □No			
<ul><li>5. Dates of solvent additions and amounts added to each machine? (applicable only to those using an alternative emission limit)</li><li>6. Idling emissions limit tests, including values obtained during the initial performance</li></ul>			□No	⊠N/A		
test? (applicable only to those using an idling emissions limit)			□No	⊠N/A		
7. All control device and parameter monitoring? (applicable only to batch vapor and in-line machines)			□No	□N/A		
8. Information on remedial actions in the event of exceedances or other repairs and subsequent monitoring of affected parameters?			□No	⊠N/A		
9. Monthly emissions calculations (applicable only to those using an alternative or idling emission limit)			□No	⊠N/A		
<ul> <li>10. 3-month rolling average emissions calculations? (applicable only to those using an alternative emission limit)</li> <li>11. Cleaning capacity calculations? (applicable only to those using an alternative emission limit without a solvent-air interface)</li></ul>		□Yes	□No	⊠N/A		
		∐Yes	□No	⊠N/A		
Elizabeth F.Susky	07/28/2010					
Inspector's Name (Please Print)	Date of Inspection					
	07/28/2011					
Inspector's Signature Approximate Date o		Inspection	1			

**COMMENTS:** In a compliance inspection conducted on 07/28/2010, AQD staff observed operations at Jolt Technology. The facility has a halogentated solvent degreaser. The houskeeping is excellent and the degreaser is well-maintained. Operations have not changed since the previous year.