

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D  ARMS COMPLA	DISCOVERY (CI)					
AIRS ID#: 0112271 DA	TE: <u>06/13/2011</u>	ARRIVE: <u>1300</u>	DEPART: <u>1400</u>					
FACILITY NAME: JOLT TECHNOLOGY								
FACILITY LOCATION	N: 6801 NW 15TH A	VE						
	FORT LAUDERD	ALE 33309-1506						
	D REPRESENTATIVE:	MITCH MORHAIM	PHONE: (954)968-8526					
Email: CONTACT NAME: R	ODNEY JAMISON		Mobile: PHONE: (954)968-8526					
Email: ENTITLEMENT PERIO	<b>OD:</b> 6/12/2011 / 6/12/ (effective date) / (end date)	2/2016 date)	Mobile:					
PADTI. INCDECTION	COMPLIANCE STATE	IG (-back of only one hos	`					
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (check ✓ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE								
PART II: NOTIFICAT  (check ☑ appropriat	<u>TON</u> – Rule 62-210.300 FA te box(es))	AC						
1. Halogenated solvent used at facility:  perchloroethylene								
PART III: <u>CLASSIFICATION</u> – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:								
Batch Vapor, x ≤	<del></del>	New In-line	Batch Cold (immersion)					
Batch Vapor, x >	> 1.21 m <sup>2</sup>	Existing In-line	Batch Cold (remote reservo	ir)				

ART IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC A. Batch Vapor and In-Line Machines			
Does the facility maintain an idling and downtime mode cover that is readily opened and			
closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	□No	
4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	□No	
5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	□Yes	□No	
6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	Yes	□No	⊠N/A
7. Does the facility have each machine equipped with:  a. a device to shut off sump heat if the solvent level drops to the heater coils?	□Yes	⊠No	
b. a device to shut off sump heat if the vapor level rises above the height of the vapor condenser?c. a primary condenser?	□Yes □Yse	□N □N	
8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	□Yes	⊠No	
Batch Cold Cleaning Machines     Does the facility collect and store all waste solvent in closed containers?     Does the facility use a flexible hose or flushing device only within the	□Yes	□No	
freeboard area?  3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping	□Yes	□No	
ceases, whichever is longer?  4. Does the facility maintain the solvent level inside the machine at or below	∐Yes	∐No	
the fill line?5. Does the facility immediately clean up spills during solvent transfer?		□No	
Store wipe rags in a covered container?  6. Does the facility operate the agitator to produce a rolling motion? (applicable	∐Yes	□No	_
only when air or pump agitated solvent bath used)7. Does the facility ensure that the machine is not exposed to drafts greater than	∐Yes	∐No	□N/A
40 m/min (132 ft/min) when the cover is open?  8. Does the facility ensure that sponges, fabrics, wood and paper products are not	∐Yes	□No	
placed in the machine? <u>Remote Reservoir Type Only</u>	□Yes	□No	
9. Does the facility employ a tightly fitting cover over the solvent sump?  The cover must be closed at all times except during parts cleaning <u>Immersion Type Only</u>	□Yes	□No	□N/A
10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry			
and removal	Yes	□No	□N/A

PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)  Facility chose to meet requirements using:  control device combination / work practice standards						
A. <u>Batch</u> <u>Vapor</u>	Machines, $x \le 1.21 \text{ m}^2$					
(Select control combination)	<u>l</u>	<u>DEVICE IN USE</u>				
3.	working mode cover	1.0 freeboard ratio -	superheated vapor superheated vapor dwell			
9.	carbon adsorber	1.0 freeboard ratio -	superheated vapor			
B. <u>Batch</u> <u>Vapor</u>	Machines, $x > 1.21 \text{ m}^2$					
( <u>Select control</u> combination)		<u>DEVICE IN USE</u>				
	freeboard refrig. device freeboard ratio	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced room draft - Feduced room draft -	1.0 freeboard ratio   working mode cover   reduced room draft   carbon adsorber   dwell    1.0 freeboard ratio   superheated vapor			
C. Existing In-L	Line Machines					
(Select control combination)	<u>l</u>	<u>DEVICE IN USE</u>				
<ol> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> <li>□g</li> </ol>	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -				
D. New In-Line	Machines					
(Select control combination)	L	<u>DEVICE IN USE</u>				
	freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber				

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC			
Has the responsible official maintained the following:			
<ol> <li>Owner's manuals, design specifications, and other instructional materials machine and control equipment?</li> <li>Date of installation for cleaning machine and all control devices? If the e unknown, they must have a letter stating installation occurred before or after</li> <li>Halogenated solvent content for each solvent used? (exempt if &lt;5% by we</li> <li>Estimates of annual solvent consumption for each machine?</li> <li>Dates of solvent additions and amounts added to each machine? (applical those using an alternative emission limit)</li> </ol>	Yes   Xact date is   11/29/93   Yes   Y	□No □No □No □No □No	⊠N/A
6. Idling emissions limit tests, including values obtained during the initial petest? (applicable only to those using an idling emissions limit)	erformance Yes	□No	⊠N/A
7. All control device and parameter monitoring? (applicable only to batch ve in-line machines)	\(\sum Yes\)	□No	□N/A
8. Information on remedial actions in the event of exceedances or other repa subsequent monitoring of affected parameters?	Yes	□No	⊠N/A
9. Monthly emissions calculations (applicable only to those using an alternational limit)	Yes	□No	⊠N/A
10. 3-month rolling average emissions calculations? (applicable only to thosalternative emission limit)		□No	⊠N/A
11. Cleaning capacity calculations? (applicable only to those using an altern limit without a solvent-air interface)		□No	⊠N/A
Elizabeth F.Susky	06/13/2011		
Inspector's Name (Please Print)  Date of Ins	spection		
06/13/2012			
Inspector's Signature Approximate Date of Ne		n	

**COMMENTS:** In a compliance conducted on 06/13/2011, AQD staff observed operations at Jolt Technology. The facility has a halogenated solvent degreaser. The housekeeping is excellent and the degreaser is well maintained.