

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2)	COMPLAINT/DI	ISCOVERY (CI)
RE-INSPECTION (FUI)	ARMS COMPLA	JNT NO:
AIRS ID#: 0112271 DATE: 7/11/2012	ARRIVE: <u>1500</u>	DEPART: <u>1545</u>
FACILITY NAME: JOLT TECHNOLOGY		
FACILITY LOCATION: 6801 NW 15TH AV	/E	
FORT LAUDERDA	ALE 33309-1506	
OWNER/AUTHORIZED REPRESENTATIVE:		PHONE: (954)968-8526
Email: CONTACT NAME: RODNEY JAMISON Email:		Mobile: PHONE: (954)968-8526 Mobile:
EMAIL: ENTITLEMENT PERIOD: 6/12/2011 / 6/12/2 (effective date) (end da	2016	мооне:
((-		
PART I: INSPECTION COMPLIANCE STATUS	$\underline{\mathbf{S}}$ (check $\mathbf{\square}$ only one box)	
IN COMPLIANCE MINOR Non-C		
	OMPLIANCE SIG	NIFICANT Non-COMPLIANCE
		NIFICAN I Non-COMPLIANCE
PART II: <u>NOTIFICATION</u> – Rule 62-210.300 FA		NIFICANT Non-COMPLIANCE
PART II: NOTIFICATION – Rule 62-210.300 FA (check 🗹 appropriate box(es))	<u> </u>	
PART II: NOTIFICATION – Rule 62-210.300 FA (check ☑ appropriate box(es)) 1. Halogenated solvent used at facility:	C 2. Indication on notif	fication form that facility has the
PART II: NOTIFICATION – Rule 62-210.300 FA (check 🗹 appropriate box(es))	C 2. Indication on notif following machine Batch Va	fication form that facility has the e type(s). appr. $x < 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check ☑ appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene	C 2. Indication on notif following machine Batch Va Batch Va Batch Va	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check ☑ appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene 1,1,1-trichloroethane	AC 2. Indication on notif following machine Batch Va Batch Va New In-l	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check ☑ appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene	AC 2. Indication on notif following machin Batch Va Batch Va New In-I Existing	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check I appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene 1,1,1-trichloroethane carbon tetrachloride	AC 2. Indication on notif following machin Batch Va Batch Va New In-I Existing	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$ apor, $x > 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check I appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride 1,1,1-trichloroethane carbon tetrachloride chloroform	AC 2. Indication on notifi following machine Batch Va Batch Va New In-I Existing Batch Co	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$ apor, $x > 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check I appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene 1,1,1-trichloroethane carbon tetrachloride	AC 2. Indication on notifi following machim Batch Va Batch Va New In-1 Existing Batch Co FAC	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$ apor, $x > 1.21 \text{ m}^2$
PART II: NOTIFICATION – Rule 62-210.300 FA (check I appropriate box(es)) 1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene 1,1,1-trichloroethane carbon tetrachloride chloroform chloroform PART III: CLASSIFICATION – Rule 62-213.300 Indicate the machine type(s) observed at the fac	AC 2. Indication on notifi following machim Batch Va Batch Va New In-1 Existing Batch Co FAC	fication form that facility has the e type(s). apor, $x \le 1.21 \text{ m}^2$ apor, $x > 1.21 \text{ m}^2$

PART IV: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC			
A. <u>Batch Vapor and In-Line Machines</u>			
1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	No	
with reduced draft according to r are it, section (5)(c)o.o or the permit nonneuton.			
2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	No	
3. Does the facility utilize a parts basket or parts whose size is less than 50% of the			
solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	⊠Yes	No	
4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	No	
5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	Yes	□No	
6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorber should not be by-passed, the lip exhaust shall be located above the closed machine cover	r □Yes	No	N/A
7. Does the facility have each machine equipped with:a. a device to shut off sump heat if the solvent level drops to the heater coils?b. a device to shut off sump heat if the vapor level rises above the height of the	Yes	No	
 b. a device to shut off sump heat if the vapor level rises above the height of the vapor condenser? c. a primary condenser?		□N □N	
8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	Yes	No	
 B. <u>Batch Cold Cleaning Machines</u> 1. Does the facility collect and store all waste solvent in closed containers? 2. Does the facility use a flexible hose or flushing device only within the 	Yes	No	
freeboard area?	Yes	No	
3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?	Yes	No	
4. Does the facility maintain the solvent level inside the machine at or below the fill line?	Yes	No	
5. Does the facility immediately clean up spills during solvent transfer? Store wipe rags in a covered container?	Yes	No	
6. Does the facility operate the agitator to produce a rolling motion? (<i>applicable only when air or pump agitated solvent bath used</i>)	Yes	No	□N/A
7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	Yes	No	
8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	Yes	No	
 <u>Remote Reservoir Type Only</u> 9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning <u>Immersion Type Only</u> 	Yes	No	N/A
10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	□Yes	No	□N/A

PA	ART V: PRO	CESS VENT CONTROLS -	- Rule 62-213.300 FAC (no.	t applicable to batch cold cleaning machines)	
		<u>e to meet requirements usin</u>			
	idling ei	mission limit / work practice s	standards (proceed to Part V	(1)	
A.	Batch Vapor	<u>r Machines</u> , x <u><</u> 1.21 m ²			
	(Select control				
	combination)		<u>DEVICE IN USE</u>		
	1. 🗌 g	working mode cover	1.0 freeboard ratio -	superheated vapor	
	1. ∐g 2. ∏g	reduced room draft	1.0 freeboard ratio -	superheated vapor	
	2. □g 3. □g	reduced room draft	1.0 freeboard ratio -	dwell	
	4. □g	freeboard refrig. device	superheated vapor		
	5. 🔲 g	freeboard refrig. device	working mode cover		
	6. 🔲 g	freeboard refrig. device	reduced room draft		
	7. 🔲 g	freeboard refrig. device	1.0 freeboard ratio -		
	8. 🗌 g	freeboard refrig. device	dwell		
	9. 🗌 g	freeboard refrig. device	carbon adsorber		
	10. 🗌 g	carbon adsorber	1.0 freeboard ratio - \Box	superheated vapor	
-		2			
в.	<u>Batch Vapor</u>	$\frac{1}{2}$ <u>Machines</u> , x > 1.21 m ²			
	(Select contro	ol			
	combination		DEVICE IN USE		
	_	_	_		
	1. 🗌 g	freeboard refrig. device	superheated vapor	1.0 freeboard ratio	
	2g	freeboard refrig. device	superheated vapor	working mode cover	
	3g	freeboard refrig. device	superheated vapor	reduced room draft	
	4. ∐g 5. ∏g	freeboard refrig. device	superheated vapor	carbon adsorber	
		freeboard refrig. device	reduced room draft -	1.0 freeboard ratio	
	6. ∐g 7. ∏g	1.0 freeboard ratio	reduced room draft -	superheated vapor	
	/• 🗆5				
C.	Existing In-I	Line Machines			
	(Select control	1			
	combination)		DEVICE IN USE		
	1g	freeboard refrig. device	1.0 freeboard ratio -		
	2. <u> </u>	superheated vapor	1.0 freeboard ratio -		
	3. 🔤 g	freeboard refrig. device	dwell		
	4. ∐g	carbon adsorber	dwell		
D.	<u>New In-Line</u>	<u>Machines</u>			
	(Select control combination)		DEVICE IN USE		
	<u>combination</u>		<u>DEVICE IN USE</u>		
		freeboard refrig. device	superheated vapor -		
		freeboard refrig. device	carbon adsorber		
		superheated vapor	carbon adsorber		
_					

4

1. Owner's manuals, design specifications, and other instructional materials for cleaning machine and control equipment?	⊠Yes	No	
 Date of installation for cleaning machine and all control devices? If the exact date is unknown, they must have a letter stating installation occurred before or after 11/29/93. Halogenated solvent content for each solvent used? (<i>exempt if <5% by weight</i>) Estimates of annual solvent consumption for each machine? 	─Yes ⊠Yes ⊠Yes	No No No	
 5. Dates of solvent additions and amounts added to each machine? (<i>applicable only to those using an alternative emission limit</i>) 	Yes		N/A
6. Idling emissions limit tests, including values obtained during the initial performance test? (<i>applicable only to those using an idling emissions limit</i>)	Yes	No	N/A
7. All control device and parameter monitoring? (<i>applicable only to batch vapor and in-line machines</i>)	Yes	No	N/A
 8. Information on remedial actions in the event of exceedances or other repairs and subsequent monitoring of affected parameters? 9. Monthly emissions calculations (<i>applicable only to those using an alternative or idling</i>) 	Yes	No	N/A
 9. Monthly emissions calculations (<i>applicable only to mose using an alternative or lating emission limit</i>)	Yes	No	N/A
<i>alternative emission limit)</i>	Yes	No	N/A
limit without a solvent-air interface)	Yes	No	N/A

Elizabeth F.Susky

Inspector's Name (Please Print)

Date of Inspection

7/11/2013

Inspector's Signature

COMMENTS: In a compliance inspection conducted on 7/11/2012, AQD staff (E.Susky) observed operations at Jolt Technology. Mr. Rodney Jamison (manager) accompanied staff on the inspection. The facility has excellent houskeeping and keeps any hazardous waste in secondary containment. The have one halogenated solvent degreaser that is well maintained.

PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC

Has the responsible official maintained the following:

7/11/2012

Approximate Date of Next Inspection