

HALOGENATED SOLVENT DEGREASERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, IN RE-INSPECTION (F		· · · 			
AIRS ID#: 0112272 DATE: 6/29/06	ARRIVE: <u>10:20</u>	DEPART: <u>11:00</u>			
FACILITY NAME: AERO PRECISION REP	AIR & OVERHAUL				
FACILITY LOCATION: 580 S Military	Trail				
DEERFIELD 1	BEACH 33442				
RESPONSIBLE OFFICIAL: ALEX TEARLI	E PH	IONE: (305)428-9500			
CONTACT NAME: Robert Lee	PH	IONE: (
REMITTANCE YEAR: 2005 ENTITLEMENT PERIOD: 9/10/2001 / 9/10/2006 (end date)					
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE					
PART II: NOTIFICATION – Rule 62-210.30 (check ☑ appropriate box(es))	00 FAC				
1. Halogenated solvent used at facility: perchloroethylene methylene chloride trichloroethylene 1,1,1-trichloroethane carbon tetrachloride chloroform	following machine ty Batch Vapor Batch Vapor New In-line Existing In-	ation form that facility has the $ype(s)$. or, $x \le 1.21 \text{ m}^2$			
DADT III. CLASSIFICATION D. D. (2.212	2200 EAC				
PART III: CLASSIFICATION – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:					
Batch Vapor, $x \le 1.21 \text{ m}^2$	New In-line	Batch Cold (immersion)			
Batch Vapor, $x > 1.21 \text{ m}^2$	Existing In-line	Batch Cold (remote reservoir)			

	RT IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC A. Batch Vapor and In-Line Machines			
	1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed			
	with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?	⊠Yes	□No	
	2. Does the facility maintain a freeboard ratio of 0.75 or greater?	⊠Yes	□No	
	3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?	Yes	□No	
	4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?	⊠Yes	□No	
	5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?	Yes	□No	
	6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorbe should not be by-passed, the lip exhaust shall be located above the closed machine cover	r □Yes	□No	⊠N/A
	7. Does the facility have each machine equipped with: a. a device to shut off sump heat if the solvent level drops to the heater coils? b. a device to shut off sump heat if the vapor level rises above the height of the	⊠Yes	□No	
	vapor condenser? c. a primary condenser?	⊠Yes ⊠Yse	□N □N	
	8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?	⊠Yes	□No	
В. <u>І</u>	Batch Cold Cleaning Machines 1. Does the facility collect and store all waste solvent in closed containers? 2. Does the facility use a flexible hose or flushing device only within the	Yes	□No	
	freeboard area?	Yes	□No	
	3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?	□Yes	□No	
	4. Does the facility maintain the solvent level inside the machine at or below the fill line?	Yes	□No	
	5. Does the facility immediately clean up spills during solvent transfer?			
	Store wipe rags in a covered container? 6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)	□Yes	□No	□N/A
	7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?	□Yes	□No	∐N/A
	8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?	□Yes	□No	
	<u>Remote Reservoir Type Only</u>			
	9. Does the facility employ a tightly fitting cover over the solvent sump? The cover must be closed at all times except during parts cleaning <i>Immersion Type Only</i>	Yes	□No	□N/A
	10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal.	□Yes	□No	□N/A

	PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines) Facility chose to meet requirements using: control device combination / work practice standards					
	(Select control combination)		<u>DEVICE IN USE</u>			
	1. ☐g 2. ☐g 3. ☐g 4. ☐g 5. ☒g 6. ☐g 7. ☐g 8. ☐g	working mode cover	1.0 freeboard ratio -	superheated vapor superheated vapor dwell		
	9.	freeboard refrig. device carbon adsorber	carbon adsorber 1.0 freeboard ratio -	superheated vapor		
В.		<u>Machines</u> , x > 1.21 m ²	_	· · · —		
	(Select contro	<u>ol</u>				
	combination)	<u>DEVICE</u> IN <u>USE</u>			
	 □g 	freeboard refrig. device	superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Feduced room draft - Feduced r	1.0 freeboard ratio working mode cover reduced room draft dwell 1.0 freeboard ratio superheated vapor		
C.	Existing In-l	Line Machines				
	(Select contro combination)	-	<u>DEVICE IN USE</u>			
	1.	freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber	1.0 freeboard ratio -			
D.	New In-Line	Machines				
	(Select contro combination)		<u>DEVICE IN USE</u>			
		freeboard refrig. device freeboard refrig. device superheated vapor	superheated vapor - carbon adsorber carbon adsorber			

PART VI: RECORDKEEPING REQUIREMENTS - Rule 62-213.300(3) FAC						
<u>Has the responsible official maintained the following:</u>						
1. Owner's manuals, design specifications, and other machine and control equipment?	control devices? If the exact date is a occurred before or after 11/29/93	<pre></pre>	No	 N/A N/A N/A N/A N/A N/A N/A N/A 		
Art Pennetta	6/29/06					
Inspector's Name (Please Print)	Date of Inspection					
	6/07					
Inspector's Signature Approximate Date of Nex		Inspection	n			
COMMENTS: 550 gallons Trichlor purchased. 165 gal disp	posed as waste. 385 gal actual usage.					