

## HALOGENATED SOLVENT DEGREASERS



## COMPLIANCE INSPECTION CHECKLIST

| <u> </u>   | (INS1, INS2)<br>ECTION (FUI) | COMPLAINT/DISCOV<br>ARMS COMPLAINT N   | · · · —  |  |  |
|--|------------------------------|--|--|--|--|
| AIRS ID#: 0112272 DATE: 4/30/0   | <u> </u>                     | RRIVE: <u>1410</u>   | DEPART: <u>1540</u>  |  |  |
| FACILITY NAME: AERO PRECIS   | SION REPAIR & OVER           | HAUL   |  |  |  |
| FACILITY LOCATION: 580   | S Military Trail             |  |  |  |  |
| DE   | ERFIELD BEACH 334            | 42   |  |  |  |
| RESPONSIBLE OFFICIAL: ALE  | X TEARLE                     | PHON   | <b>IE:</b> (954)428-9500   |  |  |
| CONTACT NAME: Brian Meyer  |                              | PHON   | Œ:   |  |  |
| REMITTANCE YEAR: 2006  | ENTITLEM                     | ENT PERIOD: 1/26/200 (effective d  |  |  |  |
| PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box)  ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE |                              |  |  |  |  |
| PART II: NOTIFICATION – Rule (check ☑ appropriate box(es))   | 62-210.300 FAC               |  |  |  |  |
| 1. Halogenated solvent used perchloroethylene methylene chloride trichloroethylene   |                              | following machine type( Batch Vapor, x Batch Vapor, x New In-line Existing In-line | form that facility has the s). $\leq 1.21 \text{ m}^2 - \dots $ $\geq 1.21 \text{ m}^2 - \dots $ |  |  |
| DADELIN CLASCOPICATION D. L. CA A12 200 DAG  |                              |  |  |  |  |
| PART III: <u>CLASSIFICATION</u> – Rule 62-213.300 FAC Indicate the machine type(s) observed at the facility:                     |                              |  |  |  |  |
| Batch Vapor, $x \le 1.21 \text{ m}^2$  | <del></del>                  | line   | Batch Cold (immersion)   |  |  |
| Batch Vapor, $x > 1.21 \text{ m}^2$ [  | Existing                     | In-line  | Batch Cold (remote reservoir)  |  |  |

|             | RT IV: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC  A. Batch Vapor and In-Line Machines   |              |          |      |
|-------------|--|--------------|----------|------|
|             | 1. Does the facility maintain an idling and downtime mode cover that is readily opened and closed, that completely covers, has no cracks, holes, or defects; OR maintain a room designed   |              |          |      |
|             | with reduced draft according to Part II, Section (5)(c)6.b of the permit notification?   | ⊠Yes         | □No      |      |
|             | 2. Does the facility maintain a freeboard ratio of 0.75 or greater?  | ⊠Yes         | □No      |      |
|             | 3. Does the facility utilize a parts basket or parts whose size is less than 50% of the solvent-air interface area; OR introduce parts or parts basket at 0.9 m/min (3 ft/min) or less?  | Yes          | □No      |      |
|             | 4. Does the facility conduct all spraying operations within the vapor zone or an area not directly exposed to ambient air?   | ⊠Yes         | □No      |      |
|             | 5. Does the facility install and maintain an automated parts handling system capable of moving the parts/parts basket at 3.4 m/min. (11ft/min) or less?  | Yes          | □No      |      |
|             | 6. Does the facility install and maintain a carbon adsorber on all machines using a lip exhaust? The exhaust concentration should not exceed 100 ppm halogenated solvent, the carbon adsorbe should not be by-passed, the lip exhaust shall be located above the closed machine cover  | r<br>□Yes    | □No      | ⊠N/A |
|             | 7. Does the facility have each machine equipped with:  a. a device to shut off sump heat if the solvent level drops to the heater coils?  b. a device to shut off sump heat if the vapor level rises above the height of the   | ⊠Yes         | □No      |      |
|             | vapor condenser?  c. a primary condenser?  | ⊠Yes<br>⊠Yse | □N<br>□N |      |
|             | 8. Does the facility store all waste solvent, still bottoms, and sump bottoms in closed containers?  | ⊠Yes         | □No      |      |
| В. <u>І</u> | Batch Cold Cleaning Machines  1. Does the facility collect and store all waste solvent in closed containers?  2. Does the facility use a flexible hose or flushing device only within the  | Yes          | □No      |      |
|             | freeboard area?  | Yes          | □No      |      |
|             | 3. Does the facility drain cleaned parts for 15 seconds or longer or until dripping ceases, whichever is longer?   | □Yes         | □No      |      |
|             | 4. Does the facility maintain the solvent level inside the machine at or below the fill line?  | Yes          | □No      |      |
|             | 5. Does the facility immediately clean up spills during solvent transfer?  |              |          |      |
|             | Store wipe rags in a covered container?  6. Does the facility operate the agitator to produce a rolling motion? (applicable only when air or pump agitated solvent bath used)  | □Yes         | □No      | □N/A |
|             | 7. Does the facility ensure that the machine is not exposed to drafts greater than 40 m/min (132 ft/min) when the cover is open?   | □Yes         | □No      | ∐N/A |
|             | 8. Does the facility ensure that sponges, fabrics, wood and paper products are <u>not</u> placed in the machine?   | □Yes         | □No      |      |
|             | <u>Remote Reservoir Type Only</u>  |              |          |      |
|             | 9. Does the facility employ a tightly fitting cover over the solvent sump?  The cover must be closed at all times except during parts cleaning <i>Immersion Type Only</i>  | Yes          | □No      | □N/A |
|             | 10. Does the facility employ a tightly fitting cover and a water layer with a thickness of at least 2.5 cm (1 in.); OR employ a tightly fitting cover and maintain a freeboard ratio of 0.75? Tightly fitting cover must be closed at all times except during parts entry and removal. | □Yes         | □No      | □N/A |

| PA | PART V: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (not applicable to batch cold cleaning machines)  Facility chose to meet requirements using:  control device combination / work practice standards  alternative solvent emission limit (proceed to Part VI)  idling emission limit / work practice standards (proceed to Part VI) |   |   |  |  |
|----|---|---|---|--|--|
| A. | Batch Vapor   | Machines, $x \le 1.21 \text{ m}^2$  |   |  |  |
|    | (Select control combination)  |   | <u>DEVICE IN USE</u>  |  |  |
|    | 1.  | working mode cover  reduced room draft freeboard refrig. device       | 1.0 freeboard ratio - \( \) 1.0 freeboard ratio - \( \) 1.0 freeboard ratio - \( \) superheated vapor \( \) working mode cover \( \) reduced room draft \( \) 1.0 freeboard ratio - \( \) dwell   | superheated vapor superheated vapor dwell  |  |
|    | 9.  | freeboard refrig. device carbon adsorber  | carbon adsorber 1.0 freeboard ratio -   | superheated vapor  |  |
| В. | Batch Vapor   | Machines, $x > 1.21 \text{ m}^2$  |   |  |  |
|    | ( Select contro   |   |   |  |  |
|    | combination   |   | <u>DEVICE</u> <u>IN</u> <u>USE</u>  |  |  |
|    | <ol> <li>□g</li> </ol>  | freeboard refrig. device 1.0 freeboard ratio | superheated vapor Superheated vapor Superheated vapor Superheated vapor Superheated vapor Preduced room draft - Preduced room draft - Preduced room draft - Superheated vapor Preduced room draft Preduced room | 1.0 freeboard ratio  working mode cover  reduced room draft  carbon adsorber  dwell   1.0 freeboard ratio  superheated vapor |  |
| C. | Existing In-I   | Line Machines   |   |  |  |
|    | (Select control combination)  |   | <u>DEVICE IN USE</u>  |  |  |
|    | 1.  | freeboard refrig. device superheated vapor freeboard refrig. device carbon adsorber   | 1.0 freeboard ratio -   |  |  |
| D. | New In-Line   | Machines  |   |  |  |
|    | (Select contro<br>combination)  |   | <u>DEVICE IN USE</u>  |  |  |
|    |   | freeboard refrig. device freeboard refrig. device superheated vapor   | superheated vapor - carbon adsorber carbon adsorber   |  |  |

| PART VI: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62   | 2-213.300(3) FAC   |            |          |  |  |  |
|--|--|------------|----------|--|--|--|
| Has the responsible official maintained the following: |  |            |          |  |  |  |
| machine and control equipment?                         | 1. Owner's manuals, design specifications, and other instructional materials for cleaning machine and control equipment? |            |          | <ul> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> </ul> |  |  |
| Art Pennetta 4/30/07                                   |  |            |          |  |  |  |
| Inspector's Name (Please Print)                        | Date of Inspection   |            |          |  |  |  |
|  | 4/08   |            |          |  |  |  |
| Inspector's Signature Approximate Date of Next         |  | Inspection | <u> </u> |  |  |  |
| COMMENTS:  |  |            |          |  |  |  |