

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

RE-INSPECTION (FUI)	COMPLAINT/DISCOVERY (CI)
(101)	ARMS COMPLAINT NO:
AIRS ID#: 0330229 DATE: <u>01/06/2009</u>	ARRIVE: <u>8:30 am</u> DEPART: <u>10:15 am</u>
FACILITY NAME: VICK'S CLEANERS #7	
FACILITY LOCATION: 2915 Navy Blvd	
PENSACOLA 32505-80)21
OWNER/AUTHORIZED REPRESENTATIVE: GRAY	Y VICK PHONE: (850)432-8351
CONTACT NAME: Gray Vick	PHONE:
ENTITLEMENT PERIOD: 8/10/2006 / 8/10/2011 (effective date) (end date)	
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (che	·
☑ IN COMPLIANCE ☐ MINOR Non-COMPL	JANCE SIGNIFICANT Non-COMPLIANCE
PART II: FACILITY CLASSIFICATION - Rule 62-213 (check only one box in A)	3.300 FAC
A. 1. Existing small area source	2. New small area source
dry-to-dry only, $x < 140 \text{ gal/yr}$ transfer only, $x < 200 \text{ gal/yr}$ both types, $x < 140 \text{ gal/yr}$ (constructed before $12/9/91$)	dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)
dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr	dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr
dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before $12/9/91$) 3. Existing large area source dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr	dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after $12/9/91$) 4. New large area source \bigcirc dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr

PA	RT III: GENERAL CONTROL REQUIREMENTS - Rule 62-213.300 FAC	(check ☑ only one box	
Do	es the responsible official of the dry cleaning facility:	for each question)	
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A	
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A	
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No	
	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A	
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No ⊠ N/A	
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)		
	1. If the facility classification is a Existing small area source , no controls are requi	ired. Proceed to Part V.	
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.		
	 If the facility classification is a Existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 If the facility classification is a New large area source, the machine should be equipped with a refrigerated 		
	condenser. Complete both sections A and B below.	Juipped with a ferrigerated	
Α.	Has the responsible official of all <u>existing large</u> <u>area & new sources</u> :	(check ☑ only one box for each question)	
1.	Equipped all machines with the appropriate vent controls?	⊠Yes □No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes No N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes No N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	- □Yes □No ⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	⊠Yes □No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)			
B. Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No		
Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	\Boxedam Yes \Boxedam No \Boxedam N/A		
a) Is the temperature differential equal to, or greater than 20° F?	☐Yes ☑ No ☐ N/A		
3. Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A		
a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A		
4. Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend,			
contraction, or expansion; and downstream from no other inlet?	Yes No N/A		
5. Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	□Yes □ No □ N/A		
6. Route airflow to the carbon adsorber (if used) at all times?	Yes No No N/A		
PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC			
Does the responsible official:	(check ✓ only one box for each question)		
1. Maintain receipts for perc purchased?	- Xes No		
2. Maintain rolling monthly total of yearly perc consumption?	∑ Yes □ No		
3. Maintain leak detection inspection and repair reports for the following:			
Maintain leak detection inspection and repair reports for the following: a) documentation of leaks repaired w/in 24 hrs? or;	- X Yes No No N/A		
	-		
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days			
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No		
a) documentation of leaks repaired w/in 24 hrs? or; b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Maintain calibration data? (for applicable direct reading instruments)	 Yes □ No □ N/A Yes □ No □ N/A Yes □ No □ N/A 		
 a) documentation of leaks repaired w/in 24 hrs? or;	 ☐ Yes ☐ No ☐ No ☐ No ☐ No ☐ No ☐ No ☐ Yes ☐ No ☐ No 		
 a) documentation of leaks repaired w/in 24 hrs? or;	☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☒ N/A ☐ Yes ☐ No ☐ Yes ☐ No ☐ Yes ☐ No		

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	
. Does the facility maintain a leak log?	
a) Hose connections, fittings, couplings, and valves	
. Which method(s) of detection (is/are) used by the responsible official?	
a) Visual examination (condensed solvent on exterior surfaces)	
1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm?	
Greg Landry 1/6/2009	
Inspector's Name (Please Print) Date of Inspection	
1/6/2010	
Inspector's Signature Approximate Date of Next Inspection	
COMMENTS: Inspections for perchloroethylene (PCE) leaks are conducted weekly using a halogenated hydrocarbon detector. A eak detection inspection was conducted while on site and the instrument was operated according to manufacturer's instructions. The PCE leak detector is capable of detecting PCE concentrations of 25 ppm or lower. The refrigerated condenser outlet remperature is monitored weekly to determine the temperature is equal to or less than 45 degrees F.	

temperature is monitored weekly to determine the temperature is equal to or less than 45 degrees F.

Records for all five PCE machines were up to date and well maintained. Inspection records, PCE purchase receipts, and spare parts

receipts were up to date. PCE purchases of 1,035 gallons for all six machines matched those amounts recorded on the calendars. Areas around the PCE machines were clean and well maintained.

The Compliance Statement Report for this facility has been received by the Department.