INCOMPANY PROTECTION	
and the	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2)	COMPLAINT/DISCOVEI ARMS COMPLAINT NO		
AIRS ID#: 0990420 DA	ГЕ: <u>4/24/2009</u>	ARRIVE: <u>1:00 PM</u>	DEPART: <u>1:30 PM</u>	
FACILITY NAME: ELI	TE CLEANERS			
FACILITY LOCATION	405 S Federal Hwy			
	BOCA RATON 33432	2		
OWNER/AUTHORIZE	D REPRESENTATIVE: DRE	EW SPOTO PHONE	C: (561)362-9788	
CONTACT NAME: Sa	ame	PHONE	2: (
ENTITLEMENT PERIC	DD: 8/20/2006 / 8/20/2011 (effective date) (end date)	L		
IN COMPLIANC	CE MINOR Non-COMP	PLIANCE SIGNIFICAN	NT Non-COMPLIANCE	
	LASSIFICATION - Rule 62-2 ly one box in A)	213.300 FAC		
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr2. New small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)2. New small area source dry-to-dry only, $x < 140$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)				
transfer only, both types, 14	e area source ly, $140 \le x \le 2,100$ gal/yr $200 \le x \le 1,800$ gal/yr $40 \le x \le 1,800$ gal/yr before $12/9/91$)	4. New large area source dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1$ (constructed on or after	x ≤ 2,100 gal/yr ≤ 1,800 gal/yr ,800 gal/yr	
5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits				
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 75 gallons.				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A

PART IV: <u>PROCESS</u> <u>VENT</u> <u>CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)				
	1. If the facility classification is a Existing small area source , no controls are required. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.			
	3. If the facility classification is a Existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Carbon adsorber must have been installed prior to September 22, 1993</i>			
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated
А.	Has the responsible official of all <u>existing large area & new sources</u> :		☑ only each que	one box for stion)
1.	Equipped all machines with the appropriate vent controls?	Yes	No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	No	□N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No	

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ o each	only one b question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes	No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? a) Is the temperature differential equal to, or greater than 20° F?		□ No □ No	⊠N/A ⊠ N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A	

PART V: <u>RECORDKEEPING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for				
Does the responsible official:	each question)			
1. Maintain receipts for perc purchased?	Yes 🗌 No			
2. Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	- Xes No N/A			
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A			
6. Maintain a startup/shutdown/malfunction plan?	Yes 🗌 No			
7. Maintain deviation reports?	Yes No N/A			
a) Problem corrected?	- Xes No N/A			
8. Maintain a compliance plan, if applicable?	Yes No N/A			

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

2. Does the facility maintain a leak log?	detection and repair inspection?	Xes No
a) Hose connections, fittings, couplings, and valves Yes No N/A g) Muck cookers Yes No N/A b) Door gakets and seating Yes No N/A h) Stills Yes No N/A c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Yes No N/A c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Yes No N/A c) Filter gaskets and seating Yes No N/A i) Exhaust dampers Yes No N/A e) Solvent tanks and containers Yes No N/A k) Cartridge filter housings Yes No N/A f) Water separators Yes No N/A k) Cartridge filter housings Yes No N/A f) Water separators Yes No N/A k) Cartridge filter housings Yes No N/A f) Water separators Yes No N/A i) Solvent on exterior surfaces) a) a) b) Solvent on surfaces) a) iiii iii iiii	2. Does the facility maintain a leak log?	🖾 Yes 🗌 No
a) Visual examination (condensed solvent on exterior surfaces) a) b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) c) e) Halogen leak detector e) **If using direct-reading instrumentation, is the equipment: e) **If using direct-reading instrumentations in a range of 0-500 ppm? 1) 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) 3) Inspected for leaks and obvious signs of wear on a weekly basis? 3) 4) Kept in a clean and secure area when not in use? 4) 5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) 5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) 4/24/2009 Inspector's Name (Please Print) 4/2010	 a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps	ills Xes No N/A haust dampers Yes No X/A verter valves Xyes No N/A
b) Physical detection (airflow felt through gaskets) b) c) Odor (noticeable perc odor) c) d) Use of direct-reading instrumentation (FID/PID/calorimetric tubes) c) e) Halogen leak detector d) **If using direct-reading instrumentation, is the equipment: e) **If using direct-reading instrumentation, is the equipment: ** [N/A 1) Capable of detecting perc vapor concentrations in a range of 0-500 ppm? 1) 2) Calibrated against a standard gas prior to and after each use (PID/FID only)? 2) 3) Inspected for leaks and obvious signs of wear on a weekly basis? 3) 4) Kept in a clean and secure area when not in use? 4) 5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) 5) Verified for accuracy by use of duplicate samples (calorimetric only)? 5) 4/24/2009 Inspector's Name (Please Print) 10 4/2010	4. Which method(s) of detection (is/are) used by the responsible offic	cial?
Inspector's Name (Please Print) Date of Inspection 4/2010	 b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tu e) Halogen leak detector	b) b) b) b) b) b) b) b)
4/2010	Jeffrey Dizek	4/24/2009
	Inspector's Name (Please Print)	Date of Inspection
Inspector's Signature Approximate Date of Next Inspection		4/2010
	Inspector's Signature	Approximate Date of Next Inspection

COMMENTS: