

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

<u>INSPECTION</u> <u>TYPE</u> : ANNUAL	L (INS1, INS2)	COMPLAINT/DISCOVERY	(CI)				
RE-INSP	ECTION (FUI)	ARMS COMPLAINT NO:					
AIRS ID#: 1030318 DATE: <u>7/10/2</u>	<u>2006</u>	ARRIVE: <u>11:00AM</u>	DEPART: <u>11:50AM</u>				
FACILITY NAME: FASHION CL	FACILITY NAME: FASHION CLEANERS						
FACILITY LOCATION: 115	FACILITY LOCATION: 1152 Court St						
CL	CLEARWATER 34756						
RESPONSIBLE OFFICIAL: MIC	HAEL SONG	PHONE:	(727)461-1137				
CONTACT NAME: MR. MICHAEL SONG		PHONE: (
REMITTANCE YEAR: 2005	ENTITLE	EMENT PERIOD: 2/2/2002 (effective date)	/ 2/2/2007 (end date)				
PART I: INSPECTION COMPLI		·					
☐ IN COMPLIANCE ☐	MINOR Non-COMPI	LIANCE SIGNIFICANT	Non-COMPLIANCE				
PART II: FACILITY CLASSIFIC (check ☑ only one box		3.300 FAC					
A. 1. Existing small area sound dry-to-dry only, x < 140 transfer only, x < 200 gas both types, x < 140 gal/y (constructed before 12/9)	gal/yr l/yr /r /91)	2. New small area source dry-to-dry only, x < 140 g transfer only, x < 200 gal/both types, x < 140 gal/yr (constructed on or after 12	/yr				
3. Existing large area sound dry-to-dry only, $140 \le x$ transfer only, $200 \le x \le$ both types, $140 \le x \le 1,8$ (constructed before $12/9$)	< 2,100 gal/yr 1,800 gal/yr 800 gal/yr	4. New large area source dry-to-dry only, $140 \le x \le 1$ transfer only, $200 \le x \le 1$, both types, $140 \le x \le 1,80$ (constructed on or after 12)	,800 gal/yr 00 gal/yr				
5. Ineligible for General F drop store/out of busines facility exceeds above li	ss/petroleum						
B . The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 0.7 gallons.							

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check ☑ only one box			
Do	es the responsible official of the dry cleaning facility:	for each question)			
1.	Store perc, and wastes containing perc, in tightly sealed & impervious containers?	⊠Yes □No □N/A			
2.	Examine the containers for leakage?	⊠Yes □ No □ N/A			
3.	Close and secure machine doors except during loading/unloading?	⊠ Yes □ No			
4.	Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	⊠Yes □ No □ N/A			
	Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	□Yes □ No □ N/A			
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the facility classification is a Existing small area source, no controls are requi	nired. Proceed to Part V.			
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a Existing large area source , the machine should be refrigerated condenser or a carbon adsorber. Complete both sections A and B belo <i>must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be econdenser. Complete both sections A and B below.	equipped with a refrigerated			
A.	Has the responsible official of all <u>existing large area & new sources</u> :	(check ☑ only one box for each question)			
1.	Equipped all machines with the appropriate vent controls?	- ⊠Yes □No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes □No □N/A			
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	- □Yes □No ⊠N/A			
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	- ⊠Yes □No			
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	⊠Yes □No □N/A			
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	- ⊠Yes □No			

PA	PART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC (continued)					
В.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)				
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	⊠Yes □No				
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- ∐Yes □ No ⊠N/A				
	a) Is the temperature differential equal to, or greater than $20^{\rm o}F?$	☐Yes ☐ No ☒ N/A				
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	□Yes □ No ⊠ N/A				
	a) Is the perc concentration equal to, or less than 100 ppm?	☐Yes ☐ No ☒ N/A				
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	□Yes □ No ⊠ N/A				
5	Equip transfer machines (dryers, reclaimers, and washers) with individual					
٥.	condenser coils?	- Yes No N/A				
6.	Route airflow to the carbon adsorber (if used) at all times?	☐Yes ☐ No ☒ N/A				
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(check ☑ only one box for				
Do	oes the responsible official:	each question)				
1.	Maintain receipts for perc purchased?	Yes No				
2.	Maintain rolling monthly total of yearly perc consumption?	⊠ Yes □ No				
3.	Maintain leak detection inspection and repair reports for the following:					
	a) documentation of leaks repaired w/in 24 hrs? or;	Yes No No N/A				
	b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	☐ Yes ☐ No N/A				
4.						
5	Maintain calibration data? (for applicable direct reading instruments)	☐ Yes ☐ No ☒ N/A				
٦.	Maintain calibration data? (for applicable direct reading instruments) Maintain exhaust duct monitoring data on perc concentrations?	<u> </u>				
		☐ Yes ☐ No N/A				
6.	Maintain exhaust duct monitoring data on perc concentrations?	☐ Yes ☐ No ☐ N/A ☐ Yes ☐ No				
6.	Maintain exhaust duct monitoring data on perc concentrations? Maintain a startup/shutdown/malfunction plan?	 Yes □ No ⋈ N/A Yes □ No Yes □ No ⋈ N/A 				

PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?				
2. Does the facility maintain a leak log?				
3. Does the responsible official check the following areas for lead a) Hose connections, fittings, couplings, and valves	Yes			
Which method(s) of detection (is/are) used by the responsible official?				
a) Visual examination (condensed solvent on exterior surfaces)				
**If using direct-reading instrumentation, is the equipment: -	**			
 Capable of detecting perc vapor concentrations in a range of Calibrated against a standard gas prior to and after each use Inspected for leaks and obvious signs of wear on a weekly Kept in a clean and secure area when not in use? Verified for accuracy by use of duplicate samples (calorim 	of 0-500 ppm? 1) Yes No e (PID/FID only)? 2) Yes No basis? 3) Yes No 4) Yes No			
SHEA JACKSON	7/10/2006			
Inspector's Name (Please Print)	Date of Inspection			
	7/2007			
Inspector's Signature	Approximate Date of Next Inspection			
COMMENTS: •During this inspection, I met with the facility responsible official, Mr. Song. I observed the Union L8602000 dryer. The Fluomatic- BT37 unit was not in use at this time. The perchloroethylene level in this machine's base reservoir was 35 gallons. Mr. Song stated the older unit has not been used since October 2005. He stated the condenser coils were leaking and he was considering replacing with a new hydrocarbon dryer. I informed Mr. Song he could have the vendor possibly transfer the perchloroethylene to the Union L860U2000 machine. • I reviewed the calendar record. Mr. Song is recording temperatures observations and perchloroethylene usage in only one				
calendar for the working dry cleaning machine. The 12 month to perchloroethylene since October 2005. The temperature readings	tal was 0.7 gallons, because Mr. Song had not purchased any			
I observed the dryer, during the cool down cycle. The te	emperature was registering at 32°F, on the temperature readout			

I asked Mr. Song to contact me if he removes the B37 machine. (See photos)

This facility is in compliance.