

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D	DISCOVERY (CI)				
AIRS ID#: 1270121 DA	ΓΕ: <u>9/5/13</u>	ARRIVE: <u>1:15</u>	DEPART: <u>2:00</u>				
FACILITY NAME: PEI	RSONAL TOUCH DRY CLEAN	IERS					
FACILITY LOCATION	2601 S Woodland Blvd						
	DELAND 32720						
OWNER/AUTHORIZE Email: debonis89@y CONTACT NAME: St Email: ENTITLEMENT PERIO	ephen Maggard	PH DEBONIS	PHONE: (386)738-9786 Mobile: PHONE: Mobile:				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION (check ✓ only one box in A) - Rule 62-213.300 FAC							
transfer only, both types, x (constructed by a constructed by a constructe	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)	transfer only, both types, x (constructed of types). A very large are dry-to-dry on transfer only, both types, 14	only, $x < 140$ gal/yr y, $x < 200$ gal/yr x < 140 gal/yr d on or after $12/9/91$)				
	volume of all perchloroethylene (was 0.00 gallons.	perc) purchases made	de in each of the previous 12 months by the	his dry			

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			(check ox for e		only o		
1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A	
2. Are all perc. containers leak free?	\boxtimes	Yes	\Box	No	\Box	N/A	
3. Are all machine doors kept closed and secured except during loading/unloading?		Yes	_	No	_		
4. Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No		N/A	
5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A	
Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes		No		N/A	
PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form) 1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V. 2. If the facility classification is a new small area source, the machine should be equipped with a refrigerated condenser. Complete section A. below. 3. If the fa cility classification is an existing large area source, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993 4. If the facility classification is a new large area source, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.							
A. Has the responsible official of all existing large area & new sources:			(check ox for e		-		
1. Equipped all machines with the appropriate vent controls?		Yes		No			
2. Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes		No		N/A	
3. Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		No		N/A	
4. Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes		No		N/A	
5. Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes		No		N/A	
6. Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes		No			

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
В.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	□ N	No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	□ N	No		N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	□ N	No		N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes	□ N	No		N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	□ N	No		N/A
						_	
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No	Ш	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No	Ш	N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	□ N	No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		(1	check 🔯	Z o	only o	ne
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(1	check 🔽	Z o	only o	ne
P A			(bo	check ☑ x for eac	Z o	only o	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(look)	check ☑ x for eac	Zoch qu	only o	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	((bo) Yes Yes	check x for each	Zoch qu	only o	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	((bo) Yes Yes	check × for each	Z o ch qu No No	only o	ne n)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	\boxtimes	Yes Yes Yes	check 🔯 x for each	Z o ich qu No No	only onestio	ne n)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check 🔯 x for each	Z o ach qu No No No	only o	ne n) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes	check 🔯 x for each	Z o ch qu No No No	only o	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained? Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? Is calibration data maintained for applicable direct reading instruments? Is exhaust duct monitoring data on perc concentrations maintained?		Yes Yes Yes Yes Yes Yes Yes	check 🔯 x for each	Z o och que No	only onestio	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	check 🔯 x for each	Z o ach qu No No No No No No	only o	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one		
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)		
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☒ None used					
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to					
	the manufacturer's instructions (manual was available and RO could demonstrate					
	procedure) ?	Yes	☐ No			
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer					
	operated according to EPA Method 21 ?	Yes	☐ No	N/A		
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of					
	each component interface where leakage could occur and moving it slowly along					
	the interface periphery?	Yes	☐ No			
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or					
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per					
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A		
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations					
	of PCE of 25 parts per million by volume (based on documented specifications) and					
	indicating a concentration of 25 parts per million by volume or greater by emitting					
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A		
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) whi	le the		
	system is in operation (§63.322(k))?					
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for inspection of perceptible leaks)					
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes N/A j	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	 N/A N/A N/A N/A N/A 		
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a halogonial value of the following dry cleaning system components inspected monthly for vapor leaks using a halogonial value of the following dry cleaning system components inspected monthly for vapor leaks using a halogonial value of the following dry cleaning system components inspected monthly for vapor leaks using a halogonial value of the following dry cleaning system components in the following dry cleaning system components are considered by the following dry cleaning system components are considered by the following dry cleaning system components are considered by the following system components are considered by the following system considered by the followi	enated	hydrocarb	on detector		
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	he		
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))					
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Yes N/A j	Yes Yes Yes Yes	□ No□ No□ No□ No□ No	 N/A N/A N/A N/A N/A 		

PART VI: LEAK DETECTION AND REPAIRS – Rule 6	2-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as required? ☐ Leak log documentation ☐ RO Assurances ☐ On-site observation ☐ other Explain other:						
Daniel K. Hall	September 5, 2013					
Inspector's Name (Please Print)	Date of Inspection					
Janist Kthel						
Inspector's Signature	Approximate Date of Next Inspection					

COMMENTS: The dry cleaning machine has been inoperable since roughly the 3rd week of May, 2011. They are currently operating as a drop-off with dry cleaning going to Classic Cleaners (1270124). The facility was found to be in compliance with air regulations, please see hazardous waste report for additional information regarding findings for that program.