MOTORIN MOTORINA	
St Kart	
Z FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS

Environmental Compliance

COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE: ANNUAL (INS1, INS2) COMPLAINT/DISCOVERY (CI) RE-INSPECTION (FUI) ARMS COMPLAINT NO:				
AIRS ID#: 1170070 DATE: <u>7/10/08</u>	ARRIVE: <u>2:33</u> DEPART: <u>2:54</u>			
FACILITY NAME: WYMORE CLEANERS				
FACILITY LOCATION: 250 S WYMORE RD				
ALTAMONTE SPRINGS	5 32714			
OWNER/AUTHORIZED REPRESENTATIVE: BONG	G TAI PHONE: (407)862-9611			
CONTACT NAME:	PHONE:			
ENTITLEMENT PERIOD: 7/2/2007 / 7/2/2012 (effective date) (end date)				
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE				
PART II: FACILITY CLASSIFICATION - Rule 62-213 (check ☑ only one box in A)	3.300 FAC			
A. 1. Existing small area source dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed before 12/9/91)	2. <u>New small area source</u> dry-to-dry only, $x < 140$ gal/yr transfer only, $x < 200$ gal/yr both types, $x < 140$ gal/yr (constructed on or after 12/9/91)			
3. Existing large area source \Box 4. New large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)4. New large area source \Box dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)5. Ineligible for General Permit drop store/out of business/petroleum facility exceeds above limits \Box				
B. The total quantity of perchloroethylene (perc) purc cleaning facility was 20 gallons.	chased within the preceding 12 months by this dry			

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	🛛 Yes 🗌 No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC

(Refer to Part II-A.1.-4. Classification: page <u>1</u> of <u>4</u>, this form)

1. If the facility classification is a **Existing small area source**, no controls are required. **Proceed to Part V.**

2. If the facility classification is a <u>New small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the facility classification is a **Existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993*

4. If the facility classification is a <u>New large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

A.	Has the responsible official of all <u>existing large area & new sources</u> :		only or only of the second sec	one box for ation)
1.	Equipped all machines with the appropriate vent controls?	Yes	No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	∐Yes □No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	IYes No N/A Yes No N/A		
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A		
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A		
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A		
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes No N/A		
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A		

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC				
Does the responsible official:	(check ☑ only one box for each question)			
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No			
2. Maintain rolling monthly total of yearly perc consumption?	Yes No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	- Xes No N/A			
 b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 	Yes No N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	- Xes No N/A			
6. Maintain a startup/shutdown/malfunction plan?	- 🛛 Yes 🗌 No			
7. Maintain deviation reports?	- Xes No N/A			
a) Problem corrected?	🗌 Yes 🗌 No 🖾 N/A			
8. Maintain a compliance plan, if applicable?	- \boxtimes Yes \square No \square N/A			

PART VI:	LEAK DETECTION AN	<u>D REPAIRS</u> – Rule 62-213.300 FAC
----------	-------------------	--

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak detection and repair inspection? ------

(check ☑ only one box for each question)



2. Does the facility maintain a leak log?	Xes No
 3. Does the responsible official check the following areas for leaks? a) Hose connections, fittings, couplings, and valves b) Door gaskets and seating c) Filter gaskets and seating d) Pumps e) Solvent tanks and containers f) Water separators Yes No N/A i Yes No N/A j Dive Yes No N/A k) Cart Yes No N/A 	s XYes No N/A ust dampers Yes No N/A rter valves Yes No N/A
4. Which method(s) of detection (is/are) used by the responsible official	1?
 a) Visual examination (condensed solvent on exterior surfaces) b) Physical detection (airflow felt through gaskets) c) Odor (noticeable perc odor) d) Use of direct-reading instrumentation (FID/PID/calorimetric tube e) Halogen leak detector 	b)⊠ c)⊠ d)□**(see below) e)□
1) Capable of detecting perc vapor concentrations in a range of 0-50	$0 \text{ ppm}? \dots 1) \square Yes \square No$
2) Calibrated against a standard gas prior to and after each use (PID3) Inspected for leaks and obvious signs of wear on a weekly basis?	
4) Kept in a clean and secure area when not in use?	4) Yes No
5) Verified for accuracy by use of duplicate samples (calorimetric o	nly)? 5) Yes No

Wanda Parker-Garvin

Inspector's Name (Please Print)

7/10/2008

Date of Inspection

Wanda Parker Karvin

Inspector's Signature

Approximate Date of Next Inspection

COMMENTS:

Facility Name :	Wymore Cleaners
Facility Address :	250 S. Wymore Road, Altamonte Springs, FL 32714
Date/Time :	July 10, 2008/2:33pm
Persons present :	Wanda Parker-Garvin - FDEP; Bong Tai
Responsible Official :	Bong Tai
Phone/Email :	407-862-9611

Hazardous Waste Requirements

<pre>{</pre>		
Inspection Question	Rule Reference	Answer
General Records:		
 Type of facility? (CESQG, SQG, LQG*) 		🖂 CESQG 🗌 SQG
Generator ID #:		
Preparedness & Prevention		
Employee notification system?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.32(a)]	🗌 Yes 🛛 No
Device to summon emergency response agencies?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.32(b)]	🗌 Yes 🛛 No
Portable fire extinguishers and spill control equipment?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.32(c)]	🗌 Yes 🛛 No
Adequate fire suppression equipment?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.32(d)]	🗌 Yes 🛛 🖾 No
Program to test emergency equipment?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.33]	🗌 Yes 🛛 No
Minimized possibility of spills and releases	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 265.31]	🗌 Yes 🛛 No
Contingency Planning:		
Designated emergency coordinator?	SQG [40 CFR 262.34(d)(4)(i)] LQG [40 CFR 265.55]	
 Posted names and telephone numbers of emergency coordinators, locations of fire alarms and extinguishers, fire department telephone numbers, and evacuation routes? 	SQG [40 CFR 262.34(d)(4)(ii)] LQG [40 CFR 265.52]	🗌 Yes 🛛 No
Storage of hazardous waste:		
• The facility must not be storing quantities of waste in excess of the quantity storage limits. To determine whether the facility is in compliance calculate the total weight of all perc waste in the	Maximum quantity limits are: CESQG = 2,200 lbs	
storage area as follows:	SQG = 13,200 lbs	
 For 15-gal containers: # of containers2 x 120 lbs/container = lbs stored 		240
 For 30-gal containers: # of containersx 240 lbs/container = lbs store 		
Are containers marked with an accumulation start date?	SQG [40 CFR 262.34(d)(4)] LQG [40 CFR 262.34(a)(2)]	🗌 Yes 🛛 No

inspector initial_____

8/21/2008 Page 1 of 4 *If the facility is an LQG then please refer to the Hazardous Waste Section for inspection.

Is the facility in compliance with quantity and time limits for HW s	storage?		
	G [40 CFR 262.34(d)]	Yes II	No 🖂N/A
	G [40 CFR 262.34(a)]		NO $\square N/A$
	G [40 CFR 262.34(c)]		
	G [40 CFR 262.34(c)]		No 🖾 N/A
 If applicable, are satellite areas at/near the point of generation? 	G [40 CFR 262.34(c)] G [40 CFR 262.34(c)]	🗌 Yes 🗌 I	No 🖾N/A
Are containers labeled with the words "Hazardous SQC	G [40 CFR 262.34(d)(4)] G [40 CFR 262.34(a)(3)]	🛛 Yes	🗌 No
Are containers in good condition and kept closed?	G [40 CFR 262.34(d)(2),(4)] G [40 CFR 262.34(a)(1)(i)]	🛛 Yes	🗌 No
	G [40 CFR 262.34(d)(2)] G [40 CFR 262.34(a)(1)(i)]	🛛 Yes	🗌 No
Adequate aisle space and clearly marked exits? SQC	G [40 CFR 262.34(d)(4)] G [40 CFR 265.35]	🛛 Yes	🗌 No
Are weekly inspections conducted and SQC	G [40 CFR 262.34(d)(2)] G [40 CFR 265.174]	🛛 Yes	🗌 No
Are hazardous waste containers stored on a crack- free surface that will contain leaks or spills?		🛛 Yes	🗌 No
Is there adequate secondary containment?		🛛 Yes	🗌 No
Is entrance by unauthorized people restricted?		🛛 Yes	No
Does the storage area have appropriate signage?		🛛 Yes	No
Record keeping			
	G [40 CFR 262 subpart B] G [40 CFR 262 subpart B]	🛛 Yes	🗌 No
Are the originals present?	G [40 CFR 262 subpart B] G [40 CFR 262 subpart B]	🛛 Yes	🗌 No
Exception reports? SQC LQC	G [40 CFR 268.44] G [40 CFR 268.42]	Yes I	No 🖾 N/A
	G [40 CFR 268.7] G [40 CFR 268.7]	🗌 Yes 🗌 I	No 🖾 N/A
facility for at least three years?	SQG [62-730.030(4) F.A.C.] G [40 CFR 262.44] G [40 CFR 262.40]	🛛 Yes	🗌 No
Does the facility ensure waste disposal to a source waste disposal to a	SQG [40 CFR 261.5(g)(3)] G [40 CFR 262.12(c)] G [40 CFR 262.12(c)]	🛛 Yes	🗌 No
Employee Training	5 [40 0/ 11 202.12(0)]		
Are employees trained in HW management? SQG	[40 CFR 262.34(d)(5)(iii)] [40 CFR 265.16(a)&(b)]	🗌 Yes	🛛 No
Is the facility in the dry cleaner solvent clean-up program? If so, what is the Facility ID #?	03, F.S.	95014	180
	078(9)(a), F.S.	🛛 Yes	□ No
around each machine or item of equipment in which			
dry cleaning solvents are used and around any area in			
which solvents or waste-containing solvents are			
stored?			
word an opino of more than a quart of any cloaning	61(1)(d), F.S.		🗌 No
solvent outside of a containment structure, on or after		⊠N	/A
July 1, 1995, reported by the owner or operator to the			
state through the State Warning Point?	61(11)(d), F.S.		
	στ(ττ)(u), τ.Ο.		No No
immediately upon the discovery of such a spill, initiate and complete actions to abate the source of the spill?		⊠N	/A

AST/UST Questions:

Inspection Question	Answer
Does the facility store petroleum products in a UST or AST?	☐ Yes ☐ No ⊠N/A

Separator Water Treatment System Questions:

Inspection Question	Answer	
Is a separator water treatment system employed?	🗌 Yes 🗌 No 🖾N/A	
Is the treatment system directly plumbed to the dry	☐ Yes ☐ No ⊠N/A	
cleaning unit? If so, is it within secondary containment?		
Does the system include a filter to reduce the	☐ Yes ☐ No ⊠N/A	
concentrations of chlorinated solvent(s) in the wastewater		
prior to evaporation or discharge?		
Are records available to demonstrate that the filters have	🗌 Yes 🗌 No 🖾N/A	
been changed in accordance with the manufacturer's		
recommendations?		
Are wastewaters that contain soaps, detergents, chlorine,	🗌 Yes 🗌 No 🖾N/A	
rust, etc. excluded from the treatments system in order to		
ensure that the filter is effective to treat the chlorinated		
solvents?		

Industrial Wastewater Standards

Inspection Question:	Rule Reference	Answer	
Does the facility discharge separator water, mop water from cleaning the work area, and vacuum return water to a sewer, tank, evaporator system provided with a filter to reduce chlorinated solvent concentrations, or container, and never to septic?	62.660 F.A.C.	🛛 Yes 🗌 No	
Are solvent-based pre-spotters excluded from use on garments that are being laundered in a system that discharges to septic?	62.600 F.A.C.	🛛 Yes 🗌 No	
Does the vacuum vent upward so that condensed solvent- containing water is returned to the vacuum tank rather than discharged onto ground?	403.087 F.S.	🛛 Yes 🗌 No	
Is the boiler configured so that no contact water (separator water or vacuum return water) is introduced and can be discharged to the ground during the boiler bleed-off?	403.087 F.S.	🛛 Yes 🗌 No	
If the facility discharges to surface waters, is it in compliance with NPDES?	62.620 F.A.C.	☐ Yes ☐ No ⊠N/A	
If the facility discharges to the ground, is it in compliance with a state permit?	62.620 F.A.C.	☐ Yes ☐ No ⊠N/A	
If the facility discharges to sewer, is it in compliance with local sewer permit?	62.625 F.A.C.	Yes No N/A	
Is the facility on sewer other than POTW?	64 E-G	☐ Yes ☐ No ⊠N/A	

inspector initial

Dry Cleaning Equipment

Туре	Manufacturer	Serial Number	Capacity	Age

<u>Other</u>

Wanda Parker Karvin

inspector initial