

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/D		(CI)	
AIRS ID#: 0571064 DAT	ΓΕ: <u>7/19/2012</u>	ARRIVE: <u>1:15 p</u>	<u>m</u>	DEPART: <u>1:25pm</u>	
FACILITY NAME: CEI	OAR CLEANERS				
FACILITY LOCATION	4330 W BAY TO BAY				
	TAMPA 33629-6607				
OWNER/AUTHORIZEI Email: CONTACT NAME: Email: ENTITLEMENT PERIC	DREPRESENTATIVE: YASA DD: 12/3/2007 / 12/3/2012 (effective date) (end date)	SER YAZBACK	PHONE: Mobile: PHONE: Mobile:	(813)837-5752	
PART I: INSPECTION ☑ IN COMPLIANC	COMPLIANCE STATUS (che	_		Non-COMPLIANCE	
PART II: FACILITY CI	LASSIFICATION - Rule 62-2 only one box in A)	213.300 FAC			
transfer only, 3 both types, x < (constructed b 3. Existing large dry-to-dry onl transfer only, 3 both types, 14 (constructed b 5. Ineligible fo d rop store/out	y, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr pefore 12/9/91)		$\frac{1}{1}$ $\frac{1}{2}$ $\frac{1}$	/yr 2/9/91) $x \le 2,100 \text{ gal/yr}$ 1,800 gal/yr 1,800 gal/yr	
B . The sum of the v cleaning facility v	volume of all perchloroethylene (was gallons.	perc) purchases mad	e in each of t	the previous 12 months by	this dry

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check ox for e		only o questio		
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?		Yes		No		N/A	
2.	Are all perc. containers leak free ?		Yes		No		N/A	
3.	Are all machine doors kept closed and secured except during loading/unloading?		Yes		No			
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?		Yes		No		N/A	
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A	
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds							
	maintain according to the manufacturer's specifications?		Yes		No		N/A	
PA	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC							
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)							
	1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to P	art V.				
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
	3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993							
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated				
A.	Has the responsible official of all existing large area & new sources:			check		only o		
			bo	X IOI E	acii ç	1400110	n)	
1.	Equipped all machines with the appropriate vent controls?		Yes	_	No	questro	n)	
	Equipped all machines with the appropriate vent controls? Equipped dry-to-dry machines with a closed-loop vapor venting system?						n) N/A	
2.			Yes		No		,	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away		Yes Yes		No No		N/A	
 3. 4. 	Equipped dry-to-dry machines with a closed-loop vapor venting system? Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door? Measured and recorded the temperature of the outlet exhaust stream of a		Yes Yes Yes		No No No		N/A	

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)				
В.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes	☐ No	
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes	□ No	□ N/A
	a) Is the temperature differential equal to, or greater than 20° F?	Ш	Yes	∐ No	∐ N/A
3.	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes	□ No	□ N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes	☐ No	□ N/A
4.			Yes	☐ No	□ N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes	☐ No	□ N/A
<u> </u>					11
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	☐ No	□ N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	☐ No	□ N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes	□ No	□ N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		(□ No check ☑ x for each o	only one
PA			(check 🗹	only one
P A	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(bo	check 🗹 x for each o	only one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check 🗹 x for each o	only one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check 🗹 x for each o	only one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo Yes Yes	check 🗹 x for each o	only one question)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check 🗹 x for each o No No No	only one question)
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check 🗹 x for each o No No No	only one question) N/A N/A
1. 2. 3. 4. 5.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes	check 🗹 x for each o No No No No No	only one question) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes	check 🗹 x for each o No No No No No No	only one question) N/A N/A N/A
1. 2. 3. 4. 5. 6.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes Yes Yes	check 🗹 x for each o No No No No No No No	only one question) N/A N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	((check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?		ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes?	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) whi	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarb	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the paragraph) of the paragraph of the system is in operation?	raph sh	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A h) Stills Yes No N/A i) Exhaust dampers Yes No N/A j) Diverter valves Y	Yes Yes Yes Yes Yes	 No No No No No No No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS – Rule	62-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed a	as required?	
☐ Leak log documentation ☐ RO Assurances ☐	On-site observation other	
Explain other:		
Jessica Lopez	7/19/2012	
Inspector's Name (Please Print)	Date of Inspection	
Inspector's Signature	Approximate Date of Next Inspection	

empty. All waste containers were empty.