

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

INSPECTION TYPE:	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/DISCOVE	, ,	
AIRS ID#: 0112281 DA ′	ГЕ: <u>2/28/2012</u>	ARRIVE: <u>1230</u>	DEPART: <u>1400</u>	
FACILITY NAME: SU	PERIOR DRY CLEANERS			
FACILITY LOCATION	5733 Hollywood Blvd			
	HOLLYWOOD 33021-	-6326		
OWNER/AUTHORIZED Email: CONTACT NAME: FI Email: ENTITLEMENT PERIC		Mobile	E: (954)588-0078 E: (954)782-8618	
PART I: INSPECTION IN COMPLIANCE	COMPLIANCE STATUS (ch		NT Non-COMPLIANCE	
A. 1. Existing smal	only one box in A) l area source ly, x < 140 gal/yr	213.300 FAC 2. New small area source dry-to-dry only, x < 1	40 gal/yr	
both types, x - (constructed by a constructed by a constr	pefore 12/9/91)	transfer only, x < 200 both types, x < 140 ga (constructed on or afte 4. New large area source dry-to-dry only, 140 ≤ transfer only, 200 ≤ both types, 140 ≤ x (constructed on or after	al/yr er 12/9/91) ee	
facility exceed B . The sum of the v	at of business/petroleum / ds above limits volume of all perchloroethylene (was 45.00 gallons.	(perc) purchases made in each	of the previous 12 months by this	s dry

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check 🗹 x for each o	only one question)
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes	☐ No	□ N/A
2.	Are all perc. containers leak free ?	\boxtimes	Yes	☐ No	□ N/A
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes	☐ No	
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes	☐ No	□ N/A
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes	☐ No	□ N/A
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?		Yes	☐ No	□ N/A
	RT IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC efer to Part II-A.14. Classification: page 1 of 4, this form)				
	1. If the f acility classification is an existing small area source , no controls are required. P	rocee	ed to P	art V.	
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped condenser. Complete section A. below.	with a	a refrig	gerated	
	3. If the fa cility classification is an existing large area source , the machine should be equipped refrigerated condenser or a carbon adsorber. Complete both sections A and B below. <i>Compust have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped condenser. Complete both sections A and B below.	with	a refriş	gerated	
A.	Has the responsible official of all <u>existing large area & new sources</u> :			check 🗹 x for each o	-
1.	Equipped all machines with the appropriate vent controls?		Yes	☐ No	
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?		Yes	☐ No	□ N/A
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes	☐ No	□ N/A
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?		Yes	☐ No	□ N/A
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?		Yes	☐ No	□ N/A
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?		Yes	□ No	

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)						
B. For all existing large or new large area sources:						
1. Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry,						
reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2. Is the washer exhaus t temperature at the condenser inlet and outlet measured						
and recorded weekly?		Yes		No		N/A
a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
3. Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber,						
if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
a) Is the rame concentration coupl to on loss than 100 nnm?		Vac		Mo		NT/A
a) Is the perc concentration equal to, or less than 100 ppm?	⊔	res	Ш	No	Ш	N/A
4. Is the sampling port on the carbon adsorber exhaust for measuring						
perc concentrations at least 8 duct diameters downstream of any bend,						ĺ
contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No	П	N/A
Contraction, or expansion, and downstream from no state factor.		100		110		11/12
5. Are transfer machines equipped (dryers, reclaimers, and washers) with individual						ľ
condenser coils?		Yes		No		N/A
condenser coils?	_	Yes Yes	_	No No		N/A N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_		_			
condenser coils?	_		_			
6. Is airflow routed to the carbon adsorber (if used) at all times?	_		_			
condenser coils?	_	Yes	(check	No 🗹	only o	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	_	Yes		No 🗹	•	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?		Yes	(check	No 🗹	•	N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?	· 🖂	Yes	(check	No V each	•	N/A
6. Is airflow routed to the carbon adsorber (if used) at all times?	· 🖂	Yes bo Yes	(check	No Z each	•	N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following:	\(\times \)	yes bo Yes Yes	(check ox for e	No Peach No No	questic	N/A one on)
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?	\(\times \)	Yes bo Yes	(check ox for e	No Z each	•	N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following:	\(\times \)	yes bo Yes Yes	(check ox for e	No Peach No No	questic	N/A one on)
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?	\Box	Yes Yes Yes Yes Yes	(check ox for e	No No No No	questic	N/A one on N/A N/A
condenser coils?		yes Yes Yes Yes Yes Yes Yes	(check ox for e	No V each No No No No	questic	N/A one on) N/A N/A N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No No No No No No No No No	questic	N/A one on N/A N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased? 2. Are rolling monthly total s of yearly perc consumption maintained? 3. Are leak detection inspection and repair reports maintained for the following: a) Of any leaks repaired w/in 24 hrs? or; b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? 4. Is calibration data maintained for applicable direct reading instruments? 5. Is exhaust duct monitoring data on perc concentrations maintained? 6. Is a startup/shutdown/malfunction plan maintained for each machine?		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	questic	N/A one on N/A N/A N/A N/A
condenser coils? 6. Is airflow routed to the carbon adsorber (if used) at all times? PART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC 1. Are receipts maintained for all perc purchased?		yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No N	questic	N/A one on) N/A N/A N/A N/A N/A
condenser coils?		Yes Yes Yes Yes Yes Yes Yes Yes	(check ox for e	No	questic	N/A one on N/A N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC	1	(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery?	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	le the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills Y		NoNoNoNoNoNo	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	ne
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes No N/A N/A N/A N/A N/A N/A Yes Yes	Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS - Rule (62-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed as ☐ Leak log documentation ☐ RO Assurances ☐ Explain other:	<u> </u>	
CPitters	2/28/2012	
Inspector's Name (Please Print)	Date of Inspection 2/28/2013	
Inspector's Signature	Approximate Date of Next Inspection	