OWERTAL PROTECTION	
San V	
FLORIDA	

PERCHLOROETHYLENE DRY CLEANERS



## COMPLIANCE INSPECTION CHECKLIST

	JAL (INS1, INS2)	COMPLAINT/DISCOVERY ARMS COMPLAINT NO:	й (CI)	
AIRS ID#: 0990436 DATE: 7/2	2/2008	ARRIVE: <u>11:00 AM</u>	DEPART: <u>11:35 AM</u>	
FACILITY NAME: PROKLEE	N CLEANERS			
FACILITY LOCATION:	21717 SR 7			
	BOCA RATON 33428			
OWNER/AUTHORIZED REPI	RESENTATIVE: ALV	ARO JARAMILLO <b>PHONE:</b>	(561)852-1277	
CONTACT NAME: Same		PHONE:	(	
	/3/2005 / 3/3/2010 fective date) (end date)			
PART I: <u>INSPECTION COMP</u>				
IN COMPLIANCE	MINOR Non-COMP	LIANCE 📋 SIGNIFICANT	Non-COMPLIANCE	
·				
PART II: FACILITY CLASSI (check I only one be		3.300 FAC		
A. 1. <u>Existing small area s</u> dry-to-dry only, x < 1 transfer only, x < 200 both types, x < 140 ga (constructed before 12	al/yr	2. <u>New small area source</u> dry-to-dry only, x < 140 g transfer only, x < 200 gal both types, x < 140 gal/yr (constructed on or after 1	l/yr r	
3. Existing large area source4. New large area sourcedry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr both types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)4. New large area sourceJoint types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)Joint types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)Joint types, $140 \le x \le 1,800$ gal/yr (constructed before 12/9/91)Joint types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)Joint types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)Joint types, $140 \le x \le 1,800$ gal/yr (constructed on or after 12/9/91)				
<ul><li>facility exceeds above limits</li><li>B. The total quantity of perchloroethylene (perc) purchased within the preceding 12 months by this dry cleaning facility was 75 gallons.</li></ul>				

PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	Yes No N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	∐Yes □ No ⊠ N/A

PART IV: <u>PROCESS</u> <u>VENT</u> <u>CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
	1. If the facility classification is a <b>Existing small area source</b> , no controls are required. <b>Proceed to Part V.</b>				
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
	3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>				
	4. If the facility classification is a <u>New large area source</u> , the machine should be excondenser. Complete both sections A and B below.	quipped v	vith a ref	rigerated	
А.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each que	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	⊠Yes	No	□N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	⊠Yes	No	□N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	⊠Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	□N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No		

PA	PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)				
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ o each	only one b question)		
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes	No		
2.	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly? a) Is the temperature differential equal to, or greater than 20° F?		□ No □ No	⊠N/A ⊠ N/A	
3.	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes	🗌 No	N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes	🗌 No	N/A	
4.	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes	🗌 No	N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	Yes	🗌 No	N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes	🗌 No	N/A	

PART V: <u>RECORDKEEPING</u> <u>REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for				
Does the responsible official:	each question)			
1. Maintain receipts for perc purchased?	Yes 🗌 No			
2. Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	- Xes No N/A			
b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?	Yes No N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A			
6. Maintain a startup/shutdown/malfunction plan?	Yes 🗌 No			
7. Maintain deviation reports?	Yes No N/A			
a) Problem corrected?	- Xes No N/A			
8. Maintain a compliance plan, if applicable?	Yes No N/A			

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No			
2. Does the facility maintain a leak log?	Xes No			
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves Xes No N/A g)</li> <li>b) Door gaskets and seating Yes No N/A h)</li> <li>c) Filter gaskets and seating Yes No N/A i) E</li> <li>d) Pumps Yes No N/A j) I</li> <li>e) Solvent tanks and containers Yes No N/A k)</li> <li>f) Water separators Yes No N/A</li> </ul>	Muck cookers       Yes       No       N/A         Stills       Yes       No       N/A         Exhaust dampers       Yes       No       N/A         Diverter valves       Yes       No       N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li> <li>b) Physical detection (airflow felt through gaskets)</li> <li>c) Odor (noticeable perc odor)</li></ul>	b)          c)          tubes)         c)          d)          ** (see below)         e)          e)          **          N/A         0-500 ppm?         1)        Yes          PID/FID only)?         2)        Yes          No         sis?       4)          Yes        No			
Jeffrey Dizek	7/2/2008			
Inspector's Name (Please Print) Date of Inspection				
	7/2009			
Inspector's Signature	Approximate Date of Next Inspection			

**COMMENTS:**