

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	UAL (INS1, INS2)	COMPLAINT/D	NISCOVERY (CI)				
AIRS ID#: 0310399 DATE: 1	0/11/2013	ARRIVE: <u>1455</u>	DEPART:				
FACILITY NAME: THIRD ST	Γ CLEANERS						
FACILITY LOCATION:	1031 N 3RD ST						
	JACKSONVILLE BEAC	CH 32250-7238					
OWNER/AUTHORIZED REPRESENTATIVE: SHAILESH PATEL Email: CONTACT NAME: Email: ENTITLEMENT PERIOD: 9/8/2007 / 9/8/2012 Facility may be operating without Entitlement!							
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☑ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE							
PART II: FACILITY CLASSIFICATION - Rule 62-213.300 FAC (check ☑ only one box in A)							
 A. 1. Existing small area dry-to-dry only, x < transfer only, x < 20 both types, x < 140 g (constructed before 3. Existing large area dry-to-dry only, 140 transfer only, 200 ≤ both types, 140 ≤ (constructed before 5. Ineligible for Gend rop store/out of but facility exceeds above 	140 gal/yr 0 gal/yr 12/9/91) source	transfer only, both types, x (constructed of types, and transfer only, both types, 14	ly, x < 140 gal/yr x < 200 gal/yr < 140 gal/yr on or after 12/9/91)				
B . The sum of the volume cleaning facility was 30		perc) purchases made	e in each of the previous 12 months by this dry				

PA	RT III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC			check x for e		only o		
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A	
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A	
	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No			
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A	
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No		N/A	
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?	\boxtimes	Yes		No		N/A	
	PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page 1 of 4, this form)							
	1. If the f acility classification is an existing small area source, no controls are required. P	rocee	ed to P	art V				
	2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.							
	3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993							
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.							
A.	Has the responsible official of all <u>existing large area & new sources</u> :					only o		
1.	Equipped all machines with the appropriate vent controls?	\boxtimes	Yes		No			
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	\boxtimes	Yes		No		N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A	
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes		No		N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	\boxtimes	Yes		No			

PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)							
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?		Yes		No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?		Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?		Yes		No		N/A
	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?		Yes		No		N/A
	a) Is the perc concentration equal to, or less than 100 ppm?		Yes		No		N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?		Yes		No		N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?		Yes		No		N/A
ч							ľ
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?		Yes		No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?		((check	V	only o	one
PA			((check ox for each	V	only o	one
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC		(bo	check	☑ ach q	only o	one
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		(bo	check	☑ ach q No	only o	one
1. 2. 3.	Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained?		(bo	(check ox for each	☑ ach q No	only o	one
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes	check	☑ ach q No No	only o	one on)
1. 2. 3.	Are receipts maintained for all perc purchased?		Yes Yes Yes	check	☑ ach q No No No	only o questio	one on)
1. 2. 3. 4.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes	check	ach quantity No	only o questio	one on) N/A N/A
1. 2. 3. 4. 5.	Are receipts maintained for all perc purchased?		Yes Yes Yes Yes Yes	(check ox for each	ach q No No No No	only o questio	one nn) N/A N/A N/A
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased?		Yes Yes Yes Yes Yes	check	Mo No No No No No No	only o questio	nne nn) N/A N/A N/A
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased? ————————————————————————————————————		Yes Yes Yes Yes Yes Yes	check	No	only o questio	nne nn) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one		
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)		
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to					
	the manufacturer's instructions (manual was available and RO could demonstrate					
	procedure) ?	Yes	☐ No			
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer					
	operated according to EPA Method 21 ?	Yes	☐ No	N/A		
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of					
	each component interface where leakage could occur and moving it slowly along					
	the interface periphery?	Yes	☐ No			
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or					
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per					
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A		
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations					
	of PCE of 25 parts per million by volume (based on documented specifications) and					
	indicating a concentration of 25 parts per million by volume or greater by emitting					
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A		
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) whi	le the		
	system is in operation (§63.322(k))?					
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	ection	of perceptib	le leaks)		
	b) Door gaskets and seating Yes No N/A h) Stills Y		□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A		
8.	Are the following dry cleaning system components inspected monthly for vapor leaks using a haloge	enated	hydrocarbo	on detector		
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parag	raph sh	hall satisfy th	ne		
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))					
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes No N/A N/A N/A N/A N/A N/A Yes Yes	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A		

PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)					
9. What evidence suggests that leak checks are performed as require	ed?				
□ Leak log documentation					
Explain other:					
Brenda Johnson	11 Oct. 2013				
Inspector's Name (Please Print)	Date of Inspection				
	2014				
Inspector's Signature	Approximate Date of Next Inspection				
COMMENTS. Met with Mr. Detales are his assent of account.	tion Facility well through many damped and an electronic many				

COMMENTS: Met with Mr. Patel to review his records of operation. Facility walk through was done and no violations were noted at the time of inspection.