

PERCHLOROETHYLENE DRY CLEANERS



COMPLIANCE INSPECTION CHECKLIST

	ANNUAL (INS1, INS2) RE-INSPECTION (FUI)	COMPLAINT/E ARMS COMPL	DISCOVERY (CI) AINT NO:			
AIRS ID#: 0310405 DAT	E: <u>10/16/13</u>	ARRIVE:	DEPART:			
FACILITY NAME: JAY	'S DRY CLEANERS & LAUN	DRY				
FACILITY LOCATION:	10025 SAN JOSE BOUL	LEVARD				
	JACKSONVILLE 3225	57-5835				
OWNER/AUTHORIZED Email: kanini_4484@y CONTACT NAME: Email: ENTITLEMENT PERIO			PHONE: (904)268-8280 Mobile: PHONE: Mobile:			
PART I: INSPECTION COMPLIANCE STATUS (check ☑ only one box) ☐ IN COMPLIANCE ☐ MINOR Non-COMPLIANCE ☐ SIGNIFICANT Non-COMPLIANCE						
PART II: FACILITY CL	ASSIFICATION - Rule 62-	213.300 FAC				
	nly one box in A)					
transfer only, x both types, x < (constructed be 3. Existing large dry-to-dry only transfer only, 2 both types, 140 (constructed be 5. Ineligible for	y, $x < 140 gal/yrx < 200 gal/yrx < 140 gal/yrefore 12/9/91)area sourcey, 140 \le x \le 2,100 \text{ gal/yr}200 \le x \le 1,800 \text{ gal/yr}0 \le x \le 1,800 \text{ gal/yr}efore 12/9/91)r General Permit \squareof business/petroleum /$	transfer only, both types, x (constructed 4. New large and dry-to-dry or transfer only, both types, 1	aly, x < 140 gal/yr , x < 200 gal/yr < 140 gal/yr on or after 12/9/91)			
B . The sum of the vocleaning facility w	-	(perc) purchases mad	e in each of the previous 12 months by this dry			

PA	ART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC					only o			
1.	Is all perc, and wastes containing perc, in tightly sealed & impervious containers?	\boxtimes	Yes		No		N/A		
2.	Are all perc. containers leak free ?	\boxtimes	Yes		No		N/A		
3.	Are all machine doors kept closed and secured except during loading/unloading?	\boxtimes	Yes		No				
4.	Are cartridge filters d rained in their housing or in sealed containers for at least 24 hours prior to disposal?	\boxtimes	Yes		No		N/A		
5.	Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions.		Yes		No	\boxtimes	N/A		
6.	Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds	_				_			
	maintain according to the manufacturer's specifications?	\boxtimes	Yes	Ш	No	Ш	N/A		
PA	ART IV: PROCESS VENT CONTROLS - Rule 62-213.300 FAC								
	efer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)								
	1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.								
2. If the facility classification is a <u>new small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.									
	3. If the fa cility classification is an existing large area source , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. Complete both sections A and B below. Carbon adsorber must have been installed prior to September 22, 1993								
	4. If the facility classification is a <u>new large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.								
A.	Has the responsible official of all existing large area & new sources:					only o			
1.	Equipped all machines with the appropriate vent controls?		Yes		No				
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	\boxtimes	Yes		No		N/A		
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?		Yes		No		N/A		
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	\boxtimes	Yes		No		N/A		
5.									
	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	\boxtimes	Yes		No		N/A		

PA	ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)					
B. 1.	For all existing large or new large area sources: Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?	Yes		No		
2.	Is the washer exhaus t temperature at the condenser inlet and outlet measured and recorded weekly?	Yes		No		N/A
	a) Is the temperature differential equal to, or greater than 20° F?	Yes		No		N/A
	Is the perc concentration in the exhaust stream inlet and outlet measured weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes		No		N/A
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes		No		N/A
4.	Is the sampling port on the carbon adsorber exhaust for measuring perc concentrations at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes		No		N/A
5.	Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?	Yes		No		N/A
!]						I
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
6.	Is airflow routed to the carbon adsorber (if used) at all times?	Yes		No		N/A
	Is airflow routed to the carbon adsorber (if used) at all times?	(check ox for e		only o	ne
PA		(check ox for e		-	ne
PA	ART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC	(bo	check ox for e	☑ each c	-	ne
1. 2.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased?	(bo	check ox for e	each o	-	ne
1. 2. 3.	Are receipts maintained for all perc purchased? Are rolling monthly total s of yearly perc consumption maintained?	(bo	check ox for e	each o	-	ne
1. 2. 3.	ART V: RECORDKEEPING REQUIREMENTS – Rule 62-213.300(3) FAC Are receipts maintained for all perc purchased? ————————————————————————————————————	Yes Yes	check ox for e	each o	questio	ne n)
1. 2. 3.	Are receipts maintained for all perc purchased?	Yes Yes Yes	check ox for e	each o No No No	questio	ne n) N/A
1. 2. 3. 4.	Are receipts maintained for all perc purchased?	Yes Yes Yes	check ox for e	No No No	questio	ne n) N/A N/A
1. 2. 3. 4. 5.	Are receipts maintained for all perc purchased? ————————————————————————————————————	Yes Yes Yes Yes Yes	check ox for e	No No No No No	questio	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased?	Yes Yes Yes Yes Yes	check ox for e	No No No No No No No	questio	ne n) N/A N/A N/A
1. 2. 3. 4. 5. 6.	Are receipts maintained for all perc purchased?	Yes Yes Yes Yes Yes Yes Yes	check ox for e	No N	questio	ne n) N/A N/A N/A

PA	ART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC		(check 🗹	only one
1.	What type of leak detection equipment is used to detect leaks?	bo	ox for each	question)
	☐ Halogenated hydrocarbon detector ☐ PCE gas analyzer ☐ None used			
2.	Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to			
	the manufacturer's instructions (manual was available and RO could demonstrate			
	procedure) ?	Yes	☐ No	
3.	For major sources is the halogenated hydrocarbon detector or PCE gas analyzer			
	operated according to EPA Method 21 ?	Yes	☐ No	N/A
4.	Is the vapor leak inspection conducted by placing the probe inlet at the surface of			
	each component interface where leakage could occur and moving it slowly along			
	the interface periphery? \boxtimes	Yes	☐ No	
5.	Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or			
	infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per			
	million by volume (based on documented specifications) ?	Yes	☐ No	N/A
6.	Is the <u>halogenated hydrocarbon detector</u> capable of detecting vapor concentrations			
	of PCE of 25 parts per million by volume (based on documented specifications) and			
	indicating a concentration of 25 parts per million by volume or greater by emitting			
	an audible or visual signal that varies as the concentration changes? 🖂	Yes	☐ No	N/A
7.	Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sm	nell or	touch) while	e the
	system is in operation (§63.322(k))?			
	(Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp	pection	of perceptib	le leaks)
	b) Door gaskets and seating Yes No N/A h) Stills X		 No No No No No No No	N/AN/AN/AN/AN/AN/A
8.	Are the following dry cleaning system components inspected $\underline{monthly}$ for $\underline{vapor\ leaks}$ using a halogen $\underline{monthly}$ for $\underline{monthly}$ f	enated	hydrocarbo	on detector
	or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this paragraph of the system) of the system is in operation?	raph sl	hall satisfy th	ne e
	requirements to conduct an inspection for perceptible leaks under §63.322(k) or (l))			
	b) Door gaskets and seating Yes No N/A N/A N/A Stills Yes Yes No N/A N/A N/A N/A N/A N/A Yes	Yes Yes Yes Yes Yes	□ No□ No□ No□ No□ No	N/AN/AN/AN/AN/AN/A

PART VI: LEAK DETECTION AND REPAIRS – Rule 6	52-213.300 FAC (continued)	
9. What evidence suggests that leak checks are performed as		
William Coffman	10/16/13	
Inspector's Name (Please Print)	Date of Inspection	
Inspector's Signature	Approximate Date of Next Inspection	
COMMENTS:		