

PERCHLOROETHYLENE DRY CLEANERS



## **COMPLIANCE INSPECTION CHECKLIST**

	OMPLAINT/DISCOVERY (CI)	
AIRS ID#: 0310407 DATE: <u>3/18/10</u> ARR	IVE: DEPART:	
FACILITY NAME: VILLAGE DRY CLEANERS		
FACILITY LOCATION: 10568 St Augustine Rd		
JACKSONVILLE 32257-394	1	
OWNER/AUTHORIZED REPRESENTATIVE: SURESH P.	ATEL <b>PHONE:</b> (904)262-5493	
CONTACT NAME:	PHONE:	
ENTITLEMENT PERIOD: 11/30/2006 / 11/30/2011 (effective date) (end date)		
PART I: <u>INSPECTION COMPLIANCE STATUS</u> (check	only one box)	
IN COMPLIANCE MINOR Non-COMPLIANC	E SIGNIFICANT Non-COMPLIANCE	
PART II: FACILITY CLASSIFICATION - Rule 62-213.300	FAC	
(check ☑ only one box in A)		
A. 1. Existing small area source $\Box$ 2. dry-to-dry only, x < 140 gal/yr	<u>New small area source</u> dry-to-dry only, x < 140 gal/yr	
transfer only, x < 200 gal/yr	transfer only, $x < 200$ gal/yr	
both types, x < 140 gal/yr (constructed before 12/9/91)	both types, $x < 140$ gal/yr (constructed on or after 12/9/91)	
(constructed before 12/9/91) (constructed on or after 12/9/91)		
	New large area source $\Box$	
dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr	dry-to-dry only, $140 \le x \le 2,100$ gal/yr transfer only, $200 \le x \le 1,800$ gal/yr	
both types, $140 \le x \le 1,800$ gal/yr	both types, $140 \le x \le 1,800$ gal/yr	
(constructed before 12/9/91)	(constructed on or after 12/9/91)	
5. Ineligible for General Permit		
drop store/out of business/petroleum		
facility exceeds above limits		
<b>B</b> . The total quantity of perchloroethylene (perc) purchased cleaning facility was 0 gallons.	within the preceding 12 months by this dry	

PART III: GENERAL CONTROL REQUIREMENTS – Rule 62-213.300 FAC	(check 🗹 only one box
Does the responsible official of the dry cleaning facility:	for each question)
1. Store perc, and wastes containing perc, in tightly sealed & impervious containers?	□Yes □No ⊠N/A
2. Examine the containers for leakage?	Yes No N/A
3. Close and secure machine doors except during loading/unloading?	Yes No
4. Drain cartridge filters in their housing or in sealed containers for at least 24 hours prior to disposal?	Yes No N/A
5. Maintain solvent-to-carbon ratios and steam pressure for carbon adsorber beds according to the manufacturer's specifications?	Yes No N/A

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)					
1. If the facility classification is a <b>Existing small area source</b> , no controls are required. <b>Proceed to Part V.</b>					
	2. If the facility classification is a <u>New small area source</u> , the machine should be equipped with a refrigerated condenser. Complete section A. below.				
3. If the facility classification is a <b>Existing large area source</b> , the machine should be equipped with either a refrigerated condenser or a carbon adsorber. <b>Complete both sections A and B below.</b> <i>Carbon adsorber must have been installed prior to September 22, 1993</i>					
	4. If the facility classification is a <u>New large area source</u> , the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.				
A.	Has the responsible official of all <u>existing large area &amp; new sources</u> :		☑ only each que	one box for stion)	
1.	Equipped all machines with the appropriate vent controls?	Yes	No		
2.	Equipped dry-to-dry machines with a closed-loop vapor venting system?	Yes	No	⊠N/A	
3.	Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?	Yes	No	⊠N/A	
4.	Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?	Yes	No		
5.	Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded 45° F?	Yes	No	⊠N/A	
6.	Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged?	Yes	No		

PART IV: <u>PROCESS VENT CONTROLS</u> – Rule 62-213.300 FAC (continued)			
B.	Does the responsible official of an existing large or new large area source also:	(check ☑ only one box for each question)	
1.	Measure and record the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines on a weekly basis?	Yes No	
	Measure and record the washer exhaust temperature at the condenser inlet and outlet weekly?	- Yes No N/A	
	a) Is the temperature differential equal to, or greater than $20^{\circ}$ F?	Yes No N/A	
	Measure and record the perc concentration in the exhaust stream weekly at the end of the final drying cycle while the machine is venting to the adsorber, if machines are equipped exclusively with a carbon adsorber?	Yes No N/A	
	a) Is the perc concentration equal to, or less than 100 ppm?	Yes No N/A	
	Assure that the sampling port on the carbon adsorber exhaust for measuring perc concentrations is at least 8 duct diameters downstream of any bend, contraction, or expansion; is at least 2 duct diameters upstream from any bend, contraction, or expansion; and downstream from no other inlet?	Yes No N/A	
5.	Equip transfer machines (dryers, reclaimers, and washers) with individual condenser coils?	- Yes No N/A	
6.	Route airflow to the carbon adsorber (if used) at all times?	Yes No N/A	

PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC (check ☑ only one box for				
Does the responsible official:	each question)			
1. Maintain receipts for perc purchased?	- 🛛 Yes 🗌 No			
2. Maintain rolling monthly total of yearly perc consumption?	🛛 Yes 🗌 No			
3. Maintain leak detection inspection and repair reports for the following:				
a) documentation of leaks repaired w/in 24 hrs? or;	- 🗌 Yes 🗌 No 🖾 N/A			
<ul> <li>b) documentation of parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt?</li> </ul>	☐ Yes ☐ No 🖾 N/A			
4. Maintain calibration data? (for applicable direct reading instruments)	Yes No N/A			
5. Maintain exhaust duct monitoring data on perc concentrations?	Yes No N/A			
6. Maintain a startup/shutdown/malfunction plan?	Yes No			
7. Maintain deviation reports?	- Yes No N/A			
a) Problem corrected?	- 🗌 Yes 🗌 No 🖾 N/A			
8. Maintain a compliance plan, if applicable?	- Yes No N/A			

## PART VI: <u>LEAK DETECTION AND REPAIRS</u> – Rule 62-213.300 FAC

1. Does the responsible official conduct a weekly (for small sources, bi-weekly) leak

(check ☑ only one box for each question)

detection and repair inspection?	Xes No			
2. Does the facility maintain a leak log?	Xes No			
<ul> <li>3. Does the responsible official check the following areas for leaks?</li> <li>a) Hose connections, fittings, couplings, and valves</li> <li>b) Door gaskets and seating</li> <li>c) Filter gaskets and seating</li> <li>d) Pumps</li> <li>e) Solvent tanks and containers</li> <li>f) Water separators</li> <li>Yes □No ⊠N/A</li> <li>Yes □No ⊠N/A k) Carther f) Water separators</li> </ul>	Yes       No       N/A         ust dampers       Yes       No       N/A         ter valves       Yes       No       N/A			
4. Which method(s) of detection (is/are) used by the responsible official?				
<ul> <li>a) Visual examination (condensed solvent on exterior surfaces)</li></ul>				
William Coffman	3/18/2010			
Inspector's Name (Please Print)	Date of Inspection			
1	N/A			
Inspector's Signature	Approximate Date of Next Inspection			

**COMMENTS:** Facility no longer does Dry Cleaning Used as drop Site Only