| OWNERTAL PROTECTION |  |
|---------------------|--|
| Some Course         |  |
| FLORIDA             |  |
|                     |  |

PERCHLOROETHYLENE DRY CLEANERS



## **COMPLIANCE INSPECTION CHECKLIST**

| INSPECTION TYPE:       ANNUAL (INS1, INS2)       COMPLAINT/DISCOVERY (CI)         RE-INSPECTION (FUI)       ARMS COMPLAINT NO:  |
|---|
| AIRS ID#: 0310407 DATE: 10/09/13       ARRIVE:       DEPART:  |
| FACILITY NAME: VILLAGE DRY CLEANERS   |
| FACILITY LOCATION: 10568 St Augustine Rd  |
| JACKSONVILLE 32257-3941   |
| OWNER/AUTHORIZED REPRESENTATIVE:       SURESH PATEL       PHONE:       (904)262-5493         Email:       Mobile:         CONTACT NAME:       PHONE:         Email:       Mobile:         Email:       Mobile:         Email:       Mobile:         Email:       Mobile:         Email:       Mobile:         (effective date)       (end date)   |
|   |
| PART I: INSPECTION COMPLIANCE STATUS (check   |
| PART II:FACILLITY CLASSIFICATION<br>(check $\square$ only one box in A)- Rule 62-213.300 FACA. 1.Existing small area source<br>dry-to-dry only, x < 140 gal/yr<br>transfer only, x < 200 gal/yr<br>both types, x < 140 gal/yr<br>(constructed before 12/9/91)2.New small area source<br>dry-to-dry only, x < 140 gal/yr<br>transfer only, x < 200 gal/yr<br>both types, x < 140 gal/yr<br>(constructed before 12/9/91)2.New small area source<br>dry-to-dry only, x < 140 gal/yr<br>transfer only, x < 200 gal/yr<br>both types, x < 140 gal/yr<br>(constructed before 12/9/91)2.New small area source<br>dry-to-dry only, x < 140 gal/yr<br>both types, x < 140 gal/yr<br>(constructed on or after 12/9/91)3.Existing large area source<br>dry-to-dry only, 140 $\leq x \leq 2$ ,100 gal/yr<br>transfer only, 200 $\leq x \leq 1$ ,800 gal/yr<br>(constructed before 12/9/91)4.New large area source<br>dry-to-dry only, 140 $\leq x \leq 2$ ,100 gal/yr<br>transfer only, 200 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to th types, 140 $\leq x \leq 1$ ,800 gal/yr<br>to the type, 140 $\leq x \leq 1$ ,800 gal/yr<br>to the type, 140 $\leq x \leq 1$ ,800 gal/yr<br>to the type, 140 $\leq x \leq 1$ ,800 gal/yr<br>to the type, 140 $\leq x \leq 1$ ,800 gal/yr <br< th=""></br<> |

cleaning facility was 0.00 gallons.

| PART III: <u>GENERAL CONTROL REQUIREMENTS</u> – Rule 62-213.300 FAC  | `   | check ☑<br>x for each q | only one<br>[uestion] |
|--|-----|-------------------------|-----------------------|
| 1. Is all perc, and wastes containing perc, in tightly sealed & impervious containers?   | Yes | 🗌 No                    | N/A                   |
| 2. Are all perc. containers leak free ?  | Yes | 🗌 No                    | N/A                   |
| 3. Are all machine doors kept closed and secured except during loading/unloading?  | Yes | 🗌 No                    |                       |
| <ol> <li>Are cartridge filters d rained in their housing or in sealed containers for at least<br/>24 hours prior to disposal?</li> </ol>   | Yes | 🗌 No                    | N/A                   |
| 5. Has each dry cleaning system installed after December 21, 2005 at an area source, routed the air-PCE gas-vapor stream contained within each dry cleaning machine through a refrigerated condenser and passed the air-PCE gas-vapor stream from inside the dry cleaning machine drum through a non-vented carbon adsorber or equivalent control device immediately before the door of the dry cleaning machine is opened? The carbon adsorber must be desorbed in accordance with manufacturer's instructions. | Yes | □ No                    | □ N/A                 |
| <ul> <li>6. Is solvent-to-carbon ratios and steam pressure for carbon adsorber beds maintain according to the manufacturer's specifications?</li> </ul>  | Yes | □ No                    | □ N/A                 |
|  |     |                         |                       |
| PART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (Refer to Part II-A.14. Classification: page <u>1</u> of <u>4</u> , this form)  |     |                         |                       |

1. If the f acility classification is an existing small area source, no controls are required. Proceed to Part V.

2. If the facility classification is a <u>new small area source</u>, the machine should be equipped with a refrigerated condenser. Complete section A. below.

3. If the fa cility classification is an **existing large area source**, the machine should be equipped with either a refrigerated condenser or a carbon adsorber. **Complete both sections A and B below.** *Carbon adsorber must have been installed prior to September 22, 1993* 

4. If the facility classification is a <u>new large area source</u>, the machine should be equipped with a refrigerated condenser. Complete both sections A and B below.

| A. | Has the responsible official of all <u>existing large area &amp; new sources</u> :   | `   | heck 🗹<br>theck to the form | only one<br>[uestion) |
|----|--|-----|-----------------------------|-----------------------|
| 1. | Equipped all machines with the appropriate vent controls?  | Yes | 🗌 No                        |                       |
| 2. | Equipped dry-to-dry machines with a closed-loop vapor venting system?  | Yes | 🗌 No                        | N/A                   |
| 3. | Equipped the condenser with a diverter valve so airflow will be directed away from the condenser upon opening the door?                      | Yes | 🗌 No                        | N/A                   |
| 4. | Measured and recorded the temperature of the outlet exhaust stream of a refrigerated condenser on a weekly basis?                            | Yes | 🗌 No                        | N/A                   |
| 5. | Repaired or adjusted the equipment within 24 hours if the exhaust temperature of the condenser exceeded $45^{\circ}$ F?                      | Yes | 🗌 No                        | N/A                   |
| 6. | Conducted all temperature monitoring after an appropriate cool-down period and after verifying that the coolant had been completely charged? | Yes | 🗌 No                        |                       |

| PA              | ART IV: PROCESS VENT CONTROLS – Rule 62-213.300 FAC (continued)   |            |      |         |
|-----------------|---|------------|------|---------|
| <b>B.</b><br>1. | <b>For all existing large or new large area sources:</b><br>Is the exhaust temperature on the outlet side of the condenser located on dry-to-dry, reclaimer, and dryer machines measured and recorded on a weekly basis?  | Yes        | 🗌 No |         |
| 2.              | Is the washer exhaus t temperature at the condenser inlet and outlet measured<br>and recorded weekly?<br>a) Is the temperature differential equal to, or greater than 20° F?  | Yes<br>Yes | D No | N/A N/A |
| 3.              | Is the perc concentration in the exhaust stream inlet and outlet measured weekly<br>at the end of the final drying cycle while the machine is venting to the adsorber,<br>if machines are equipped exclusively with a carbon adsorber?  | Yes        | 🗌 No | N/A     |
|                 | a) Is the perc concentration equal to, or less than 100 ppm?  | Yes        | 🗌 No | N/A     |
| 4.              | Is the sampling port on the carbon adsorber exhaust for measuring<br>perc concentrations at least 8 duct diameters downstream of any bend,<br>contraction, or expansion; is at least 2 duct diameters upstream from any bend,<br>contraction, or expansion; and downstream from no other inlet? | Yes        | 🗌 No | □ N/A   |
| 5.              | Are transfer machines equipped (dryers, reclaimers, and washers) with individual condenser coils?   | Yes        | 🗌 No | N/A     |
| 6.              | Is airflow routed to the carbon adsorber (if used) at all times?  | Yes        | 🗌 No | N/A     |

| PART V: <u>RECORDKEEPING REQUIREMENTS</u> – Rule 62-213.300(3) FAC   |     | check ☑<br>k for each c | only one (uestion) |
|--|-----|-------------------------|--------------------|
| 1. Are receipts maintained for all perc purchased?   | Yes | 🗌 No                    |                    |
| 2. Are rolling monthly total s of yearly perc consumption maintained ?   | Yes | 🗌 No                    |                    |
| 3. Are leak detection inspection and repair reports maintained for the following:                                |     |                         |                    |
| a) Of any leaks repaired w/in 24 hrs? or;  | Yes | 🗌 No                    | N/A                |
| b) Of any parts ordered to repair leak and leak repaired w/in 2 days and parts installed w/in 5 days of receipt? | Yes | 🗌 No                    | □ N/A              |
| 4. Is calibration data maintained for applicable direct reading instruments?                                     | Yes | 🗌 No                    | N/A                |
| 5. Is exhaust duct monitoring data on perc concentrations maintained?  | Yes | 🗌 No                    | N/A                |
| 6. Is a startup/shutdown/malfunction plan maintained for each machine?   | Yes | 🗌 No                    |                    |
| 7. Are deviation reports maintained?   | Yes | 🗌 No                    | N/A                |
| a) Problem corrected?  | Yes | 🗌 No                    | N/A                |
| 8. Is a compliance plan maintained, if applicable?   | Yes | 🗌 No                    | N/A                |
|  |     |                         |                    |

| P  | ART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC  | (check 🗹 only one   |
|----|---|---|
| 1. | What type of leak detection equipment is used to detect leaks?  | box for each question)  |
|    | Halogenated hydrocarbon detector PCE gas analyzer None used   |   |
| 2. | Is the halogenated hydrocarbon detector or PCE gas analyzer operated according to   |   |
|    | the manufacturer's instructions (manual was available and RO could demonstrate  |   |
|    | procedure) ?  | Yes 🗌 No  |
| 3. | For major sources is the halogenated hydrocarbon detector or PCE gas analyzer   |   |
|    | operated according to EPA Method 21 ?   | Yes No N/A  |
| 4. | Is the vapor leak inspection conducted by placing the probe inlet at the surface of   |   |
|    | each component interface where leakage could occur and moving it slowly along   |   |
|    | the interface periphery?  | Yes 🗌 No  |
| 5. | Is the PCE gas analyzer a flame ionization detector, photo ionization detector, or  |   |
|    | infrared analyzer capable of detecting vapor concentrations of PCE of 25 parts per  |   |
|    | million by volume (based on documented specifications) ?  | Yes No N/A  |
| 6. | Is the halogenated hydrocarbon detector capable of detecting vapor concentrations   |   |
|    | of PCE of 25 parts per million by volume (based on documented specifications) and   |   |
|    | indicating a concentration of 25 parts per million by volume or greater by emitting   |   |
|    | an audible or visual signal that varies as the concentration changes?   | Yes No N/A  |
| 7. | Are the following dry cleaning system components inspected weekly for perceptible leaks (sight, sn  | nell or touch) while the  |
|    | system is in operation (§63.322(k))?  |   |
|    | (Inspection with a halogenated hydrocarbon detector or PCE gas analyzer also fulfills the requirement for insp  | pection of perceptible leaks)   |
|    | b) Door gaskets and seating       Yes       No       N/A       h) Stills       C)         c) Filter gaskets and seating       Yes       No       N/A       i) Exhaust dampers       C)         d) Pumps       Yes       No       N/A       j) Diverter valves       Yes | Yes       No       N/A         Yes       No       N/A |
| 8. | Are the following dry cleaning system components inspected monthly for vapor leaks using a halog  | enated hydrocarbon detector   |
|    | or PCE gas analyzer while the system is in operation? (Any inspection conducted according to this parage  | raph shall satisfy the  |
|    | requirements to conduct an inspection for perceptible leaks under $(3.322(k) \text{ or } (l))$  |   |
|    | b) Door gaskets and seating       Yes       No       N/A       h) Stills       C)         c) Filter gaskets and seating       Yes       No       N/A       i) Exhaust dampers       C)         d) Pumps       Yes       No       N/A       j) Diverter valves       Yes | Yes       No       N/A         Yes       No       N/A |

| PART VI: LEAK DETECTION AND REPAIRS – Rule 62-213.300 FAC (continued)  |                                     |  |  |  |  |  |
|--|-------------------------------------|--|--|--|--|--|
| <ul> <li>9. What evidence suggests that leak checks are performed as required?</li> <li>Leak log documentation RO Assurances On-site observation other</li> <li>Explain other :</li> </ul> |                                     |  |  |  |  |  |
| William Coffman  | 10/09/13                            |  |  |  |  |  |
| Inspector's Name (Please Print)  | Date of Inspection                  |  |  |  |  |  |
| Inspector's Signature  | Approximate Date of Next Inspection |  |  |  |  |  |
| <b>COMMENTS:</b> Facility now a drop site. No perc machine on s  | site                                |  |  |  |  |  |